

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	ACICLO200MG STV11A00
User ID :	pb97604	Batch NO. :	VIM2500220
Print Interval :	50000 Tablets	Running Time :	01 Hour 46 Min 05 Sec
Total Counter :	300206	Total Running Time :	354 Hour 52 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	79	%	Manual ;	45	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		1740000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.3	Sec
Lower Punch Interval Time(S2) ;		60	Min	Supply Time ;	0.3	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	12.09	kN	No		
HEP :	25.0 %	11.63	kN	Yes	10 Rotations	10 Tablets
HCP :	2.0 %	9.49	kN	Yes	10 Times	
Ref :		9.30	kN			
LCP :	2.0 %	9.12	kN	Yes	10 Times	
LEP :	25.0 %	6.98	kN	Yes	10 Rotations	10 Tablets
LSP :	30.0 %	6.51	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	1.75	kN	Min :	1.73	kN	Punch NO.;	5
SD :	0.60	%	Max :	1.78	kN	Punch NO.;	33
Mean Main Pressure :	9.48	kN	Min :	9.19	kN	Punch NO.;	34
SD :	1.50	%	Max :	9.87	kN	Punch NO.;	38
Filling Depth :	Increase ;	6	Times	Decrease ;	32	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	25	RPM	Capacity :	195000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	20	RPM
Pre Upper Punch Position ;	2.50	mm			
Pre Lower Punch Position ;	6.00	mm	Pre Thickness ;	3.50	mm
Main Upper Punch Position ;	2.50	mm			
Main Lower Punch Position ;	3.96	mm	Main Thickness ;	1.46	mm
Filling Depth :	5.63	mm	Current Cam :	Cam B	
Main Air pressure :	0.823	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	30	Min			
Lower Punch Remain Time (S2):	52	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.02	kN		
	Max ;	0.05	kN	Max Punch ;	54
Lower Punch :	Average ;	0.08	kN		
	Max ;	0.13	kN	Max Punch ;	25
Ejection Force :	Average ;	0.05	kN		
	Max ;	0.07	kN	Max Punch ;	37

Tablet Data (N/A)

Total Counter :	300206	Tablets			
A.W.C Counter :	284457	Tablets			
HEP :	46 (0.0%)	Tablets	LEP :	46 (0.0%)	Tablets
GOOD :	284365 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	ACICLO200MG STV11A00
User ID :	pb97604	Batch NO. :	VIM2500220
Print Interval :	50000 Tablets	Running Time :	01 Hour 46 Min 05 Sec
Total Counter :	300206	Total Running Time :	354 Hour 52 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	80	%	Manual ;	59	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		1740000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.3	Sec
Lower Punch Interval Time(S2) ;		60	Min	Supply Time ;	0.3	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	12.85	kN	No		
HEP :	25.0 %	12.36	kN	Yes	10 Rotations	10 Tablets
HCP :	2.0 %	10.09	kN	Yes	10 Times	
Ref :		9.89	kN			
LCP :	2.0 %	9.69	kN	Yes	10 Times	
LEP :	25.0 %	7.42	kN	Yes	10 Rotations	10 Tablets
LSP :	30.0 %	6.92	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	1.52	kN	Min :	1.49	kN	Punch NO.;	9
SD :	0.90	%	Max :	1.56	kN	Punch NO.;	43
Mean Main Pressure :	9.91	kN	Min :	9.30	kN	Punch NO.;	13
SD :	2.20	%	Max :	10.36	kN	Punch NO.;	31
Filling Depth :	Increase ;	13	Times	Decrease ;	31	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	25	RPM	Capacity :	195000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	20	RPM
Pre Upper Punch Position ;	2.50	mm			
Pre Lower Punch Position ;	6.00	mm	Pre Thickness ;	3.50	mm
Main Upper Punch Position ;	2.50	mm			
Main Lower Punch Position ;	4.00	mm	Main Thickness ;	1.50	mm
Filling Depth :	5.87	mm	Current Cam :	Cam B 4.5-10mm	
Main Air pressure :	0.823	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	30	Min			
Lower Punch Remain Time (S2):	52	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.02	kN		
	Max ;	0.05	kN	Max Punch ;	54
Lower Punch :	Average ;	0.08	kN		
	Max ;	0.13	kN	Max Punch ;	8
Ejection Force :	Average ;	0.05	kN		
	Max ;	0.08	kN	Max Punch ;	37

Tablet Data (N/A)

Total Counter :	300206	Tablets			
A.W.C Counter :	284457	Tablets			
HEP :	46 (0.0%)	Tablets	LEP :	46 (0.0%)	Tablets
GOOD :	284365 (100.0%)	Tablets			