

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	ACICLO200MG STV11A00
User ID :	ka89411	Batch NO. :	VIM2500220
Print Interval :	50000 Tablets	Running Time :	05 Hour 31 Min 30 Sec
Total Counter :	1000538	Total Running Time :	358 Hour 38 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	74	%	Manual ;	45	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		1740000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.3	Sec
Lower Punch Interval Time(S2) ;		60	Min	Supply Time ;	0.3	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	12.28	kN	No		
HEP :	25.0 %	11.80	kN	Yes 10	Rotations 10	Tablets
HCP :	2.0 %	9.63	kN	Yes 10	Times	
Ref :		9.44	kN			
LCP :	2.0 %	9.25	kN	Yes 10	Times	
LEP :	25.0 %	7.08	kN	Yes 10	Rotations 10	Tablets
LSP :	30.0 %	6.61	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	1.71	kN	Min :	1.69	kN	Punch NO.;	13
SD :	0.50	%	Max :	1.74	kN	Punch NO.;	40
Mean Main Pressure :	9.42	kN	Min :	8.98	kN	Punch NO.;	47
SD :	2.10	%	Max :	9.89	kN	Punch NO.;	38
Filling Depth :	Increase ; 7	Times	Decrease ; 35	Times			

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	156000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	15	RPM
Pre Upper Punch Position ;	2.50	mm			
Pre Lower Punch Position ;	6.00	mm	Pre Thickness ;	3.50	mm
Main Upper Punch Position ;	2.50	mm			
Main Lower Punch Position ;	3.96	mm	Main Thickness ;	1.46	mm
Filling Depth :	6.05	mm	Current Cam :	Cam B	
Main Air pressure :	0.805	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	48	Min			
Lower Punch Remain Time (S2):	10	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.02	kN		
	Max ;	0.09	kN	Max Punch ;	53
Lower Punch :	Average ;	0.08	kN		
	Max ;	0.12	kN	Max Punch ;	16
Ejection Force :	Average ;	0.05	kN		
	Max ;	0.07	kN	Max Punch ;	59

Tablet Data (N/A)

Total Counter :	1000538	Tablets			
A.W.C Counter :	979340	Tablets			
HEP :	46 (0.0%)	Tablets	LEP :	46 (0.0%)	Tablets
GOOD :	979248 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	ACICLO200MG STV11A00
User ID :	ka89411	Batch NO. :	VIM2500220
Print Interval :	50000 Tablets	Running Time :	05 Hour 31 Min 30 Sec
Total Counter :	1000538	Total Running Time :	358 Hour 38 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	74	%	Manual ;	59	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		1740000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.3	Sec
Lower Punch Interval Time(S2) ;		60	Min	Supply Time ;	0.3	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	12.75	kN	No		
HEP :	25.0 %	12.26	kN	Yes	10 Rotations	10 Tablets
HCP :	2.0 %	10.00	kN	Yes	10 Times	
Ref :		9.80	kN			
LCP :	2.0 %	9.61	kN	Yes	10 Times	
LEP :	25.0 %	7.35	kN	Yes	10 Rotations	10 Tablets
LSP :	30.0 %	6.86	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	1.49	kN	Min :	1.46	kN	Punch NO.;	59
SD :	0.90	%	Max :	1.52	kN	Punch NO.;	16
Mean Main Pressure :	9.91	kN	Min :	9.31	kN	Punch NO.;	23
SD :	2.50	%	Max :	10.57	kN	Punch NO.;	30
Filling Depth :	Increase ;	16	Times	Decrease ;	38	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	156000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	15	RPM
Pre Upper Punch Position ;	2.50	mm			
Pre Lower Punch Position ;	6.00	mm	Pre Thickness ;	3.50	mm
Main Upper Punch Position ;	2.50	mm			
Main Lower Punch Position ;	4.00	mm	Main Thickness ;	1.50	mm
Filling Depth :	5.94	mm	Current Cam :	Cam B 4.5-10mm	
Main Air pressure :	0.805	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	48	Min			
Lower Punch Remain Time (S2):	10	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.02	kN		
	Max ;	0.09	kN	Max Punch ;	53
Lower Punch :	Average ;	0.08	kN		
	Max ;	0.13	kN	Max Punch ;	25
Ejection Force :	Average ;	0.05	kN		
	Max ;	0.07	kN	Max Punch ;	59

Tablet Data (N/A)

Total Counter :	1000538	Tablets			
A.W.C Counter :	979340	Tablets			
HEP :	46 (0.0%)	Tablets	LEP :	46 (0.0%)	Tablets
GOOD :	979248 (100.0%)	Tablets			