

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	ACICLO400MG STV11B00
User ID :	pb97604	Batch NO. :	VIM2500140
Print Interval :	50000 Tablets	Running Time :	02 Hour 47 Min 28 Sec
Total Counter :	500352	Total Running Time :	366 Hour 12 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	89	%	Manual ;	45	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		1500000	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.3	Sec
Lower Punch Interval Time(S2) ;		60	Min	Supply Time ;	0.3	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	19.41	kN	No		
HEP :	25.0 %	18.67	kN	Yes	10 Rotations	10 Tablets
HCP :	2.0 %	15.23	kN	Yes	10 Times	
Ref :		14.93	kN			
LCP :	2.0 %	14.64	kN	Yes	10 Times	
LEP :	25.0 %	11.20	kN	Yes	10 Rotations	10 Tablets
LSP :	30.0 %	10.45	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	2.45	kN	Min :	2.38	kN	Punch NO.;	34
SD :	1.40	%	Max :	2.54	kN	Punch NO.;	59
Mean Main Pressure :	14.96	kN	Min :	14.38	kN	Punch NO.;	12
SD :	1.60	%	Max :	15.54	kN	Punch NO.;	43
Filling Depth :	Increase ; 4	Times	Decrease ;	13	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	25	RPM	Capacity :	195000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	22	RPM
Pre Upper Punch Position ;	2.50	mm			
Pre Lower Punch Position ;	6.00	mm	Pre Thickness ;	3.50	mm
Main Upper Punch Position ;	2.50	mm			
Main Lower Punch Position ;	4.44	mm	Main Thickness ;	1.94	mm
Filling Depth :	7.19	mm	Current Cam :	Cam C	
Main Air pressure :	0.829	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	11	Min			
Lower Punch Remain Time (S2):	53	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.00	kN		
	Max ;	0.01	kN	Max Punch ;	26
Lower Punch :	Average ;	0.13	kN		
	Max ;	0.16	kN	Max Punch ;	11
Ejection Force :	Average ;	0.08	kN		
	Max ;	0.11	kN	Max Punch ;	12

Tablet Data (N/A)

Total Counter :	500352	Tablets			
A.W.C Counter :	490831	Tablets			
HEP :	43 (0.0%)	Tablets	LEP :	125 (0.0%)	Tablets
GOOD :	490663 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	ACICLO400MG STV11B00
User ID :	pb97604	Batch NO. :	VIM2500140
Print Interval :	50000 Tablets	Running Time :	02 Hour 47 Min 28 Sec
Total Counter :	500352	Total Running Time :	366 Hour 12 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	89	%	Manual ;	59	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		1500000	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.3	Sec
Lower Punch Interval Time(S2) ;		60	Min	Supply Time ;	0.3	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	20.02	kN	No		
HEP :	25.0 %	19.25	kN	Yes	10 Rotations	10 Tablets
HCP :	2.0 %	15.71	kN	Yes	10 Times	
Ref :		15.40	kN			
LCP :	2.0 %	15.09	kN	Yes	10 Times	
LEP :	25.0 %	11.55	kN	Yes	10 Rotations	10 Tablets
LSP :	30.0 %	10.78	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	2.43	kN	Min :	2.33	kN	Punch NO.;	63
SD :	1.80	%	Max :	2.56	kN	Punch NO.;	46
Mean Main Pressure :	15.44	kN	Min :	14.90	kN	Punch NO.;	9
SD :	2.00	%	Max :	16.41	kN	Punch NO.;	43
Filling Depth :	Increase ;	1	Times	Decrease ;	12	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	25	RPM	Capacity :	195000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	22	RPM
Pre Upper Punch Position ;	2.50	mm			
Pre Lower Punch Position ;	6.00	mm	Pre Thickness ;	3.50	mm
Main Upper Punch Position ;	2.50	mm			
Main Lower Punch Position ;	4.52	mm	Main Thickness ;	2.02	mm
Filling Depth :	7.46	mm	Current Cam :	Cam C	
Main Air pressure :	0.829	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	11	Min			
Lower Punch Remain Time (S2):	53	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0
Lower Punch :	Average ;	0.13	kN		
	Max ;	0.16	kN	Max Punch ;	11
Ejection Force :	Average ;	0.08	kN		
	Max ;	0.11	kN	Max Punch ;	12

Tablet Data (N/A)

Total Counter :	500352	Tablets			
A.W.C Counter :	490831	Tablets			
HEP :	43 (0.0%)	Tablets	LEP :	125 (0.0%)	Tablets
GOOD :	490663 (100.0%)	Tablets			