

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	ACICLO400MG STV11B00
User ID :	yu98249	Batch NO. :	VIM2500140
Print Interval :	50000 Tablets	Running Time :	08 Hour 15 Min 32 Sec
Total Counter :	1400698	Total Running Time :	371 Hour 40 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	89	%	Manual ;	45	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		1500000	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.3	Sec
Lower Punch Interval Time(S2) ;		60	Min	Supply Time ;	0.3	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	19.80	kN	No		
HEP :	25.0 %	19.04	kN	Yes 10	Rotations 10	Tablets
HCP :	2.0 %	15.54	kN	Yes 10	Times	
Ref :		15.23	kN			
LCP :	2.0 %	14.93	kN	Yes 10	Times	
LEP :	25.0 %	11.43	kN	Yes 10	Rotations 10	Tablets
LSP :	30.0 %	10.66	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	2.76	kN	Min :	2.69	kN	Punch NO.;	63
SD :	1.00	%	Max :	2.83	kN	Punch NO.;	27
Mean Main Pressure :	15.24	kN	Min :	14.57	kN	Punch NO.;	14
SD :	1.80	%	Max :	15.80	kN	Punch NO.;	5
Filling Depth :	Increase ; 5	Times	Decrease ;	27	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	156000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	18	RPM
Pre Upper Punch Position ;	2.50	mm			
Pre Lower Punch Position ;	6.00	mm	Pre Thickness ;	3.50	mm
Main Upper Punch Position ;	2.50	mm			
Main Lower Punch Position ;	4.44	mm	Main Thickness ;	1.94	mm
Filling Depth :	7.29	mm	Current Cam :	Cam C	
Main Air pressure :	0.794	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	4	Min			
Lower Punch Remain Time (S2):	26	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.03	kN		
	Max ;	0.11	kN	Max Punch ;	23
Lower Punch :	Average ;	0.12	kN		
	Max ;	0.17	kN	Max Punch ;	12
Ejection Force :	Average ;	0.03	kN		
	Max ;	0.08	kN	Max Punch ;	12

Tablet Data (N/A)

Total Counter :	1400698	Tablets			
A.W.C Counter :	1388242	Tablets			
HEP :	142 (0.0%)	Tablets	LEP :	164 (0.0%)	Tablets
GOOD :	1387936 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	ACICLO400MG STV11B00
User ID :	yu98249	Batch NO. :	VIM2500140
Print Interval :	50000 Tablets	Running Time :	08 Hour 15 Min 32 Sec
Total Counter :	1400698	Total Running Time :	371 Hour 40 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	89	%	Manual ;	59	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		1500000	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.3	Sec
Lower Punch Interval Time(S2) ;		60	Min	Supply Time ;	0.3	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	19.70	kN	No		
HEP :	25.0 %	18.94	kN	Yes 10	Rotations 10	Tablets
HCP :	2.0 %	15.46	kN	Yes 10	Times	
Ref :		15.16	kN			
LCP :	2.0 %	14.85	kN	Yes 10	Times	
LEP :	25.0 %	11.37	kN	Yes 10	Rotations 10	Tablets
LSP :	30.0 %	10.61	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	2.42	kN	Min :	2.34	kN	Punch NO.;	32
SD :	1.70	%	Max :	2.51	kN	Punch NO.;	46
Mean Main Pressure :	15.30	kN	Min :	14.72	kN	Punch NO.;	12
SD :	2.10	%	Max :	15.96	kN	Punch NO.;	30
Filling Depth :	Increase ;	8	Times	Decrease ;	19	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	156000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	18	RPM
Pre Upper Punch Position ;	2.50	mm			
Pre Lower Punch Position ;	6.00	mm	Pre Thickness ;	3.50	mm
Main Upper Punch Position ;	2.50	mm			
Main Lower Punch Position ;	4.52	mm	Main Thickness ;	2.02	mm
Filling Depth :	7.46	mm	Current Cam :	Cam C	
Main Air pressure :	0.794	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	4	Min			
Lower Punch Remain Time (S2):	26	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.03	kN		
	Max ;	0.11	kN	Max Punch ;	23
Lower Punch :	Average ;	0.12	kN		
	Max ;	0.17	kN	Max Punch ;	12
Ejection Force :	Average ;	0.03	kN		
	Max ;	0.08	kN	Max Punch ;	12

Tablet Data (N/A)

Total Counter :	1400698	Tablets			
A.W.C Counter :	1388242	Tablets			
HEP :	142 (0.0%)	Tablets	LEP :	164 (0.0%)	Tablets
GOOD :	1387936 (100.0%)	Tablets			