

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	ACICLO400MG STV11B00
User ID :	pb97604	Batch NO. :	VIM2500240
Print Interval :	50000 Tablets	Running Time :	02 Hour 46 Min 52 Sec
Total Counter :	500316	Total Running Time :	374 Hour 56 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	89	%	Manual ;	45	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		1500000	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.3	Sec
Lower Punch Interval Time(S2) ;		60	Min	Supply Time ;	0.3	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	18.71	kN	No		
HEP :	25.0 %	17.99	kN	Yes	10 Rotations	10 Tablets
HCP :	2.0 %	14.68	kN	Yes	10 Times	
Ref :		14.40	kN			
LCP :	2.0 %	14.11	kN	Yes	10 Times	
LEP :	25.0 %	10.80	kN	Yes	10 Rotations	10 Tablets
LSP :	30.0 %	10.08	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	2.64	kN	Min :	2.55	kN	Punch NO.;	63
SD :	1.40	%	Max :	2.74	kN	Punch NO.;	27
Mean Main Pressure :	14.53	kN	Min :	14.05	kN	Punch NO.;	9
SD :	1.70	%	Max :	15.24	kN	Punch NO.;	36
Filling Depth :	Increase ;	15	Times	Decrease ;	43	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	25	RPM	Capacity :	195000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	22	RPM
Pre Upper Punch Position ;	2.50	mm			
Pre Lower Punch Position ;	6.00	mm	Pre Thickness ;	3.50	mm
Main Upper Punch Position ;	2.50	mm			
Main Lower Punch Position ;	4.49	mm	Main Thickness ;	1.99	mm
Filling Depth :	7.93	mm	Current Cam :	Cam C 8.5-14mm	
Main Air pressure :	0.793	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	55	Min			
Lower Punch Remain Time (S2):	17	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.00	kN		
	Max ;	0.03	kN	Max Punch ;	24
Lower Punch :	Average ;	0.13	kN		
	Max ;	0.16	kN	Max Punch ;	11
Ejection Force :	Average ;	0.06	kN		
	Max ;	0.10	kN	Max Punch ;	12

Tablet Data (N/A)

Total Counter :	500316	Tablets			
A.W.C Counter :	490297	Tablets			
HEP :	0 (0%)	Tablets	LEP :	22 (0.0%)	Tablets
GOOD :	490275 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	ACICLO400MG STV11B00
User ID :	pb97604	Batch NO. :	VIM2500240
Print Interval :	50000 Tablets	Running Time :	02 Hour 46 Min 52 Sec
Total Counter :	500316	Total Running Time :	374 Hour 56 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	89	%	Manual ;	59	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		1500000	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.3	Sec
Lower Punch Interval Time(S2) ;		60	Min	Supply Time ;	0.3	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	19.80	kN	No		
HEP :	25.0 %	19.04	kN	Yes	10 Rotations	10 Tablets
HCP :	2.0 %	15.54	kN	Yes	10 Times	
Ref :		15.23	kN			
LCP :	2.0 %	14.93	kN	Yes	10 Times	
LEP :	25.0 %	11.42	kN	Yes	10 Rotations	10 Tablets
LSP :	30.0 %	10.66	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	2.52	kN	Min :	2.43	kN	Punch NO.;	63
SD :	1.70	%	Max :	2.64	kN	Punch NO.;	9
Mean Main Pressure :	15.29	kN	Min :	14.68	kN	Punch NO.;	47
SD :	1.80	%	Max :	16.10	kN	Punch NO.;	30
Filling Depth :	Increase ;	12	Times	Decrease ;	25	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	25	RPM	Capacity :	195000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	22	RPM
Pre Upper Punch Position ;	2.50	mm			
Pre Lower Punch Position ;	6.00	mm	Pre Thickness ;	3.50	mm
Main Upper Punch Position ;	2.50	mm			
Main Lower Punch Position ;	4.53	mm	Main Thickness ;	2.03	mm
Filling Depth :	7.82	mm	Current Cam :	Cam C	
Main Air pressure :	0.793	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	55	Min			
Lower Punch Remain Time (S2):	17	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.00	kN		
	Max ;	0.03	kN	Max Punch ;	24
Lower Punch :	Average ;	0.13	kN		
	Max ;	0.16	kN	Max Punch ;	11
Ejection Force :	Average ;	0.06	kN		
	Max ;	0.10	kN	Max Punch ;	12

Tablet Data (N/A)

Total Counter :	500316	Tablets			
A.W.C Counter :	490297	Tablets			
HEP :	0 (0%)	Tablets	LEP :	22 (0.0%)	Tablets
GOOD :	490275 (100.0%)	Tablets			