

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	ACICLO400MG STV11B00
User ID :	pb97604	Batch NO. :	VIM2500240
Print Interval :	50000 Tablets	Running Time :	04 Hour 23 Min 13 Sec
Total Counter :	800418	Total Running Time :	376 Hour 32 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	89	%	Manual ;	45	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		1500000	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.3	Sec
Lower Punch Interval Time(S2) ;		60	Min	Supply Time ;	0.3	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	18.82	kN	No		
HEP :	25.0 %	18.09	kN	Yes 10	Rotations 10	Tablets
HCP :	2.0 %	14.76	kN	Yes 10	Times	
Ref :		14.47	kN			
LCP :	2.0 %	14.18	kN	Yes 10	Times	
LEP :	25.0 %	10.86	kN	Yes 10	Rotations 10	Tablets
LSP :	30.0 %	10.13	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	2.62	kN	Min :	2.58	kN	Punch NO.;	32
SD :	0.90	%	Max :	2.69	kN	Punch NO.;	48
Mean Main Pressure :	14.54	kN	Min :	13.92	kN	Punch NO.;	22
SD :	1.60	%	Max :	15.18	kN	Punch NO.;	58
Filling Depth :	Increase ; 16	Times	Decrease ;	45	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	156000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	18	RPM
Pre Upper Punch Position ;	2.50	mm			
Pre Lower Punch Position ;	6.00	mm	Pre Thickness ;	3.50	mm
Main Upper Punch Position ;	2.50	mm			
Main Lower Punch Position ;	4.49	mm	Main Thickness ;	1.99	mm
Filling Depth :	7.88	mm	Current Cam :	Cam C	
Main Air pressure :	0.780	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	40	Min			
Lower Punch Remain Time (S2):	42	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.03	kN		
	Max ;	0.08	kN	Max Punch ;	21
Lower Punch :	Average ;	0.12	kN		
	Max ;	0.16	kN	Max Punch ;	20
Ejection Force :	Average ;	0.03	kN		
	Max ;	0.08	kN	Max Punch ;	12

Tablet Data (N/A)

Total Counter :	800418	Tablets			
A.W.C Counter :	788870	Tablets			
HEP :	0 (0%)	Tablets	LEP :	22 (0.0%)	Tablets
GOOD :	788848 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	ACICLO400MG STV11B00
User ID :	pb97604	Batch NO. :	VIM2500240
Print Interval :	50000 Tablets	Running Time :	04 Hour 23 Min 13 Sec
Total Counter :	800418	Total Running Time :	376 Hour 32 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	89	%	Manual ;	59	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		1500000	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.3	Sec
Lower Punch Interval Time(S2) ;		60	Min	Supply Time ;	0.3	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	19.66	kN	No		
HEP :	25.0 %	18.90	kN	Yes	10 Rotations	10 Tablets
HCP :	2.0 %	15.43	kN	Yes	10 Times	
Ref :		15.12	kN			
LCP :	2.0 %	14.82	kN	Yes	10 Times	
LEP :	25.0 %	11.34	kN	Yes	10 Rotations	10 Tablets
LSP :	30.0 %	10.59	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	2.43	kN	Min :	2.34	kN	Punch NO.;	37
SD :	1.60	%	Max :	2.54	kN	Punch NO.;	46
Mean Main Pressure :	15.21	kN	Min :	14.64	kN	Punch NO.;	12
SD :	2.00	%	Max :	15.86	kN	Punch NO.;	30
Filling Depth :	Increase ;	13	Times	Decrease ;	29	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	156000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	18	RPM
Pre Upper Punch Position ;	2.50	mm			
Pre Lower Punch Position ;	6.00	mm	Pre Thickness ;	3.50	mm
Main Upper Punch Position ;	2.50	mm			
Main Lower Punch Position ;	4.53	mm	Main Thickness ;	2.03	mm
Filling Depth :	7.87	mm	Current Cam :	Cam C	
Main Air pressure :	0.780	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	40	Min			
Lower Punch Remain Time (S2):	42	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.03	kN		
	Max ;	0.08	kN	Max Punch ;	21
Lower Punch :	Average ;	0.12	kN		
	Max ;	0.16	kN	Max Punch ;	20
Ejection Force :	Average ;	0.03	kN		
	Max ;	0.08	kN	Max Punch ;	12

Tablet Data (N/A)

Total Counter :	800418	Tablets			
A.W.C Counter :	788870	Tablets			
HEP :	0 (0%)	Tablets	LEP :	22 (0.0%)	Tablets
GOOD :	788848 (100.0%)	Tablets			