

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	METFORM 850 STMR7B00
User ID :	pn98247	Batch NO. :	MRM2500285
Print Interval :	50000 Tablets	Running Time :	01 Hour 35 Min 01 Sec
Total Counter :	150018	Total Running Time :	382 Hour 31 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	90	%	Manual ;	60	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		2647059	Tablets			
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.3	Sec
Lower Punch Interval Time(S2) ;		60	Min	Supply Time ;	0.3	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		1.00	kN			
				Stop Condition ;		
HSP :	30.0 %	21.08	kN	No		
HEP :	25.0 %	20.27	kN	Yes 10	Rotations 10	Tablets
HCP :	2.0 %	16.54	kN	Yes 10	Times	
Ref :		16.22	kN			
LCP :	2.0 %	15.89	kN	Yes 10	Times	
LEP :	25.0 %	12.16	kN	Yes 10	Rotations 10	Tablets
LSP :	30.0 %	11.35	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	8.27	kN	Min :	8.08	kN	Punch NO.;	20
SD :	0.80	%	Max :	8.42	kN	Punch NO.;	51
Mean Main Pressure :	16.35	kN	Min :	15.70	kN	Punch NO.;	33
SD :	1.60	%	Max :	16.80	kN	Punch NO.;	29
Filling Depth :	Increase ; 61	Times	Decrease ; 51	Times			

PRODUCTION REPORT

Operation Value

Disk Speed :	15	RPM	Capacity :	95400	Tablets/hour
Feeder : Status ;	Auto		Speed ;	14	RPM
Pre Upper Punch Position ;	2.50	mm			
Pre Lower Punch Position ;	6.70	mm	Pre Thickness ;	4.20	mm
Main Upper Punch Position ;	2.50	mm			
Main Lower Punch Position ;	5.95	mm	Main Thickness ;	3.45	mm
Filling Depth :	8.46	mm	Current Cam :	Cam C	
Main Air pressure :	0.793	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	42	Min			
Lower Punch Remain Time (S2):	24	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.32	kN		
	Max ;	0.38	kN	Max Punch ;	20
Lower Punch :	Average ;	0.09	kN		
	Max ;	0.14	kN	Max Punch ;	37
Ejection Force :	Average ;	0.04	kN		
	Max ;	0.11	kN	Max Punch ;	2

Tablet Data (N/A)

Total Counter :	150018	Tablets			
A.W.C Counter :	99195	Tablets			
HEP :	10 (0.0%)	Tablets	LEP :	6 (0.0%)	Tablets
GOOD :	99179 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	METFORM 850 STMR7B00
User ID :	pn98247	Batch NO. :	MRM2500285
Print Interval :	50000 Tablets	Running Time :	01 Hour 35 Min 01 Sec
Total Counter :	150018	Total Running Time :	382 Hour 31 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	90	%	Manual ;	60	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		2647059	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.3	Sec
Lower Punch Interval Time(S2) ;		60	Min	Supply Time ;	0.3	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		1.00	kN			
				Stop Condition ;		
HSP :	30.0 %	20.57	kN	No		
HEP :	25.0 %	19.78	kN	Yes	10 Rotations	10 Tablets
HCP :	2.0 %	16.14	kN	Yes	10 Times	
Ref :		15.82	kN			
LCP :	2.0 %	15.50	kN	Yes	10 Times	
LEP :	25.0 %	11.87	kN	Yes	10 Rotations	10 Tablets
LSP :	30.0 %	11.07	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	8.47	kN	Min :	8.20	kN	Punch NO.;	27
SD :	1.60	%	Max :	8.80	kN	Punch NO.;	16
Mean Main Pressure :	15.60	kN	Min :	14.75	kN	Punch NO.;	27
SD :	3.20	%	Max :	16.70	kN	Punch NO.;	16
Filling Depth :	Increase ;	42	Times	Decrease ;	18	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	15	RPM	Capacity :	95400	Tablets/hour
Feeder : Status ;	Auto		Speed ;	14	RPM
Pre Upper Punch Position ;	2.50	mm			
Pre Lower Punch Position ;	6.70	mm	Pre Thickness ;	4.20	mm
Main Upper Punch Position ;	2.50	mm			
Main Lower Punch Position ;	6.05	mm	Main Thickness ;	3.55	mm
Filling Depth :	8.76	mm	Current Cam :	Cam C	
Main Air pressure :	0.793	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	42	Min			
Lower Punch Remain Time (S2):	24	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.32	kN		
	Max ;	0.38	kN	Max Punch ;	24
Lower Punch :	Average ;	0.09	kN		
	Max ;	0.14	kN	Max Punch ;	37
Ejection Force :	Average ;	0.04	kN		
	Max ;	0.11	kN	Max Punch ;	2

Tablet Data (N/A)

Total Counter :	150018	Tablets			
A.W.C Counter :	99195	Tablets			
HEP :	10 (0.0%)	Tablets	LEP :	6 (0.0%)	Tablets
GOOD :	99179 (100.0%)	Tablets			