

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	METFORM 850 STMR7B00
User ID :	pb97604	Batch NO. :	MRM2500285
Print Interval :	50000 Tablets	Running Time :	03 Hour 41 Min 16 Sec
Total Counter :	350062	Total Running Time :	384 Hour 38 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	120	%	Manual ;	60	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		2647059	Tablets			
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.3	Sec
Lower Punch Interval Time(S2) ;		60	Min	Supply Time ;	0.3	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		1.00	kN			
				Stop Condition ;		
HSP :	30.0 %	20.18	kN	No		
HEP :	25.0 %	19.40	kN	Yes 10	Rotations 10	Tablets
HCP :	2.0 %	15.83	kN	Yes 10	Times	
Ref :		15.52	kN			
LCP :	2.0 %	15.21	kN	Yes 10	Times	
LEP :	25.0 %	11.64	kN	Yes 10	Rotations 10	Tablets
LSP :	30.0 %	10.86	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	8.42	kN	Min :	8.30	kN	Punch NO.;	10
SD :	0.60	%	Max :	8.55	kN	Punch NO.;	39
Mean Main Pressure :	15.72	kN	Min :	15.08	kN	Punch NO.;	20
SD :	1.70	%	Max :	16.38	kN	Punch NO.;	47
Filling Depth :	Increase ;	108	Times	Decrease ;	89	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	15	RPM	Capacity :	95400	Tablets/hour
Feeder : Status ;	Auto		Speed ;	18	RPM
Pre Upper Punch Position ;	2.50	mm			
Pre Lower Punch Position ;	6.85	mm	Pre Thickness ;	4.35	mm
Main Upper Punch Position ;	2.50	mm			
Main Lower Punch Position ;	5.95	mm	Main Thickness ;	3.45	mm
Filling Depth :	9.15	mm	Current Cam :	Cam C	
Main Air pressure :	0.807	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	78	Min			
Lower Punch Remain Time (S2):	20	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.34	kN		
	Max ;	0.40	kN	Max Punch ;	27
Lower Punch :	Average ;	0.09	kN		
	Max ;	0.14	kN	Max Punch ;	44
Ejection Force :	Average ;	0.03	kN		
	Max ;	0.06	kN	Max Punch ;	19

Tablet Data (N/A)

Total Counter :	350062	Tablets			
A.W.C Counter :	297263	Tablets			
HEP :	10 (0.0%)	Tablets	LEP :	41 (0.0%)	Tablets
GOOD :	297212 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	METFORM 850 STMR7B00
User ID :	pb97604	Batch NO. :	MRM2500285
Print Interval :	50000 Tablets	Running Time :	03 Hour 41 Min 16 Sec
Total Counter :	350062	Total Running Time :	384 Hour 38 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	119	%	Manual ;	60	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		2647059	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.3	Sec
Lower Punch Interval Time(S2) ;		60	Min	Supply Time ;	0.3	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		1.00	kN			
				Stop Condition ;		
HSP :	30.0 %	22.35	kN	No		
HEP :	25.0 %	21.49	kN	Yes	10 Rotations	10 Tablets
HCP :	2.0 %	17.53	kN	Yes	10 Times	
Ref :		17.19	kN			
LCP :	2.0 %	16.85	kN	Yes	10 Times	
LEP :	25.0 %	12.89	kN	Yes	10 Rotations	10 Tablets
LSP :	30.0 %	12.03	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	8.41	kN	Min :	8.27	kN	Punch NO.;	33
SD :	1.00	%	Max :	8.64	kN	Punch NO.;	14
Mean Main Pressure :	17.18	kN	Min :	16.40	kN	Punch NO.;	33
SD :	1.90	%	Max :	18.08	kN	Punch NO.;	14
Filling Depth :	Increase ;	50	Times	Decrease ;	38	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	15	RPM	Capacity :	95400	Tablets/hour
Feeder : Status ;	Auto		Speed ;	18	RPM
Pre Upper Punch Position ;	2.50	mm			
Pre Lower Punch Position ;	6.95	mm	Pre Thickness ;	4.45	mm
Main Upper Punch Position ;	2.50	mm			
Main Lower Punch Position ;	6.05	mm	Main Thickness ;	3.55	mm
Filling Depth :	9.45	mm	Current Cam :	Cam C	
Main Air pressure :	0.807	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	78	Min			
Lower Punch Remain Time (S2):	20	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.34	kN		
	Max ;	0.40	kN	Max Punch ;	27
Lower Punch :	Average ;	0.09	kN		
	Max ;	0.14	kN	Max Punch ;	44
Ejection Force :	Average ;	0.03	kN		
	Max ;	0.06	kN	Max Punch ;	19

Tablet Data (N/A)

Total Counter :	350062	Tablets			
A.W.C Counter :	297263	Tablets			
HEP :	10 (0.0%)	Tablets	LEP :	41 (0.0%)	Tablets
GOOD :	297212 (100.0%)	Tablets			