

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	METFORM 850 STM7B00
User ID :	pb97604	Batch NO. :	MRM2500285
Print Interval :	50000 Tablets	Running Time :	04 Hour 12 Min 50 Sec
Total Counter :	400082	Total Running Time :	385 Hour 9 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	120	%	Manual ;	60	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		2647059	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.3	Sec
Lower Punch Interval Time(S2) ;		60	Min	Supply Time ;	0.3	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		1.00	kN			
				Stop Condition ;		
HSP :	30.0 %	20.48	kN	No		
HEP :	25.0 %	19.70	kN	Yes 10	Rotations 10	Tablets
HCP :	2.0 %	16.07	kN	Yes 10	Times	
Ref :		15.76	kN			
LCP :	2.0 %	15.44	kN	Yes 10	Times	
LEP :	25.0 %	11.82	kN	Yes 10	Rotations 10	Tablets
LSP :	30.0 %	11.03	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	8.45	kN	Min :	8.29	kN	Punch NO.;	11
SD :	0.70	%	Max :	8.61	kN	Punch NO.;	44
Mean Main Pressure :	15.90	kN	Min :	15.16	kN	Punch NO.;	11
SD :	1.90	%	Max :	16.75	kN	Punch NO.;	44
Filling Depth :	Increase ;	121	Times	Decrease ;	93	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	15	RPM	Capacity :	95400	Tablets/hour
Feeder : Status ;	Auto		Speed ;	18	RPM
Pre Upper Punch Position ;	2.50	mm			
Pre Lower Punch Position ;	6.85	mm	Pre Thickness ;	4.35	mm
Main Upper Punch Position ;	2.50	mm			
Main Lower Punch Position ;	5.95	mm	Main Thickness ;	3.45	mm
Filling Depth :	9.53	mm	Current Cam :	Cam C	
Main Air pressure :	0.795	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	47	Min			
Lower Punch Remain Time (S2):	49	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.34	kN		
	Max ;	0.41	kN	Max Punch ;	27
Lower Punch :	Average ;	0.10	kN		
	Max ;	0.14	kN	Max Punch ;	49
Ejection Force :	Average ;	0.03	kN		
	Max ;	0.05	kN	Max Punch ;	35

Tablet Data (N/A)

Total Counter :	400082	Tablets			
A.W.C Counter :	347242	Tablets			
HEP :	10 (0.0%)	Tablets	LEP :	41 (0.0%)	Tablets
GOOD :	347191 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	METFORM 850 STMR7B00
User ID :	pb97604	Batch NO. :	MRM2500285
Print Interval :	50000 Tablets	Running Time :	04 Hour 12 Min 50 Sec
Total Counter :	400082	Total Running Time :	385 Hour 9 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	119	%	Manual ;	60	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		2647059	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.3	Sec
Lower Punch Interval Time(S2) ;		60	Min	Supply Time ;	0.3	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		1.00	kN			
				Stop Condition ;		
HSP :	30.0 %	22.35	kN	No		
HEP :	25.0 %	21.49	kN	Yes	10 Rotations	10 Tablets
HCP :	2.0 %	17.53	kN	Yes	10 Times	
Ref :		17.19	kN			
LCP :	2.0 %	16.85	kN	Yes	10 Times	
LEP :	25.0 %	12.89	kN	Yes	10 Rotations	10 Tablets
LSP :	30.0 %	12.03	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	8.35	kN	Min :	8.21	kN	Punch NO.;	2
SD :	0.70	%	Max :	8.50	kN	Punch NO.;	19
Mean Main Pressure :	17.04	kN	Min :	16.40	kN	Punch NO.;	2
SD :	1.70	%	Max :	17.79	kN	Punch NO.;	48
Filling Depth :	Increase ;	50	Times	Decrease ;	40	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	15	RPM	Capacity :	95400	Tablets/hour
Feeder : Status ;	Auto		Speed ;	18	RPM
Pre Upper Punch Position ;	2.50	mm			
Pre Lower Punch Position ;	6.95	mm	Pre Thickness ;	4.45	mm
Main Upper Punch Position ;	2.50	mm			
Main Lower Punch Position ;	6.05	mm	Main Thickness ;	3.55	mm
Filling Depth :	9.39	mm	Current Cam :	Cam C	
Main Air pressure :	0.795	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	47	Min			
Lower Punch Remain Time (S2):	49	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.34	kN		
	Max ;	0.40	kN	Max Punch ;	25
Lower Punch :	Average ;	0.10	kN		
	Max ;	0.14	kN	Max Punch ;	49
Ejection Force :	Average ;	0.03	kN		
	Max ;	0.05	kN	Max Punch ;	35

Tablet Data (N/A)

Total Counter :	400082	Tablets			
A.W.C Counter :	347242	Tablets			
HEP :	10 (0.0%)	Tablets	LEP :	41 (0.0%)	Tablets
GOOD :	347191 (100.0%)	Tablets			