

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	METFORM 850 STMR7B00
User ID :	ka98463	Batch NO. :	MRM2500185
Print Interval :	50000 Tablets	Running Time :	05 Hour 50 Min 33 Sec
Total Counter :	600154	Total Running Time :	414 Hour 26 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	119	%	Manual ;	60	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		2647059	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.3	Sec
Lower Punch Interval Time(S2) ;		60	Min	Supply Time ;	0.3	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		1.00	kN			
				Stop Condition ;		
HSP :	30.0 %	20.20	kN	No		
HEP :	25.0 %	19.42	kN	Yes	10 Rotations	10 Tablets
HCP :	2.0 %	15.85	kN	Yes	10 Times	
Ref :		15.54	kN			
LCP :	2.0 %	15.23	kN	Yes	10 Times	
LEP :	25.0 %	11.65	kN	Yes	10 Rotations	10 Tablets
LSP :	30.0 %	10.88	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	8.18	kN	Min :	8.10	kN	Punch NO.;	10
SD :	0.50	%	Max :	8.27	kN	Punch NO.;	44
Mean Main Pressure :	15.60	kN	Min :	15.02	kN	Punch NO.;	10
SD :	1.70	%	Max :	16.01	kN	Punch NO.;	7
Filling Depth :	Increase ;	13	Times	Decrease ;	26	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	18	RPM	Capacity :	114480	Tablets/hour
Feeder : Status ;	Auto		Speed ;	21	RPM
Pre Upper Punch Position ;	2.50	mm			
Pre Lower Punch Position ;	6.89	mm	Pre Thickness ;	4.39	mm
Main Upper Punch Position ;	2.50	mm			
Main Lower Punch Position ;	5.95	mm	Main Thickness ;	3.45	mm
Filling Depth :	9.58	mm	Current Cam :	Cam C	
Main Air pressure :	0.793	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	2	Min			
Lower Punch Remain Time (S2):	4	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.32	kN		
	Max ;	0.37	kN	Max Punch ;	52
Lower Punch :	Average ;	0.08	kN		
	Max ;	0.14	kN	Max Punch ;	51
Ejection Force :	Average ;	0.04	kN		
	Max ;	0.08	kN	Max Punch ;	13

Tablet Data (N/A)

Total Counter :	600154	Tablets			
A.W.C Counter :	595989	Tablets			
HEP :	0 (0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	595989 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	METFORM 850 STMR7B00
User ID :	ka98463	Batch NO. :	MRM2500185
Print Interval :	50000 Tablets	Running Time :	05 Hour 50 Min 33 Sec
Total Counter :	600154	Total Running Time :	414 Hour 26 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	119	%	Manual ;	60	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		2647059	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.3	Sec
Lower Punch Interval Time(S2) ;		60	Min	Supply Time ;	0.3	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		1.00	kN			
				Stop Condition ;		
HSP :	30.0 %	23.21	kN	No		
HEP :	25.0 %	22.32	kN	Yes	10 Rotations	10 Tablets
HCP :	2.0 %	18.21	kN	Yes	10 Times	
Ref :		17.85	kN			
LCP :	2.0 %	17.50	kN	Yes	10 Times	
LEP :	25.0 %	13.39	kN	Yes	10 Rotations	10 Tablets
LSP :	30.0 %	12.50	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	8.13	kN	Min :	8.03	kN	Punch NO.;	36
SD :	0.60	%	Max :	8.30	kN	Punch NO.;	44
Mean Main Pressure :	17.92	kN	Min :	17.37	kN	Punch NO.;	36
SD :	2.00	%	Max :	19.07	kN	Punch NO.;	44
Filling Depth :	Increase ;	7	Times	Decrease ;	15	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	18	RPM	Capacity :	114480	Tablets/hour
Feeder : Status ;	Auto		Speed ;	21	RPM
Pre Upper Punch Position ;	2.50	mm			
Pre Lower Punch Position ;	6.99	mm	Pre Thickness ;	4.49	mm
Main Upper Punch Position ;	2.50	mm			
Main Lower Punch Position ;	6.00	mm	Main Thickness ;	3.50	mm
Filling Depth :	9.47	mm	Current Cam :	Cam C	
Main Air pressure :	0.793	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	2	Min			
Lower Punch Remain Time (S2):	4	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.32	kN		
	Max ;	0.37	kN	Max Punch ;	52
Lower Punch :	Average ;	0.07	kN		
	Max ;	0.09	kN	Max Punch ;	53
Ejection Force :	Average ;	0.04	kN		
	Max ;	0.06	kN	Max Punch ;	13

Tablet Data (N/A)

Total Counter :	600154	Tablets			
A.W.C Counter :	595989	Tablets			
HEP :	0 (0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	595989 (100.0%)	Tablets			