

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	METFORM 850 STMR7B00
User ID :	ka98463	Batch NO. :	MRM2500185
Print Interval :	50000 Tablets	Running Time :	11 Hour 06 Min 10 Sec
Total Counter :	1200284	Total Running Time :	419 Hour 42 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	147	%	Manual ;	60	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		2647059	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.3	Sec
Lower Punch Interval Time(S2) ;		60	Min	Supply Time ;	0.3	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		1.00	kN			
				Stop Condition ;		
HSP :	30.0 %	21.01	kN	No		
HEP :	25.0 %	20.20	kN	Yes 10	Rotations 10	Tablets
HCP :	2.0 %	16.48	kN	Yes 15	Times	
Ref :		16.16	kN			
LCP :	2.0 %	15.84	kN	Yes 15	Times	
LEP :	25.0 %	12.12	kN	Yes 10	Rotations 10	Tablets
LSP :	30.0 %	11.31	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	6.10	kN	Min :	5.97	kN	Punch NO.;	10
SD :	0.80	%	Max :	6.32	kN	Punch NO.;	9
Mean Main Pressure :	16.25	kN	Min :	15.37	kN	Punch NO.;	10
SD :	2.40	%	Max :	18.03	kN	Punch NO.;	9
Filling Depth :	Increase ;	134	Times	Decrease ;	177	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	18	RPM	Capacity :	114480	Tablets/hour
Feeder : Status ;	Auto		Speed ;	26	RPM
Pre Upper Punch Position ;	2.50	mm			
Pre Lower Punch Position ;	6.89	mm	Pre Thickness ;	4.39	mm
Main Upper Punch Position ;	2.50	mm			
Main Lower Punch Position ;	5.95	mm	Main Thickness ;	3.45	mm
Filling Depth :	8.81	mm	Current Cam :	Cam C	
Main Air pressure :	0.796	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	12	Min			
Lower Punch Remain Time (S2):	54	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.33	kN		
	Max ;	0.39	kN	Max Punch ;	25
Lower Punch :	Average ;	0.11	kN		
	Max ;	0.13	kN	Max Punch ;	9
Ejection Force :	Average ;	0.05	kN		
	Max ;	0.08	kN	Max Punch ;	1

Tablet Data (N/A)

Total Counter :	1200284	Tablets			
A.W.C Counter :	1194422	Tablets			
HEP :	10 (0.0%)	Tablets	LEP :	141 (0.0%)	Tablets
GOOD :	1194271 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	METFORM 850 STMR7B00
User ID :	ka98463	Batch NO. :	MRM2500185
Print Interval :	50000 Tablets	Running Time :	11 Hour 06 Min 10 Sec
Total Counter :	1200284	Total Running Time :	419 Hour 42 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	119	%	Manual ;	60	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		2647059	Tablets			
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.3	Sec
Lower Punch Interval Time(S2) ;		60	Min	Supply Time ;	0.3	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		1.00	kN			
				Stop Condition ;		
HSP :	30.0 %	21.51	kN	No		
HEP :	25.0 %	20.68	kN	Yes 10	Rotations 10	Tablets
HCP :	2.0 %	16.88	kN	Yes 15	Times	
Ref :		16.55	kN			
LCP :	2.0 %	16.22	kN	Yes 15	Times	
LEP :	25.0 %	12.41	kN	Yes 10	Rotations 10	Tablets
LSP :	30.0 %	11.58	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	6.37	kN	Min :	6.27	kN	Punch NO.;	23
SD :	0.80	%	Max :	6.61	kN	Punch NO.;	9
Mean Main Pressure :	16.55	kN	Min :	16.01	kN	Punch NO.;	36
SD :	2.70	%	Max :	18.52	kN	Punch NO.;	9
Filling Depth :	Increase ;	45	Times	Decrease ;	64	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	18	RPM	Capacity :	114480	Tablets/hour
Feeder : Status ;	Auto		Speed ;	21	RPM
Pre Upper Punch Position ;	2.50	mm			
Pre Lower Punch Position ;	6.99	mm	Pre Thickness ;	4.49	mm
Main Upper Punch Position ;	2.50	mm			
Main Lower Punch Position ;	6.00	mm	Main Thickness ;	3.50	mm
Filling Depth :	9.02	mm	Current Cam :	Cam C 8.5-14mm	
Main Air pressure :	0.796	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	12	Min			
Lower Punch Remain Time (S2):	54	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.33	kN		
	Max ;	0.39	kN	Max Punch ;	53
Lower Punch :	Average ;	0.11	kN		
	Max ;	0.13	kN	Max Punch ;	9
Ejection Force :	Average ;	0.05	kN		
	Max ;	0.08	kN	Max Punch ;	1

Tablet Data (N/A)

Total Counter :	1200284	Tablets			
A.W.C Counter :	1194422	Tablets			
HEP :	10 (0.0%)	Tablets	LEP :	141 (0.0%)	Tablets
GOOD :	1194271 (100.0%)	Tablets			