

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	METFORM 850 STMR7B00
User ID :	ka98463	Batch NO. :	MRM2500185
Print Interval :	50000 Tablets	Running Time :	22 Hour 29 Min 53 Sec
Total Counter :	2500782	Total Running Time :	431 Hour 7 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	160	%	Manual ;	76	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		2647059	Tablets			
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.3	Sec
Lower Punch Interval Time(S2) ;		60	Min	Supply Time ;	0.3	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		1.00	kN			
				Stop Condition ;		
HSP :	30.0 %	18.21	kN	No		
HEP :	25.0 %	17.51	kN	Yes 10	Rotations 10	Tablets
HCP :	2.0 %	14.29	kN	Yes 15	Times	
Ref :		14.01	kN			
LCP :	2.0 %	13.73	kN	Yes 15	Times	
LEP :	25.0 %	10.50	kN	Yes 10	Rotations 10	Tablets
LSP :	30.0 %	9.80	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	SD :	5.55	kN	Min :	5.41	kN	Punch NO.;	10
		1.40	%	Max :	5.77	kN	Punch NO.;	24
Mean Main Pressure :		13.66	kN	Min :	12.07	kN	Punch NO.;	45
	SD :	5.50	%	Max :	15.56	kN	Punch NO.;	24
Filling Depth :	Increase ;	670	Times	Decrease ;	689	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	18	RPM	Capacity :	0	Tablets/hour
Feeder : Status ;	Auto		Speed ;	29	RPM
Pre Upper Punch Position ;	2.50	mm			
Pre Lower Punch Position ;	6.89	mm	Pre Thickness ;	4.39	mm
Main Upper Punch Position ;	2.50	mm			
Main Lower Punch Position ;	5.95	mm	Main Thickness ;	3.45	mm
Filling Depth :	11.01	mm	Current Cam :	Cam C 8.5-14mm	
Main Air pressure :	0.804	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	62	Min			
Lower Punch Remain Time (S2):	44	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.30	kN		
	Max ;	0.34	kN	Max Punch ;	1
Lower Punch :	Average ;	0.09	kN		
	Max ;	0.11	kN	Max Punch ;	49
Ejection Force :	Average ;	0.05	kN		
	Max ;	0.08	kN	Max Punch ;	49

Tablet Data (N/A)

Total Counter :	2500782	Tablets			
A.W.C Counter :	2488479	Tablets			
HEP :	779 (0.0%)	Tablets	LEP :	564 (0.0%)	Tablets
GOOD :	2487136 (99.9%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	METFORM 850 STMR7B00
User ID :	ka98463	Batch NO. :	MRM2500185
Print Interval :	50000 Tablets	Running Time :	22 Hour 29 Min 53 Sec
Total Counter :	2500782	Total Running Time :	431 Hour 7 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	166	%	Manual ;	60	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		2647059	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.3	Sec
Lower Punch Interval Time(S2) ;		60	Min	Supply Time ;	0.3	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		1.00	kN			
				Stop Condition ;		
HSP :	30.0 %	18.38	kN	No		
HEP :	25.0 %	17.68	kN	Yes 10	Rotations 10	Tablets
HCP :	2.0 %	14.42	kN	Yes 15	Times	
Ref :		14.14	kN			
LCP :	2.0 %	13.86	kN	Yes 15	Times	
LEP :	25.0 %	10.61	kN	Yes 10	Rotations 10	Tablets
LSP :	30.0 %	9.90	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	6.03	kN	Min :	5.89	kN	Punch NO.;	53
SD :	1.80	%	Max :	6.73	kN	Punch NO.;	28
Mean Main Pressure :	14.00	kN	Min :	12.63	kN	Punch NO.;	53
SD :	7.20	%	Max :	20.11	kN	Punch NO.;	28
Filling Depth :	Increase ;	377	Times	Decrease ;	338	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	18	RPM	Capacity :	0	Tablets/hour
Feeder : Status ;	Auto		Speed ;	30	RPM
Pre Upper Punch Position ;	2.50	mm			
Pre Lower Punch Position ;	6.99	mm	Pre Thickness ;	4.49	mm
Main Upper Punch Position ;	2.50	mm			
Main Lower Punch Position ;	6.00	mm	Main Thickness ;	3.50	mm
Filling Depth :	11.10	mm	Current Cam :	Cam C 8.5-14mm	
Main Air pressure :	0.804	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	62	Min			
Lower Punch Remain Time (S2):	44	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.31	kN		
	Max ;	0.34	kN	Max Punch ;	53
Lower Punch :	Average ;	0.09	kN		
	Max ;	0.11	kN	Max Punch ;	49
Ejection Force :	Average ;	0.05	kN		
	Max ;	0.08	kN	Max Punch ;	49

Tablet Data (N/A)

Total Counter :	2500782	Tablets			
A.W.C Counter :	2488479	Tablets			
HEP :	779 (0.0%)	Tablets	LEP :	564 (0.0%)	Tablets
GOOD :	2487136 (99.9%)	Tablets			