

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	METFORM 850 STMR7B00
User ID :	pb97604	Batch NO. :	MRM2500485
Print Interval :	50000 Tablets	Running Time :	20 Hour 09 Min 16 Sec
Total Counter :	2300792	Total Running Time :	475 Hour 20 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	160	%	Manual ;	76	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		2647059	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.3	Sec
Lower Punch Interval Time(S2) ;		60	Min	Supply Time ;	0.3	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		1.00	kN			
				Stop Condition ;		
HSP :	30.0 %	19.67	kN	No		
HEP :	23.0 %	18.61	kN	Yes 10	Rotations 10	Tablets
HCP :	2.0 %	15.43	kN	Yes 15	Times	
Ref :		15.13	kN			
LCP :	2.0 %	14.83	kN	Yes 15	Times	
LEP :	23.0 %	11.65	kN	Yes 10	Rotations 10	Tablets
LSP :	30.0 %	10.59	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	SD :	6.07	kN	Min :	5.96	kN	Punch NO.;	36
		0.70	%	Max :	6.16	kN	Punch NO.;	41
Mean Main Pressure :	SD :	15.23	kN	Min :	14.64	kN	Punch NO.;	36
		2.40	%	Max :	16.05	kN	Punch NO.;	39
Filling Depth :	Increase ;	1495	Times	Decrease ;	1589	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	18	RPM	Capacity :	114480	Tablets/hour
Feeder : Status ;	Auto		Speed ;	29	RPM
Pre Upper Punch Position ;	2.50	mm			
Pre Lower Punch Position ;	6.89	mm	Pre Thickness ;	4.39	mm
Main Upper Punch Position ;	2.50	mm			
Main Lower Punch Position ;	6.00	mm	Main Thickness ;	3.50	mm
Filling Depth :	9.45	mm	Current Cam :	Cam C	
Main Air pressure :	0.814	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	74	Min			
Lower Punch Remain Time (S2):	56	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.32	kN		
	Max ;	0.36	kN	Max Punch ;	50
Lower Punch :	Average ;	0.09	kN		
	Max ;	0.13	kN	Max Punch ;	13
Ejection Force :	Average ;	0.06	kN		
	Max ;	0.09	kN	Max Punch ;	11

Tablet Data (N/A)

Total Counter :	2300792	Tablets			
A.W.C Counter :	2296537	Tablets			
HEP :	646 (0.0%)	Tablets	LEP :	212 (0.0%)	Tablets
GOOD :	2295679 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	METFORM 850 STMR7B00
User ID :	pb97604	Batch NO. :	MRM2500485
Print Interval :	50000 Tablets	Running Time :	20 Hour 09 Min 16 Sec
Total Counter :	2300792	Total Running Time :	475 Hour 20 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	166	%	Manual ;	60	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		2647059	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.3	Sec
Lower Punch Interval Time(S2) ;		60	Min	Supply Time ;	0.3	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		1.00	kN			
				Stop Condition ;		
HSP :	30.0 %	20.36	kN	No		
HEP :	23.0 %	19.26	kN	Yes 10	Rotations 10	Tablets
HCP :	2.0 %	15.97	kN	Yes 15	Times	
Ref :		15.66	kN			
LCP :	2.0 %	15.35	kN	Yes 15	Times	
LEP :	23.0 %	12.06	kN	Yes 10	Rotations 10	Tablets
LSP :	30.0 %	10.96	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	5.82	kN	Min :	5.75	kN	Punch NO.;	4
SD :	0.60	%	Max :	5.92	kN	Punch NO.;	13
Mean Main Pressure :	14.50	kN	Min :	13.92	kN	Punch NO.;	47
SD :	2.40	%	Max :	15.46	kN	Punch NO.;	13
Filling Depth :	Increase ;	980	Times	Decrease ;	1008	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	18	RPM	Capacity :	114480	Tablets/hour
Feeder : Status ;	Auto		Speed ;	30	RPM
Pre Upper Punch Position ;	2.50	mm			
Pre Lower Punch Position ;	6.99	mm	Pre Thickness ;	4.49	mm
Main Upper Punch Position ;	2.50	mm			
Main Lower Punch Position ;	6.00	mm	Main Thickness ;	3.50	mm
Filling Depth :	9.54	mm	Current Cam :	Cam C 8.5-14mm	
Main Air pressure :	0.814	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	74	Min			
Lower Punch Remain Time (S2):	56	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.32	kN		
	Max ;	0.36	kN	Max Punch ;	50
Lower Punch :	Average ;	0.10	kN		
	Max ;	0.16	kN	Max Punch ;	20
Ejection Force :	Average ;	0.06	kN		
	Max ;	0.09	kN	Max Punch ;	22

Tablet Data (N/A)

Total Counter :	2300792	Tablets			
A.W.C Counter :	2296537	Tablets			
HEP :	646 (0.0%)	Tablets	LEP :	212 (0.0%)	Tablets
GOOD :	2295679 (100.0%)	Tablets			