

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	AMIOD 200MG STAI3A00
User ID :	pb97604	Batch NO. :	AIM2500120
Print Interval :	50000 Tablets	Running Time :	05 Hour 47 Min 37 Sec
Total Counter :	650256	Total Running Time :	483 Hour 57 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	120	%	Manual ;	20	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		1500000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		1.00	kN			
				Stop Condition ;		
HSP :	30.0 %	21.36	kN	No		
HEP :	20.0 %	19.72	kN	Yes 10	Rotations 10	Tablets
HCP :	2.0 %	16.76	kN	Yes 15	Times	
Ref :		16.43	kN			
LCP :	2.0 %	16.11	kN	Yes 15	Times	
LEP :	20.0 %	13.15	kN	Yes 10	Rotations 10	Tablets
LSP :	30.0 %	11.50	kN	No		
SD limit :	20.0 %			Yes		
Pre HSP		20.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	3.58	kN	Min :	3.12	kN	Punch NO.;	32
SD :	5.40	%	Max :	3.92	kN	Punch NO.;	44
Mean Main Pressure :	16.67	kN	Min :	15.31	kN	Punch NO.;	42
SD :	3.50	%	Max :	18.20	kN	Punch NO.;	19
Filling Depth :	Increase ;	277	Times	Decrease ;	278	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	18	RPM	Capacity :	114480	Tablets/hour
Feeder : Status ;	Auto		Speed ;	22	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	4.50	mm	Pre Thickness ;	1.51	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	3.95	mm	Main Thickness ;	0.96	mm
Filling Depth :	5.78	mm	Current Cam :	Cam B	
Main Air pressure :	0.743	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	60	Min			
Lower Punch Remain Time (S2):	5	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.24	kN		
	Max ;	0.34	kN	Max Punch ;	53
Lower Punch :	Average ;	0.10	kN		
	Max ;	0.13	kN	Max Punch ;	24
Ejection Force :	Average ;	0.04	kN		
	Max ;	0.05	kN	Max Punch ;	41

Tablet Data (N/A)

Total Counter :	650256	Tablets			
A.W.C Counter :	637974	Tablets			
HEP :	79 (0.0%)	Tablets	LEP :	1 (0.0%)	Tablets
GOOD :	637894 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	AMIOD 200MG STAI3A00
User ID :	pb97604	Batch NO. :	AIM2500120
Print Interval :	50000 Tablets	Running Time :	05 Hour 47 Min 37 Sec
Total Counter :	650256	Total Running Time :	483 Hour 57 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	111	%	Manual ;	20	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		1500000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		1.00	kN			
				Stop Condition ;		
HSP :	30.0 %	21.43	kN	No		
HEP :	20.0 %	19.79	kN	Yes 10	Rotations 10	Tablets
HCP :	2.0 %	16.82	kN	Yes 15	Times	
Ref :		16.49	kN			
LCP :	2.0 %	16.16	kN	Yes 15	Times	
LEP :	20.0 %	13.19	kN	Yes 10	Rotations 10	Tablets
LSP :	30.0 %	11.54	kN	No		
SD limit :	20.0 %			Yes		
Pre HSP		20.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	1.92	kN	Min :	1.79	kN	Punch NO.;	2
SD :	2.90	%	Max :	2.07	kN	Punch NO.;	27
Mean Main Pressure :	16.52	kN	Min :	15.57	kN	Punch NO.;	8
SD :	3.40	%	Max :	18.01	kN	Punch NO.;	51
Filling Depth :	Increase ;	133	Times	Decrease ;	113	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	18	RPM	Capacity :	114480	Tablets/hour
Feeder : Status ;	Auto		Speed ;	20	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	5.00	mm	Pre Thickness ;	2.01	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	4.02	mm	Main Thickness ;	1.03	mm
Filling Depth :	6.05	mm	Current Cam :	Cam B	
Main Air pressure :	0.743	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	60	Min			
Lower Punch Remain Time (S2):	5	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.24	kN		
	Max ;	0.34	kN	Max Punch ;	53
Lower Punch :	Average ;	0.10	kN		
	Max ;	0.14	kN	Max Punch ;	24
Ejection Force :	Average ;	0.04	kN		
	Max ;	0.05	kN	Max Punch ;	41

Tablet Data (N/A)

Total Counter :	650256	Tablets			
A.W.C Counter :	637974	Tablets			
HEP :	79 (0.0%)	Tablets	LEP :	1 (0.0%)	Tablets
GOOD :	637894 (100.0%)	Tablets			