

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	ACICLO800mg STV11C00
User ID :	pb97604	Batch NO. :	VIM2500180
Print Interval :	50000 Tablets	Running Time :	00 Hour 47 Min 05 Sec
Total Counter :	80942	Total Running Time :	492 Hour 13 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	112	%	Manual ;	35	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		750000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		1.00	kN			
				Stop Condition ;		
HSP :	30.0 %	25.52	kN	No		
HEP :	25.0 %	24.54	kN	Yes 10	Rotations 10	Tablets
HCP :	2.0 %	20.03	kN	Yes 15	Times	
Ref :		19.63	kN			
LCP :	2.0 %	19.24	kN	Yes 15	Times	
LEP :	25.0 %	14.72	kN	Yes 10	Rotations 10	Tablets
LSP :	30.0 %	13.74	kN	No		
SD limit :	20.0 %			Yes		
Pre HSP		20.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	2.37	kN	Min :	2.26	kN	Punch NO.;	23
SD :	2.40	%	Max :	2.49	kN	Punch NO.;	6
Mean Main Pressure :	19.69	kN	Min :	19.03	kN	Punch NO.;	28
SD :	1.40	%	Max :	20.58	kN	Punch NO.;	27
Filling Depth :	Increase ; 3	Times	Decrease ;	48	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	127200	Tablets/hour
Feeder : Status ;	Auto		Speed ;	22	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	7.40	mm	Pre Thickness ;	4.41	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.70	mm	Main Thickness ;	2.71	mm
Filling Depth :	9.50	mm	Current Cam :	Cam C	
Main Air pressure :	0.802	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	72	Min			
Lower Punch Remain Time (S2):	18	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.21	kN		
	Max ;	0.31	kN	Max Punch ;	25
Lower Punch :	Average ;	0.07	kN		
	Max ;	0.13	kN	Max Punch ;	20
Ejection Force :	Average ;	0.05	kN		
	Max ;	0.06	kN	Max Punch ;	2

Tablet Data (N/A)

Total Counter :	80942	Tablets			
A.W.C Counter :	72246	Tablets			
HEP :	28 (0.0%)	Tablets	LEP :	148 (0.2%)	Tablets
GOOD :	72070 (99.8%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	ACICLO800mg STV11C00
User ID :	pb97604	Batch NO. :	VIM2500180
Print Interval :	50000 Tablets	Running Time :	00 Hour 47 Min 05 Sec
Total Counter :	80942	Total Running Time :	492 Hour 13 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	110	%	Manual ;	20	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		750000	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		1.00	kN			
				Stop Condition ;		
HSP :	30.0 %	25.01	kN	No		
HEP :	25.0 %	24.04	kN	Yes 10	Rotations 10	Tablets
HCP :	2.0 %	19.62	kN	Yes 15	Times	
Ref :		19.24	kN			
LCP :	2.0 %	18.85	kN	Yes 15	Times	
LEP :	25.0 %	14.43	kN	Yes 10	Rotations 10	Tablets
LSP :	30.0 %	13.46	kN	No		
SD limit :	20.0 %			Yes		
Pre HSP		20.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	2.87	kN	Min :	2.76	kN	Punch NO.;	18
SD :	2.00	%	Max :	3.03	kN	Punch NO.;	48
Mean Main Pressure :	19.58	kN	Min :	18.88	kN	Punch NO.;	29
SD :	2.00	%	Max :	20.73	kN	Punch NO.;	27
Filling Depth :	Increase ;	4	Times	Decrease ;	10	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	127200	Tablets/hour
Feeder : Status ;	Auto		Speed ;	22	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	7.40	mm	Pre Thickness ;	4.41	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.78	mm	Main Thickness ;	2.79	mm
Filling Depth :	9.82	mm	Current Cam :	Cam C	
Main Air pressure :	0.802	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	72	Min			
Lower Punch Remain Time (S2):	18	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.21	kN		
	Max ;	0.32	kN	Max Punch ;	25
Lower Punch :	Average ;	0.07	kN		
	Max ;	0.13	kN	Max Punch ;	20
Ejection Force :	Average ;	0.05	kN		
	Max ;	0.06	kN	Max Punch ;	2

Tablet Data (N/A)

Total Counter :	80942	Tablets			
A.W.C Counter :	72299	Tablets			
HEP :	28 (0.0%)	Tablets	LEP :	148 (0.2%)	Tablets
GOOD :	72123 (99.8%)	Tablets			