

## PRODUCTION REPORT

### Product Information

|                  |               |                      |                         |
|------------------|---------------|----------------------|-------------------------|
| Machine Name :   | VANTIX P720D  | Product Name :       | ACICLO800mg<br>STV11C00 |
| User ID :        | pb97604       | Batch NO. :          | VIM2500180              |
| Print Interval : | 50000 Tablets | Running Time :       | 01 Hour 19 Min 53 Sec   |
| Total Counter :  | 150036        | Total Running Time : | 492 Hour 45 Min         |
| Station :        | Station 1     |                      |                         |

### Setting Value

|                                    |             |          |         |                    |              |           |
|------------------------------------|-------------|----------|---------|--------------------|--------------|-----------|
| Feeder :                           | Auto ;      | 112      | %       | Manual ;           | 35           | RPM       |
| Filling Cam :                      |             | Cam C    |         | Cam Range :        | Min :        | 6.50 mm   |
|                                    |             | 8.5-14mm |         |                    | Max :        | 12.00 mm  |
| Target Quantity :                  |             | 750000   | Tablets |                    |              |           |
| Air Pressure Low Limit :           |             | 0.400    | MPa     |                    |              |           |
| Oil Lubrication :                  |             |          |         |                    |              |           |
| Upper Punch Interval Time(S1) ;    |             | 80       | Min     | Supply Time ;      | 0.5          | Sec       |
| Lower Punch Interval Time(S2) ;    |             | 20       | Min     | Supply Time ;      | 1.0          | Sec       |
| Powder Supply Time :               |             | 5.0      | Sec     |                    |              |           |
| Initial Reject Time :              |             | 2        | Tablets |                    |              |           |
| Upper Punch Tightness High Limit : |             | 1.00     | kN      |                    |              |           |
| Lower Punch Tightness High Limit : |             | 1.00     | kN      |                    |              |           |
| Ejecting Force High Limit :        |             | 1.00     | kN      |                    |              |           |
|                                    |             |          |         | Stop Condition ;   |              |           |
| HSP :                              | 30.0 %      | 25.35    | kN      | No                 |              |           |
| HEP :                              | 25.0 %      | 24.38    | kN      | Yes 10             | Rotations 10 | Tablets   |
| HCP :                              | 2.0 %       | 19.89    | kN      | Yes 15             | Times        |           |
| Ref :                              |             | 19.50    | kN      |                    |              |           |
| LCP :                              | 2.0 %       | 19.11    | kN      | Yes 15             | Times        |           |
| LEP :                              | 25.0 %      | 14.63    | kN      | Yes 10             | Rotations 10 | Tablets   |
| LSP :                              | 30.0 %      | 13.65    | kN      | No                 |              |           |
| SD limit :                         | 20.0 %      |          |         | Yes                |              |           |
| Pre HSP                            |             | 20.00    | kN      | Yes                |              |           |
| Mean Calculation range :           | 2 Rotations |          |         | Calculation Pass : | 2            | Rotations |
| Empty Punch No. :                  | None        |          |         |                    |              |           |

### Pressure Data

|                      |              |       |            |       |       |            |    |
|----------------------|--------------|-------|------------|-------|-------|------------|----|
| Mean Pre Pressure :  | 2.30         | kN    | Min :      | 2.21  | kN    | Punch NO.; | 12 |
| SD :                 | 2.10         | %     | Max :      | 2.42  | kN    | Punch NO.; | 43 |
| Mean Main Pressure : | 19.53        | kN    | Min :      | 18.86 | kN    | Punch NO.; | 41 |
| SD :                 | 1.50         | %     | Max :      | 20.53 | kN    | Punch NO.; | 27 |
| Filling Depth :      | Increase ; 3 | Times | Decrease ; | 48    | Times |            |    |

## PRODUCTION REPORT

### Operation Value

|                               |         |     |                  |          |              |
|-------------------------------|---------|-----|------------------|----------|--------------|
| Disk Speed :                  | 20      | RPM | Capacity :       | 127200   | Tablets/hour |
| Feeder : Status ;             | Auto    |     | Speed ;          | 22       | RPM          |
| Pre Upper Punch Position ;    | 2.99    | mm  |                  |          |              |
| Pre Lower Punch Position ;    | 7.40    | mm  | Pre Thickness ;  | 4.41     | mm           |
| Main Upper Punch Position ;   | 2.99    | mm  |                  |          |              |
| Main Lower Punch Position ;   | 5.70    | mm  | Main Thickness ; | 2.71     | mm           |
| Filling Depth :               | 9.52    | mm  | Current Cam :    | Cam C    |              |
| Main Air pressure :           | 0.804   | MPa |                  | 8.5-14mm |              |
| Oil Lubrication status :      |         |     |                  |          |              |
| Upper Punch Remain Time (S1): | 39      | Min |                  |          |              |
| Lower Punch Remain Time (S2): | 5       | Min |                  |          |              |
| Lower Head Remain Time (S3):  | 0       | Min |                  |          |              |
| Powder Status :               | Disable |     | Dust Collector : | Off      |              |
| Initial Reject :              | Off     |     | Buzzer :         | Off      |              |

### Tightness

|                  |           |      |    |             |    |
|------------------|-----------|------|----|-------------|----|
| Upper Punch :    | Average ; | 0.24 | kN |             |    |
|                  | Max ;     | 0.35 | kN | Max Punch ; | 25 |
| Lower Punch :    | Average ; | 0.08 | kN |             |    |
|                  | Max ;     | 0.13 | kN | Max Punch ; | 20 |
| Ejection Force : | Average ; | 0.06 | kN |             |    |
|                  | Max ;     | 0.07 | kN | Max Punch ; | 33 |

### Tablet Data (N/A)

|                 |                   |         |       |            |         |
|-----------------|-------------------|---------|-------|------------|---------|
| Total Counter : | 150036            | Tablets |       |            |         |
| A.W.C Counter : | 141358            | Tablets |       |            |         |
| HEP :           | 28 (0.0%)         | Tablets | LEP : | 148 (0.1%) | Tablets |
| GOOD :          | 141182<br>(99.9%) | Tablets |       |            |         |

## PRODUCTION REPORT

### Product Information

|                  |               |                      |                         |
|------------------|---------------|----------------------|-------------------------|
| Machine Name :   | VANTIX P720D  | Product Name :       | ACICLO800mg<br>STV11C00 |
| User ID :        | pb97604       | Batch NO. :          | VIM2500180              |
| Print Interval : | 50000 Tablets | Running Time :       | 01 Hour 19 Min 53 Sec   |
| Total Counter :  | 150036        | Total Running Time : | 492 Hour 45 Min         |
| Station :        | Station 2     |                      |                         |

### Setting Value

|                                    |        |           |         |                    |       |                      |
|------------------------------------|--------|-----------|---------|--------------------|-------|----------------------|
| Feeder :                           | Auto ; | 110       | %       | Manual ;           | 20    | RPM                  |
| Filling Cam :                      |        | Cam C     |         | Cam Range :        | Min : | 6.50 mm              |
|                                    |        | 8.5-14mm  |         |                    | Max : | 12.00 mm             |
| Target Quantity :                  |        | 750000    | Tablets |                    |       |                      |
| Air Pressure Low Limit :           |        | 0.400     | MPa     |                    |       |                      |
| Oil Lubrication :                  |        |           |         |                    |       |                      |
| Upper Punch Interval Time(S1) ;    |        | 80        | Min     | Supply Time ;      | 0.5   | Sec                  |
| Lower Punch Interval Time(S2) ;    |        | 20        | Min     | Supply Time ;      | 1.0   | Sec                  |
| Powder Supply Time :               |        | 5.0       | Sec     |                    |       |                      |
| Initial Reject Time :              |        | 2         | Tablets |                    |       |                      |
| Upper Punch Tightness High Limit : |        | 1.00      | kN      |                    |       |                      |
| Lower Punch Tightness High Limit : |        | 1.00      | kN      |                    |       |                      |
| Ejecting Force High Limit :        |        | 1.00      | kN      |                    |       |                      |
|                                    |        |           |         | Stop Condition ;   |       |                      |
| HSP :                              | 30.0 % | 25.13     | kN      | No                 |       |                      |
| HEP :                              | 25.0 % | 24.17     | kN      | Yes                | 10    | Rotations 10 Tablets |
| HCP :                              | 2.0 %  | 19.72     | kN      | Yes                | 15    | Times                |
| Ref :                              |        | 19.33     | kN      |                    |       |                      |
| LCP :                              | 2.0 %  | 18.95     | kN      | Yes                | 15    | Times                |
| LEP :                              | 25.0 % | 14.50     | kN      | Yes                | 10    | Rotations 10 Tablets |
| LSP :                              | 30.0 % | 13.53     | kN      | No                 |       |                      |
| SD limit :                         | 20.0 % |           |         | Yes                |       |                      |
| Pre HSP                            |        | 20.00     | kN      | Yes                |       |                      |
| Mean Calculation range :           | 2      | Rotations |         | Calculation Pass : | 2     | Rotations            |
| Empty Punch No. :                  | N      |           |         |                    |       |                      |

### Pressure Data

|                      |            |    |       |            |    |            |    |
|----------------------|------------|----|-------|------------|----|------------|----|
| Mean Pre Pressure :  | 2.78       | kN | Min : | 2.67       | kN | Punch NO.; | 23 |
| SD :                 | 2.10       | %  | Max : | 2.93       | kN | Punch NO.; | 48 |
| Mean Main Pressure : | 19.34      | kN | Min : | 18.61      | kN | Punch NO.; | 28 |
| SD :                 | 2.00       | %  | Max : | 20.54      | kN | Punch NO.; | 27 |
| Filling Depth :      | Increase ; | 4  | Times | Decrease ; | 13 | Times      |    |

## PRODUCTION REPORT

### Operation Value

|                               |         |     |                  |          |              |
|-------------------------------|---------|-----|------------------|----------|--------------|
| Disk Speed :                  | 20      | RPM | Capacity :       | 127200   | Tablets/hour |
| Feeder : Status ;             | Auto    |     | Speed ;          | 22       | RPM          |
| Pre Upper Punch Position ;    | 2.99    | mm  |                  |          |              |
| Pre Lower Punch Position ;    | 7.40    | mm  | Pre Thickness ;  | 4.41     | mm           |
| Main Upper Punch Position ;   | 2.99    | mm  |                  |          |              |
| Main Lower Punch Position ;   | 5.78    | mm  | Main Thickness ; | 2.79     | mm           |
| Filling Depth :               | 9.75    | mm  | Current Cam :    | Cam C    |              |
| Main Air pressure :           | 0.804   | MPa |                  | 8.5-14mm |              |
| Oil Lubrication status :      |         |     |                  |          |              |
| Upper Punch Remain Time (S1): | 39      | Min |                  |          |              |
| Lower Punch Remain Time (S2): | 5       | Min |                  |          |              |
| Lower Head Remain Time (S3):  | 0       | Min |                  |          |              |
| Powder Status :               | Disable |     | Dust Collector : | Off      |              |
| Initial Reject :              | Off     |     | Buzzer :         | Off      |              |

### Tightness

|                  |           |      |    |             |    |
|------------------|-----------|------|----|-------------|----|
| Upper Punch :    | Average ; | 0.24 | kN |             |    |
|                  | Max ;     | 0.35 | kN | Max Punch ; | 25 |
| Lower Punch :    | Average ; | 0.08 | kN |             |    |
|                  | Max ;     | 0.13 | kN | Max Punch ; | 20 |
| Ejection Force : | Average ; | 0.06 | kN |             |    |
|                  | Max ;     | 0.07 | kN | Max Punch ; | 33 |

### Tablet Data (N/A)

|                 |                   |         |       |            |         |
|-----------------|-------------------|---------|-------|------------|---------|
| Total Counter : | 150036            | Tablets |       |            |         |
| A.W.C Counter : | 141358            | Tablets |       |            |         |
| HEP :           | 28 (0.0%)         | Tablets | LEP : | 148 (0.1%) | Tablets |
| GOOD :          | 141182<br>(99.9%) | Tablets |       |            |         |