

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	ACICLO800mg STV11C00
User ID :	ka98463	Batch NO. :	VIM2500280
Print Interval :	50000 Tablets	Running Time :	00 Hour 46 Min 34 Sec
Total Counter :	79748	Total Running Time :	498 Hour 31 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	94	%	Manual ;	35	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		750000	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		1.00	kN			
				Stop Condition ;		
HSP :	30.0 %	25.23	kN	No		
HEP :	25.0 %	24.26	kN	Yes 10	Rotations 10	Tablets
HCP :	2.0 %	19.80	kN	Yes 15	Times	
Ref :		19.41	kN			
LCP :	2.0 %	19.02	kN	Yes 15	Times	
LEP :	25.0 %	14.56	kN	Yes 10	Rotations 10	Tablets
LSP :	30.0 %	13.59	kN	No		
SD limit :	20.0 %			Yes		
Pre HSP		20.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	2.48	kN	Min :	2.34	kN	Punch NO.;	50
SD :	2.80	%	Max :	2.62	kN	Punch NO.;	6
Mean Main Pressure :	19.62	kN	Min :	19.10	kN	Punch NO.;	28
SD :	1.50	%	Max :	20.38	kN	Punch NO.;	27
Filling Depth :	Increase ; 7	Times	Decrease ;	70	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	127200	Tablets/hour
Feeder : Status ;	Auto		Speed ;	19	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	7.40	mm	Pre Thickness ;	4.41	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.74	mm	Main Thickness ;	2.75	mm
Filling Depth :	10.15	mm	Current Cam :	Cam C	
Main Air pressure :	0.788	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	21	Min			
Lower Punch Remain Time (S2):	7	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.20	kN		
	Max ;	0.29	kN	Max Punch ;	52
Lower Punch :	Average ;	0.08	kN		
	Max ;	0.13	kN	Max Punch ;	20
Ejection Force :	Average ;	0.06	kN		
	Max ;	0.14	kN	Max Punch ;	28

Tablet Data (N/A)

Total Counter :	79748	Tablets			
A.W.C Counter :	70607	Tablets			
HEP :	38 (0.1%)	Tablets	LEP :	206 (0.3%)	Tablets
GOOD :	70363 (99.7%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	ACICLO800mg STV11C00
User ID :	ka98463	Batch NO. :	VIM2500280
Print Interval :	50000 Tablets	Running Time :	00 Hour 46 Min 34 Sec
Total Counter :	79748	Total Running Time :	498 Hour 31 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	95	%	Manual ;	20	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		750000	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		1.00	kN			
				Stop Condition ;		
HSP :	30.0 %	25.25	kN	No		
HEP :	25.0 %	24.28	kN	Yes	10 Rotations	10 Tablets
HCP :	2.0 %	19.81	kN	Yes	15 Times	
Ref :		19.42	kN			
LCP :	2.0 %	19.04	kN	Yes	15 Times	
LEP :	25.0 %	14.57	kN	Yes	10 Rotations	10 Tablets
LSP :	30.0 %	13.60	kN	No		
SD limit :	20.0 %			Yes		
Pre HSP		20.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	2.96	kN	Min :	2.85	kN	Punch NO.;	18
SD :	2.30	%	Max :	3.20	kN	Punch NO.;	29
Mean Main Pressure :	19.50	kN	Min :	18.78	kN	Punch NO.;	18
SD :	1.80	%	Max :	20.55	kN	Punch NO.;	27
Filling Depth :	Increase ;	11	Times	Decrease ;	14	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	127200	Tablets/hour
Feeder : Status ;	Auto		Speed ;	19	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	7.40	mm	Pre Thickness ;	4.41	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.80	mm	Main Thickness ;	2.81	mm
Filling Depth :	10.56	mm	Current Cam :	Cam C 8.5-14mm	
Main Air pressure :	0.788	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	21	Min			
Lower Punch Remain Time (S2):	7	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.20	kN		
	Max ;	0.31	kN	Max Punch ;	1
Lower Punch :	Average ;	0.08	kN		
	Max ;	0.13	kN	Max Punch ;	20
Ejection Force :	Average ;	0.06	kN		
	Max ;	0.14	kN	Max Punch ;	28

Tablet Data (N/A)

Total Counter :	79748	Tablets			
A.W.C Counter :	70607	Tablets			
HEP :	38 (0.1%)	Tablets	LEP :	206 (0.3%)	Tablets
GOOD :	70363 (99.7%)	Tablets			