

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	ACICLO800mg STV11C00
User ID :	ka98463	Batch NO. :	VIM2500280
Print Interval :	50000 Tablets	Running Time :	03 Hour 11 Min 14 Sec
Total Counter :	383664	Total Running Time :	500 Hour 56 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	94	%	Manual ;	35	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		750000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		1.00	kN			
				Stop Condition ;		
HSP :	30.0 %	25.22	kN	No		
HEP :	25.0 %	24.25	kN	Yes 10	Rotations 10	Tablets
HCP :	2.0 %	19.79	kN	Yes 15	Times	
Ref :		19.40	kN			
LCP :	2.0 %	19.01	kN	Yes 15	Times	
LEP :	25.0 %	14.55	kN	Yes 10	Rotations 10	Tablets
LSP :	30.0 %	13.58	kN	No		
SD limit :	20.0 %			Yes		
Pre HSP		20.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	2.47	kN	Min :	2.33	kN	Punch NO.;	26
SD :	2.50	%	Max :	2.59	kN	Punch NO.;	43
Mean Main Pressure :	19.39	kN	Min :	18.80	kN	Punch NO.;	28
SD :	1.60	%	Max :	20.14	kN	Punch NO.;	1
Filling Depth :	Increase ; 14	Times	Decrease ; 75	Times			

PRODUCTION REPORT

Operation Value

Disk Speed :	18	RPM	Capacity :	114480	Tablets/hour
Feeder : Status ;	Auto		Speed ;	17	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	7.40	mm	Pre Thickness ;	4.41	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.76	mm	Main Thickness ;	2.77	mm
Filling Depth :	10.54	mm	Current Cam :	Cam C	
Main Air pressure :	0.800	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	38	Min			
Lower Punch Remain Time (S2):	4	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.29	kN		
	Max ;	0.43	kN	Max Punch ;	51
Lower Punch :	Average ;	0.08	kN		
	Max ;	0.14	kN	Max Punch ;	20
Ejection Force :	Average ;	0.07	kN		
	Max ;	0.09	kN	Max Punch ;	27

Tablet Data (N/A)

Total Counter :	383664	Tablets			
A.W.C Counter :	373558	Tablets			
HEP :	38 (0.0%)	Tablets	LEP :	206 (0.1%)	Tablets
GOOD :	373314 (99.9%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	ACICLO800mg STV11C00
User ID :	ka98463	Batch NO. :	VIM2500280
Print Interval :	50000 Tablets	Running Time :	03 Hour 11 Min 14 Sec
Total Counter :	383664	Total Running Time :	500 Hour 56 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	95	%	Manual ;	20	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		750000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		1.00	kN			
				Stop Condition ;		
HSP :	30.0 %	24.93	kN	No		
HEP :	25.0 %	23.97	kN	Yes	10	Rotations 10 Tablets
HCP :	2.0 %	19.56	kN	Yes	15	Times
Ref :		19.18	kN			
LCP :	2.0 %	18.79	kN	Yes	15	Times
LEP :	25.0 %	14.38	kN	Yes	10	Rotations 10 Tablets
LSP :	30.0 %	13.42	kN	No		
SD limit :	20.0 %			Yes		
Pre HSP		20.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	2.86	kN	Min :	2.73	kN	Punch NO.;	36
SD :	2.40	%	Max :	3.02	kN	Punch NO.;	49
Mean Main Pressure :	19.10	kN	Min :	18.45	kN	Punch NO.;	28
SD :	1.80	%	Max :	20.15	kN	Punch NO.;	27
Filling Depth :	Increase ;	15	Times	Decrease ;	14	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	18	RPM	Capacity :	114480	Tablets/hour
Feeder : Status ;	Auto		Speed ;	17	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	7.40	mm	Pre Thickness ;	4.41	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.82	mm	Main Thickness ;	2.83	mm
Filling Depth :	10.48	mm	Current Cam :	Cam C	
Main Air pressure :	0.800	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	38	Min			
Lower Punch Remain Time (S2):	4	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.29	kN		
	Max ;	0.42	kN	Max Punch ;	51
Lower Punch :	Average ;	0.08	kN		
	Max ;	0.14	kN	Max Punch ;	20
Ejection Force :	Average ;	0.07	kN		
	Max ;	0.09	kN	Max Punch ;	27

Tablet Data (N/A)

Total Counter :	383664	Tablets			
A.W.C Counter :	373558	Tablets			
HEP :	38 (0.0%)	Tablets	LEP :	206 (0.1%)	Tablets
GOOD :	373314 (99.9%)	Tablets			