

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	ACICLO800mg STV11C00
User ID :	yu98249	Batch NO. :	VIM2500380
Print Interval :	50000 Tablets	Running Time :	01 Hour 43 Min 02 Sec
Total Counter :	200060	Total Running Time :	505 Hour 49 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	149	%	Manual ;	35	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		750000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		1.00	kN			
				Stop Condition ;		
HSP :	30.0 %	24.00	kN	No		
HEP :	25.0 %	23.07	kN	Yes 10	Rotations 10	Tablets
HCP :	2.0 %	18.83	kN	Yes 15	Times	
Ref :		18.46	kN			
LCP :	2.0 %	18.09	kN	Yes 15	Times	
LEP :	25.0 %	13.84	kN	Yes 10	Rotations 10	Tablets
LSP :	30.0 %	12.92	kN	No		
SD limit :	20.0 %			Yes		
Pre HSP		20.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	2.28	kN	Min :	2.18	kN	Punch NO.;	26
SD :	2.50	%	Max :	2.39	kN	Punch NO.;	38
Mean Main Pressure :	18.61	kN	Min :	18.02	kN	Punch NO.;	28
SD :	1.30	%	Max :	19.19	kN	Punch NO.;	27
Filling Depth :	Increase ; 24	Times	Decrease ;	75	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	127200	Tablets/hour
Feeder : Status ;	Auto		Speed ;	30	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	7.40	mm	Pre Thickness ;	4.41	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.77	mm	Main Thickness ;	2.78	mm
Filling Depth :	10.03	mm	Current Cam :	Cam C	
Main Air pressure :	0.791	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	71	Min			
Lower Punch Remain Time (S2):	18	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.19	kN		
	Max ;	0.30	kN	Max Punch ;	53
Lower Punch :	Average ;	0.08	kN		
	Max ;	0.14	kN	Max Punch ;	20
Ejection Force :	Average ;	0.07	kN		
	Max ;	0.10	kN	Max Punch ;	9

Tablet Data (N/A)

Total Counter :	200060	Tablets			
A.W.C Counter :	193312	Tablets			
HEP :	0 (0%)	Tablets	LEP :	102 (0.1%)	Tablets
GOOD :	193210 (99.9%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	ACICLO800mg STV11C00
User ID :	yu98249	Batch NO. :	VIM2500380
Print Interval :	50000 Tablets	Running Time :	01 Hour 43 Min 02 Sec
Total Counter :	200060	Total Running Time :	505 Hour 49 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	149	%	Manual ;	20	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		750000	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		1.00	kN			
				Stop Condition ;		
HSP :	30.0 %	23.85	kN	No		
HEP :	25.0 %	22.94	kN	Yes 10	Rotations 10	Tablets
HCP :	2.0 %	18.72	kN	Yes 15	Times	
Ref :		18.35	kN			
LCP :	2.0 %	17.98	kN	Yes 15	Times	
LEP :	25.0 %	13.76	kN	Yes 10	Rotations 10	Tablets
LSP :	30.0 %	12.84	kN	No		
SD limit :	20.0 %			Yes		
Pre HSP		20.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	2.77	kN	Min :	2.66	kN	Punch NO.;	26
SD :	2.10	%	Max :	2.90	kN	Punch NO.;	16
Mean Main Pressure :	18.55	kN	Min :	17.90	kN	Punch NO.;	41
SD :	1.80	%	Max :	19.57	kN	Punch NO.;	27
Filling Depth :	Increase ;	24	Times	Decrease ;	20	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	127200	Tablets/hour
Feeder : Status ;	Auto		Speed ;	30	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	7.40	mm	Pre Thickness ;	4.41	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.83	mm	Main Thickness ;	2.84	mm
Filling Depth :	9.98	mm	Current Cam :	Cam C	
Main Air pressure :	0.791	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	71	Min			
Lower Punch Remain Time (S2):	18	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.19	kN		
	Max ;	0.30	kN	Max Punch ;	53
Lower Punch :	Average ;	0.08	kN		
	Max ;	0.13	kN	Max Punch ;	20
Ejection Force :	Average ;	0.07	kN		
	Max ;	0.10	kN	Max Punch ;	9

Tablet Data (N/A)

Total Counter :	200060	Tablets			
A.W.C Counter :	193312	Tablets			
HEP :	0 (0%)	Tablets	LEP :	102 (0.1%)	Tablets
GOOD :	193210 (99.9%)	Tablets			