

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MEBEVE135MG,STMV2 A00
User ID :	pb97604	Batch NO. :	MVM2500113
Print Interval :	50000 Tablets	Running Time :	00 Hour 09 Min 17 Sec
Total Counter :	18326	Total Running Time :	529 Hour 47 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	58	%	Manual ;	35	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		2000000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		30	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		1.00	kN			
				Stop Condition ;		
HSP :	30.0 %	16.86	kN	No		
HEP :	25.0 %	16.21	kN	Yes 10	Rotations 10	Tablets
HCP :	2.0 %	13.23	kN	Yes 15	Times	
Ref :		12.97	kN			
LCP :	2.0 %	12.71	kN	Yes 15	Times	
LEP :	25.0 %	9.73	kN	Yes 10	Rotations 10	Tablets
LSP :	30.0 %	9.08	kN	No		
SD limit :	20.0 %			Yes		
Pre HSP		20.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	1.43	kN	Min :	1.30	kN	Punch NO.;	53
SD :	3.30	%	Max :	1.53	kN	Punch NO.;	51
Mean Main Pressure :	13.00	kN	Min :	12.50	kN	Punch NO.;	20
SD :	2.60	%	Max :	13.79	kN	Punch NO.;	11
Filling Depth :	Increase ; 8	Times	Decrease ; 1	Times			

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	127200	Tablets/hour
Feeder : Status ;	Auto		Speed ;	12	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	5.75	mm	Pre Thickness ;	2.76	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	4.66	mm	Main Thickness ;	1.66	mm
Filling Depth :	9.51	mm	Current Cam :	Cam C	
Main Air pressure :	0.789	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	18	Min			
Lower Punch Remain Time (S2):	5	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.12	kN		
	Max ;	0.22	kN	Max Punch ;	24
Lower Punch :	Average ;	0.12	kN		
	Max ;	0.13	kN	Max Punch ;	34
Ejection Force :	Average ;	0.05	kN		
	Max ;	0.07	kN	Max Punch ;	12

Tablet Data (N/A)

Total Counter :	18326	Tablets			
A.W.C Counter :	10978	Tablets			
HEP :	0 (0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	10978 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MEBEVE135MG,STMV2 A00
User ID :	pb97604	Batch NO. :	MVM2500113
Print Interval :	50000 Tablets	Running Time :	00 Hour 09 Min 17 Sec
Total Counter :	18326	Total Running Time :	529 Hour 47 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	59	%	Manual ;	20	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		2000000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		30	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		1.00	kN			
				Stop Condition ;		
HSP :	30.0 %	17.16	kN	No		
HEP :	25.0 %	16.50	kN	Yes 10	Rotations 10	Tablets
HCP :	2.0 %	13.46	kN	Yes 15	Times	
Ref :		13.20	kN			
LCP :	2.0 %	12.93	kN	Yes 15	Times	
LEP :	25.0 %	9.90	kN	Yes 10	Rotations 10	Tablets
LSP :	30.0 %	9.24	kN	No		
SD limit :	20.0 %			Yes		
Pre HSP		20.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	1.47	kN	Min :	1.36	kN	Punch NO.;	46
SD :	4.10	%	Max :	1.63	kN	Punch NO.;	25
Mean Main Pressure :	13.33	kN	Min :	12.70	kN	Punch NO.;	7
SD :	2.10	%	Max :	13.84	kN	Punch NO.;	52
Filling Depth :	Increase ;	6	Times	Decrease ;	5	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	127200	Tablets/hour
Feeder : Status ;	Auto		Speed ;	12	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	5.70	mm	Pre Thickness ;	2.71	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	4.82	mm	Main Thickness ;	1.83	mm
Filling Depth :	8.32	mm	Current Cam :	Cam C 8.5-14mm	
Main Air pressure :	0.789	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	18	Min			
Lower Punch Remain Time (S2):	5	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.12	kN		
	Max ;	0.22	kN	Max Punch ;	24
Lower Punch :	Average ;	0.12	kN		
	Max ;	0.13	kN	Max Punch ;	34
Ejection Force :	Average ;	0.05	kN		
	Max ;	0.06	kN	Max Punch ;	41

Tablet Data (N/A)

Total Counter :	18326	Tablets			
A.W.C Counter :	10978	Tablets			
HEP :	0 (0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	10978 (100.0%)	Tablets			