

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MEBEVE135MG,STMV2 A00
User ID :	pb97604	Batch NO. :	MVM2500113
Print Interval :	50000 Tablets	Running Time :	13 Hour 24 Min 59 Sec
Total Counter :	1700718	Total Running Time :	543 Hour 4 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	55	%	Manual ;	35	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		2000000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		30	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		1.00	kN			
				Stop Condition ;		
HSP :	30.0 %	16.69	kN	No		
HEP :	22.0 %	15.66	kN	Yes 10	Rotations 10	Tablets
HCP :	2.0 %	13.09	kN	Yes 15	Times	
Ref :		12.84	kN			
LCP :	2.0 %	12.58	kN	Yes 15	Times	
LEP :	22.0 %	10.01	kN	Yes 10	Rotations 10	Tablets
LSP :	30.0 %	8.99	kN	No		
SD limit :	20.0 %			Yes		
Pre HSP		20.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	1.38	kN	Min :	1.21	kN	Punch NO.;	35
SD :	5.50	%	Max :	1.59	kN	Punch NO.;	26
Mean Main Pressure :	12.81	kN	Min :	11.75	kN	Punch NO.;	48
SD :	3.20	%	Max :	13.51	kN	Punch NO.;	20
Filling Depth :	Increase ;	344	Times	Decrease ;	352	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	127200	Tablets/hour
Feeder : Status ;	Auto		Speed ;	11	RPM
Pre Upper Punch Position ;	2.50	mm			
Pre Lower Punch Position ;	5.21	mm	Pre Thickness ;	2.71	mm
Main Upper Punch Position ;	2.20	mm			
Main Lower Punch Position ;	3.89	mm	Main Thickness ;	1.69	mm
Filling Depth :	9.53	mm	Current Cam :	Cam C	
Main Air pressure :	0.826	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	12	Min			
Lower Punch Remain Time (S2):	19	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.17	kN		
	Max ;	0.26	kN	Max Punch ;	53
Lower Punch :	Average ;	0.11	kN		
	Max ;	0.12	kN	Max Punch ;	3
Ejection Force :	Average ;	0.04	kN		
	Max ;	0.06	kN	Max Punch ;	16

Tablet Data (N/A)

Total Counter :	1700718	Tablets			
A.W.C Counter :	1689367	Tablets			
HEP :	1 (0.0%)	Tablets	LEP :	540 (0.0%)	Tablets
GOOD :	1688826 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MEBEVE135MG,STMV2 A00
User ID :	pb97604	Batch NO. :	MVM2500113
Print Interval :	50000 Tablets	Running Time :	13 Hour 24 Min 59 Sec
Total Counter :	1700718	Total Running Time :	543 Hour 4 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	54	%	Manual ;	20	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		2000000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		30	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		1.00	kN			
				Stop Condition ;		
HSP :	30.0 %	17.77	kN	No		
HEP :	22.0 %	16.68	kN	Yes 10	Rotations 10	Tablets
HCP :	2.0 %	13.94	kN	Yes 15	Times	
Ref :		13.67	kN			
LCP :	2.0 %	13.40	kN	Yes 15	Times	
LEP :	22.0 %	10.66	kN	Yes 10	Rotations 10	Tablets
LSP :	30.0 %	9.57	kN	No		
SD limit :	20.0 %			Yes		
Pre HSP		20.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	1.46	kN	Min :	1.27	kN	Punch NO.;	27
SD :	4.60	%	Max :	1.63	kN	Punch NO.;	49
Mean Main Pressure :	13.75	kN	Min :	12.98	kN	Punch NO.;	51
SD :	2.50	%	Max :	14.63	kN	Punch NO.;	33
Filling Depth :	Increase ;	114	Times	Decrease ;	110	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	127200	Tablets/hour
Feeder : Status ;	Auto		Speed ;	11	RPM
Pre Upper Punch Position ;	2.50	mm			
Pre Lower Punch Position ;	5.21	mm	Pre Thickness ;	2.71	mm
Main Upper Punch Position ;	2.20	mm			
Main Lower Punch Position ;	4.03	mm	Main Thickness ;	1.83	mm
Filling Depth :	8.63	mm	Current Cam :	Cam C	
Main Air pressure :	0.826	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	12	Min			
Lower Punch Remain Time (S2):	19	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.17	kN		
	Max ;	0.28	kN	Max Punch ;	53
Lower Punch :	Average ;	0.11	kN		
	Max ;	0.12	kN	Max Punch ;	3
Ejection Force :	Average ;	0.04	kN		
	Max ;	0.06	kN	Max Punch ;	16

Tablet Data (N/A)

Total Counter :	1700718	Tablets			
A.W.C Counter :	1689367	Tablets			
HEP :	1 (0.0%)	Tablets	LEP :	540 (0.0%)	Tablets
GOOD :	1688826 (100.0%)	Tablets			