

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MEBEVE135MG,STMV2 A00
User ID :	yu98249	Batch NO. :	MVM2500113
Print Interval :	50000 Tablets	Running Time :	15 Hour 27 Min 52 Sec
Total Counter :	1960434	Total Running Time :	545 Hour 7 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	65	%	Manual ;	35	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		2000000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		30	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		1.00	kN			
				Stop Condition ;		
HSP :	30.0 %	16.69	kN	No		
HEP :	22.0 %	15.66	kN	Yes 10	Rotations 10	Tablets
HCP :	2.0 %	13.09	kN	Yes 15	Times	
Ref :		12.84	kN			
LCP :	2.0 %	12.58	kN	Yes 15	Times	
LEP :	22.0 %	10.01	kN	Yes 10	Rotations 10	Tablets
LSP :	30.0 %	8.99	kN	No		
SD limit :	20.0 %			Yes		
Pre HSP		20.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	1.25	kN	Min :	1.11	kN	Punch NO.;	52
SD :	5.90	%	Max :	1.46	kN	Punch NO.;	4
Mean Main Pressure :	12.00	kN	Min :	11.27	kN	Punch NO.;	32
SD :	2.70	%	Max :	12.71	kN	Punch NO.;	27
Filling Depth :	Increase ;	403	Times	Decrease ;	416	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	0	Tablets/hour
Feeder : Status ;	Auto		Speed ;	13	RPM
Pre Upper Punch Position ;	2.50	mm			
Pre Lower Punch Position ;	5.21	mm	Pre Thickness ;	2.71	mm
Main Upper Punch Position ;	2.20	mm			
Main Lower Punch Position ;	3.89	mm	Main Thickness ;	1.69	mm
Filling Depth :	9.81	mm	Current Cam :	Cam C 8.5-14mm	
Main Air pressure :	0.818	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	12	Min			
Lower Punch Remain Time (S2):	19	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	Off	
Initial Reject :	On		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.18	kN		
	Max ;	0.28	kN	Max Punch ;	51
Lower Punch :	Average ;	0.11	kN		
	Max ;	0.12	kN	Max Punch ;	26
Ejection Force :	Average ;	0.05	kN		
	Max ;	0.06	kN	Max Punch ;	4

Tablet Data (N/A)

Total Counter :	1960434	Tablets			
A.W.C Counter :	1948933	Tablets			
HEP :	11 (0.0%)	Tablets	LEP :	573 (0.0%)	Tablets
GOOD :	1948349 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MEBEVE135MG,STMV2 A00
User ID :	yu98249	Batch NO. :	MVM2500113
Print Interval :	50000 Tablets	Running Time :	15 Hour 27 Min 52 Sec
Total Counter :	1960434	Total Running Time :	545 Hour 7 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	64	%	Manual ;	20	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		2000000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		30	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		1.00	kN			
				Stop Condition ;		
HSP :	30.0 %	17.44	kN	No		
HEP :	22.0 %	16.37	kN	Yes 10	Rotations 10	Tablets
HCP :	2.0 %	13.68	kN	Yes 15	Times	
Ref :		13.41	kN			
LCP :	2.0 %	13.15	kN	Yes 15	Times	
LEP :	22.0 %	10.46	kN	Yes 10	Rotations 10	Tablets
LSP :	30.0 %	9.39	kN	No		
SD limit :	20.0 %			Yes		
Pre HSP		20.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	1.27	kN	Min :	1.16	kN	Punch NO.;	31
SD :	4.00	%	Max :	1.42	kN	Punch NO.;	4
Mean Main Pressure :	13.21	kN	Min :	12.47	kN	Punch NO.;	48
SD :	3.10	%	Max :	14.81	kN	Punch NO.;	32
Filling Depth :	Increase ;	165	Times	Decrease ;	170	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	0	Tablets/hour
Feeder : Status ;	Auto		Speed ;	13	RPM
Pre Upper Punch Position ;	2.50	mm			
Pre Lower Punch Position ;	5.21	mm	Pre Thickness ;	2.71	mm
Main Upper Punch Position ;	2.20	mm			
Main Lower Punch Position ;	4.03	mm	Main Thickness ;	1.83	mm
Filling Depth :	8.60	mm	Current Cam :	Cam C 8.5-14mm	
Main Air pressure :	0.818	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	12	Min			
Lower Punch Remain Time (S2):	19	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	Off	
Initial Reject :	On		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.18	kN		
	Max ;	0.32	kN	Max Punch ;	53
Lower Punch :	Average ;	0.11	kN		
	Max ;	0.12	kN	Max Punch ;	26
Ejection Force :	Average ;	0.05	kN		
	Max ;	0.06	kN	Max Punch ;	4

Tablet Data (N/A)

Total Counter :	1960434	Tablets			
A.W.C Counter :	1948933	Tablets			
HEP :	11 (0.0%)	Tablets	LEP :	573 (0.0%)	Tablets
GOOD :	1948349 (100.0%)	Tablets			