

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MEBEVE135MG STMV2A00
User ID :	sj97904	Batch NO. :	MVM2500213
Print Interval :	50000 Tablets	Running Time :	12 Hour 56 Min 33 Sec
Total Counter :	1642916	Total Running Time :	558 Hour 4 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	82	%	Manual ;	20	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		2000000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		30	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		1.00	kN			
				Stop Condition ;		
HSP :	30.0 %	14.89	kN	No		
HEP :	22.0 %	13.98	kN	Yes 10	Rotations 10	Tablets
HCP :	2.0 %	11.69	kN	Yes 15	Times	
Ref :		11.46	kN			
LCP :	2.0 %	11.23	kN	Yes 15	Times	
LEP :	22.0 %	8.94	kN	Yes 10	Rotations 10	Tablets
LSP :	30.0 %	8.02	kN	No		
SD limit :	20.0 %			Yes		
Pre HSP		20.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	1.50	kN	Min :	1.44	kN	Punch NO.;	9
SD :	2.00	%	Max :	1.56	kN	Punch NO.;	28
Mean Main Pressure :	11.37	kN	Min :	10.72	kN	Punch NO.;	15
SD :	2.80	%	Max :	12.04	kN	Punch NO.;	50
Filling Depth :	Increase ;	960	Times	Decrease ;	925	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	127200	Tablets/hour
Feeder : Status ;	Auto		Speed ;	16	RPM
Pre Upper Punch Position ;	2.50	mm			
Pre Lower Punch Position ;	5.70	mm	Pre Thickness ;	3.20	mm
Main Upper Punch Position ;	2.20	mm			
Main Lower Punch Position ;	4.03	mm	Main Thickness ;	1.83	mm
Filling Depth :	9.47	mm	Current Cam :	Cam C	
Main Air pressure :	0.800	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	3	Min			
Lower Punch Remain Time (S2):	20	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.18	kN		
	Max ;	0.27	kN	Max Punch ;	53
Lower Punch :	Average ;	0.12	kN		
	Max ;	0.13	kN	Max Punch ;	27
Ejection Force :	Average ;	0.05	kN		
	Max ;	0.06	kN	Max Punch ;	28

Tablet Data (N/A)

Total Counter :	1642916	Tablets			
A.W.C Counter :	1634838	Tablets			
HEP :	168 (0.0%)	Tablets	LEP :	2 (0.0%)	Tablets
GOOD :	1634668 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MEBEVE135MG STMV2A00
User ID :	sj97904	Batch NO. :	MVM2500213
Print Interval :	50000 Tablets	Running Time :	12 Hour 56 Min 33 Sec
Total Counter :	1642916	Total Running Time :	558 Hour 4 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	64	%	Manual ;	20	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		2000000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		30	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		1.00	kN			
				Stop Condition ;		
HSP :	30.0 %	16.56	kN	No		
HEP :	22.0 %	15.54	kN	Yes 10	Rotations 10	Tablets
HCP :	2.0 %	12.99	kN	Yes 15	Times	
Ref :		12.74	kN			
LCP :	2.0 %	12.48	kN	Yes 15	Times	
LEP :	22.0 %	9.94	kN	Yes 10	Rotations 10	Tablets
LSP :	30.0 %	8.92	kN	No		
SD limit :	20.0 %			Yes		
Pre HSP		20.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	1.33	kN	Min :	1.24	kN	Punch NO.;	49
SD :	3.00	%	Max :	1.42	kN	Punch NO.;	41
Mean Main Pressure :	12.63	kN	Min :	11.56	kN	Punch NO.;	9
SD :	3.30	%	Max :	13.73	kN	Punch NO.;	1
Filling Depth :	Increase ;	545	Times	Decrease ;	528	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	127200	Tablets/hour
Feeder : Status ;	Auto		Speed ;	13	RPM
Pre Upper Punch Position ;	2.50	mm			
Pre Lower Punch Position ;	5.70	mm	Pre Thickness ;	3.20	mm
Main Upper Punch Position ;	2.20	mm			
Main Lower Punch Position ;	4.08	mm	Main Thickness ;	1.88	mm
Filling Depth :	8.60	mm	Current Cam :	Cam C	
Main Air pressure :	0.800	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	3	Min			
Lower Punch Remain Time (S2):	20	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.18	kN		
	Max ;	0.27	kN	Max Punch ;	53
Lower Punch :	Average ;	0.12	kN		
	Max ;	0.14	kN	Max Punch ;	27
Ejection Force :	Average ;	0.05	kN		
	Max ;	0.07	kN	Max Punch ;	28

Tablet Data (N/A)

Total Counter :	1642916	Tablets			
A.W.C Counter :	1634838	Tablets			
HEP :	168 (0.0%)	Tablets	LEP :	2 (0.0%)	Tablets
GOOD :	1634668 (100.0%)	Tablets			