

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	Mebeve135mg STMV2A00
User ID :	yu98249	Batch NO. :	MVM2500313
Print Interval :	50000 Tablets	Running Time :	11 Hour 25 Min 24 Sec
Total Counter :	1450618	Total Running Time :	572 Hour 4 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	85	%	Manual ;	20	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		2000000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		30	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		1.00	kN			
				Stop Condition ;		
HSP :	30.0 %	13.81	kN	No		
HEP :	22.0 %	12.96	kN	Yes 10	Rotations 10	Tablets
HCP :	2.0 %	10.83	kN	Yes 15	Times	
Ref :		10.62	kN			
LCP :	2.0 %	10.41	kN	Yes 15	Times	
LEP :	22.0 %	8.28	kN	Yes 10	Rotations 10	Tablets
LSP :	30.0 %	7.44	kN	No		
SD limit :	20.0 %			Yes		
Pre HSP		20.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	1.57	kN	Min :	1.51	kN	Punch NO.;	25
SD :	1.60	%	Max :	1.65	kN	Punch NO.;	44
Mean Main Pressure :	10.79	kN	Min :	10.35	kN	Punch NO.;	17
SD :	2.00	%	Max :	11.26	kN	Punch NO.;	25
Filling Depth :	Increase ;	1274	Times	Decrease ;	1107	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	127200	Tablets/hour
Feeder : Status ;	Auto		Speed ;	17	RPM
Pre Upper Punch Position ;	2.50	mm			
Pre Lower Punch Position ;	5.65	mm	Pre Thickness ;	3.15	mm
Main Upper Punch Position ;	2.20	mm			
Main Lower Punch Position ;	4.03	mm	Main Thickness ;	1.83	mm
Filling Depth :	9.25	mm	Current Cam :	Cam C	
Main Air pressure :	0.825	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	20	Min			
Lower Punch Remain Time (S2):	17	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.17	kN		
	Max ;	0.26	kN	Max Punch ;	53
Lower Punch :	Average ;	0.12	kN		
	Max ;	0.13	kN	Max Punch ;	27
Ejection Force :	Average ;	0.05	kN		
	Max ;	0.06	kN	Max Punch ;	28

Tablet Data (N/A)

Total Counter :	1450618	Tablets			
A.W.C Counter :	1442160	Tablets			
HEP :	192 (0.0%)	Tablets	LEP :	672 (0.0%)	Tablets
GOOD :	1441296 (99.9%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	Mebeve135mg STMV2A00
User ID :	yu98249	Batch NO. :	MVM2500313
Print Interval :	50000 Tablets	Running Time :	11 Hour 25 Min 24 Sec
Total Counter :	1450618	Total Running Time :	572 Hour 4 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	85	%	Manual ;	20	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		2000000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		30	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		1.00	kN			
				Stop Condition ;		
HSP :	30.0 %	17.30	kN	No		
HEP :	22.0 %	16.24	kN	Yes 10	Rotations 10	Tablets
HCP :	2.0 %	13.58	kN	Yes 15	Times	
Ref :		13.31	kN			
LCP :	2.0 %	13.04	kN	Yes 15	Times	
LEP :	22.0 %	10.38	kN	Yes 10	Rotations 10	Tablets
LSP :	30.0 %	9.32	kN	No		
SD limit :	20.0 %			Yes		
Pre HSP		20.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	1.48	kN	Min :	1.44	kN	Punch NO.;	6
SD :	1.50	%	Max :	1.54	kN	Punch NO.;	28
Mean Main Pressure :	13.25	kN	Min :	12.76	kN	Punch NO.;	28
SD :	2.20	%	Max :	13.79	kN	Punch NO.;	40
Filling Depth :	Increase ;	801	Times	Decrease ;	741	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	127200	Tablets/hour
Feeder : Status ;	Auto		Speed ;	17	RPM
Pre Upper Punch Position ;	2.50	mm			
Pre Lower Punch Position ;	5.65	mm	Pre Thickness ;	3.15	mm
Main Upper Punch Position ;	2.20	mm			
Main Lower Punch Position ;	4.08	mm	Main Thickness ;	1.88	mm
Filling Depth :	8.54	mm	Current Cam :	Cam C	
Main Air pressure :	0.825	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	20	Min			
Lower Punch Remain Time (S2):	17	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.17	kN		
	Max ;	0.26	kN	Max Punch ;	53
Lower Punch :	Average ;	0.12	kN		
	Max ;	0.13	kN	Max Punch ;	27
Ejection Force :	Average ;	0.05	kN		
	Max ;	0.06	kN	Max Punch ;	28

Tablet Data (N/A)

Total Counter :	1450618	Tablets			
A.W.C Counter :	1442160	Tablets			
HEP :	192 (0.0%)	Tablets	LEP :	672 (0.0%)	Tablets
GOOD :	1441296 (99.9%)	Tablets			