

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	Mebeve135mg STMV2A00
User ID :	sj97904	Batch NO. :	MVM2500313
Print Interval :	50000 Tablets	Running Time :	12 Hour 36 Min 20 Sec
Total Counter :	1600636	Total Running Time :	573 Hour 15 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	65	%	Manual ;	20	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		2000000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		30	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		1.00	kN			
				Stop Condition ;		
HSP :	30.0 %	13.84	kN	No		
HEP :	22.0 %	12.98	kN	Yes 10	Rotations 10	Tablets
HCP :	2.0 %	10.86	kN	Yes 15	Times	
Ref :		10.64	kN			
LCP :	2.0 %	10.43	kN	Yes 15	Times	
LEP :	22.0 %	8.30	kN	Yes 10	Rotations 10	Tablets
LSP :	30.0 %	7.45	kN	No		
SD limit :	20.0 %			Yes		
Pre HSP		20.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	1.65	kN	Min :	1.57	kN	Punch NO.;	11
SD :	2.00	%	Max :	1.75	kN	Punch NO.;	21
Mean Main Pressure :	10.67	kN	Min :	10.15	kN	Punch NO.;	28
SD :	2.20	%	Max :	11.21	kN	Punch NO.;	52
Filling Depth :	Increase ;	1351	Times	Decrease ;	1160	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	127200	Tablets/hour
Feeder : Status ;	Auto		Speed ;	13	RPM
Pre Upper Punch Position ;	2.50	mm			
Pre Lower Punch Position ;	5.65	mm	Pre Thickness ;	3.15	mm
Main Upper Punch Position ;	2.20	mm			
Main Lower Punch Position ;	4.03	mm	Main Thickness ;	1.83	mm
Filling Depth :	9.30	mm	Current Cam :	Cam C	
Main Air pressure :	0.829	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	14	Min			
Lower Punch Remain Time (S2):	11	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.17	kN		
	Max ;	0.25	kN	Max Punch ;	1
Lower Punch :	Average ;	0.11	kN		
	Max ;	0.13	kN	Max Punch ;	27
Ejection Force :	Average ;	0.05	kN		
	Max ;	0.06	kN	Max Punch ;	28

Tablet Data (N/A)

Total Counter :	1600636	Tablets			
A.W.C Counter :	1590376	Tablets			
HEP :	403 (0.0%)	Tablets	LEP :	688 (0.0%)	Tablets
GOOD :	1589285 (99.9%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	Mebeve135mg STMV2A00
User ID :	sj97904	Batch NO. :	MVM2500313
Print Interval :	50000 Tablets	Running Time :	12 Hour 36 Min 20 Sec
Total Counter :	1600636	Total Running Time :	573 Hour 15 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	55	%	Manual ;	10	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		2000000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		30	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		1.00	kN			
				Stop Condition ;		
HSP :	30.0 %	17.21	kN	No		
HEP :	22.0 %	16.15	kN	Yes 10	Rotations 10	Tablets
HCP :	2.0 %	13.50	kN	Yes 15	Times	
Ref :		13.24	kN			
LCP :	2.0 %	12.97	kN	Yes 15	Times	
LEP :	22.0 %	10.33	kN	Yes 10	Rotations 10	Tablets
LSP :	30.0 %	9.27	kN	No		
SD limit :	20.0 %			Yes		
Pre HSP		20.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	1.53	kN	Min :	1.48	kN	Punch NO.;	38
SD :	1.50	%	Max :	1.57	kN	Punch NO.;	28
Mean Main Pressure :	13.25	kN	Min :	12.61	kN	Punch NO.;	47
SD :	2.50	%	Max :	14.40	kN	Punch NO.;	34
Filling Depth :	Increase ;	867	Times	Decrease ;	771	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	127200	Tablets/hour
Feeder : Status ;	Auto		Speed ;	11	RPM
Pre Upper Punch Position ;	2.50	mm			
Pre Lower Punch Position ;	5.65	mm	Pre Thickness ;	3.15	mm
Main Upper Punch Position ;	2.20	mm			
Main Lower Punch Position ;	4.08	mm	Main Thickness ;	1.88	mm
Filling Depth :	8.78	mm	Current Cam :	Cam C	
Main Air pressure :	0.829	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	14	Min			
Lower Punch Remain Time (S2):	11	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.17	kN		
	Max ;	0.25	kN	Max Punch ;	1
Lower Punch :	Average ;	0.11	kN		
	Max ;	0.13	kN	Max Punch ;	27
Ejection Force :	Average ;	0.05	kN		
	Max ;	0.06	kN	Max Punch ;	28

Tablet Data (N/A)

Total Counter :	1600636	Tablets			
A.W.C Counter :	1590376	Tablets			
HEP :	403 (0.0%)	Tablets	LEP :	688 (0.0%)	Tablets
GOOD :	1589285 (99.9%)	Tablets			