

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	Mebeve135mg STMV2A00
User ID :	sj97904	Batch NO. :	MVM2500313
Print Interval :	50000 Tablets	Running Time :	14 Hour 10 Min 48 Sec
Total Counter :	1800718	Total Running Time :	574 Hour 49 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	65	%	Manual ;	20	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		2000000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		30	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		1.00	kN			
				Stop Condition ;		
HSP :	30.0 %	13.84	kN	No		
HEP :	22.0 %	12.98	kN	Yes 10	Rotations 10	Tablets
HCP :	2.0 %	10.86	kN	Yes 15	Times	
Ref :		10.64	kN			
LCP :	2.0 %	10.43	kN	Yes 15	Times	
LEP :	22.0 %	8.30	kN	Yes 10	Rotations 10	Tablets
LSP :	30.0 %	7.45	kN	No		
SD limit :	20.0 %			Yes		
Pre HSP		20.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	1.63	kN	Min :	1.58	kN	Punch NO.;	27
SD :	1.80	%	Max :	1.71	kN	Punch NO.;	21
Mean Main Pressure :	10.62	kN	Min :	10.10	kN	Punch NO.;	19
SD :	2.00	%	Max :	11.16	kN	Punch NO.;	37
Filling Depth :	Increase ;	1351	Times	Decrease ;	1161	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	127200	Tablets/hour
Feeder : Status ;	Auto		Speed ;	13	RPM
Pre Upper Punch Position ;	2.50	mm			
Pre Lower Punch Position ;	5.65	mm	Pre Thickness ;	3.15	mm
Main Upper Punch Position ;	2.20	mm			
Main Lower Punch Position ;	4.03	mm	Main Thickness ;	1.83	mm
Filling Depth :	9.27	mm	Current Cam :	Cam C	
Main Air pressure :	0.807	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	9	Min			
Lower Punch Remain Time (S2):	16	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.17	kN		
	Max ;	0.26	kN	Max Punch ;	53
Lower Punch :	Average ;	0.11	kN		
	Max ;	0.13	kN	Max Punch ;	27
Ejection Force :	Average ;	0.05	kN		
	Max ;	0.06	kN	Max Punch ;	35

Tablet Data (N/A)

Total Counter :	1800718	Tablets			
A.W.C Counter :	1790451	Tablets			
HEP :	403 (0.0%)	Tablets	LEP :	688 (0.0%)	Tablets
GOOD :	1789360 (99.9%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	Mebeve135mg STMV2A00
User ID :	sj97904	Batch NO. :	MVM2500313
Print Interval :	50000 Tablets	Running Time :	14 Hour 10 Min 48 Sec
Total Counter :	1800718	Total Running Time :	574 Hour 49 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	55	%	Manual ;	10	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		2000000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		30	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		1.00	kN			
				Stop Condition ;		
HSP :	30.0 %	17.21	kN	No		
HEP :	22.0 %	16.15	kN	Yes 10	Rotations 10	Tablets
HCP :	2.0 %	13.50	kN	Yes 15	Times	
Ref :		13.24	kN			
LCP :	2.0 %	12.97	kN	Yes 15	Times	
LEP :	22.0 %	10.33	kN	Yes 10	Rotations 10	Tablets
LSP :	30.0 %	9.27	kN	No		
SD limit :	20.0 %			Yes		
Pre HSP		20.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	1.49	kN	Min :	1.43	kN	Punch NO.;	35
SD :	1.50	%	Max :	1.54	kN	Punch NO.;	21
Mean Main Pressure :	13.27	kN	Min :	12.78	kN	Punch NO.;	2
SD :	1.80	%	Max :	13.90	kN	Punch NO.;	40
Filling Depth :	Increase ;	894	Times	Decrease ;	799	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	127200	Tablets/hour
Feeder : Status ;	Auto		Speed ;	11	RPM
Pre Upper Punch Position ;	2.50	mm			
Pre Lower Punch Position ;	5.65	mm	Pre Thickness ;	3.15	mm
Main Upper Punch Position ;	2.20	mm			
Main Lower Punch Position ;	4.08	mm	Main Thickness ;	1.88	mm
Filling Depth :	8.60	mm	Current Cam :	Cam C	
Main Air pressure :	0.807	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	9	Min			
Lower Punch Remain Time (S2):	16	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.17	kN		
	Max ;	0.27	kN	Max Punch ;	1
Lower Punch :	Average ;	0.11	kN		
	Max ;	0.13	kN	Max Punch ;	27
Ejection Force :	Average ;	0.05	kN		
	Max ;	0.06	kN	Max Punch ;	35

Tablet Data (N/A)

Total Counter :	1800718	Tablets			
A.W.C Counter :	1790451	Tablets			
HEP :	403 (0.0%)	Tablets	LEP :	688 (0.0%)	Tablets
GOOD :	1789360 (99.9%)	Tablets			