

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	Mebeve135mg STMV2A00
User ID :	sj97904	Batch NO. :	MVM2500313
Print Interval :	50000 Tablets	Running Time :	14 Hour 34 Min 25 Sec
Total Counter :	1850744	Total Running Time :	575 Hour 13 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	65	%	Manual ;	20	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		2000000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		30	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		1.00	kN			
				Stop Condition ;		
HSP :	30.0 %	13.84	kN	No		
HEP :	22.0 %	12.98	kN	Yes 10	Rotations 10	Tablets
HCP :	2.0 %	10.86	kN	Yes 15	Times	
Ref :		10.64	kN			
LCP :	2.0 %	10.43	kN	Yes 15	Times	
LEP :	22.0 %	8.30	kN	Yes 10	Rotations 10	Tablets
LSP :	30.0 %	7.45	kN	No		
SD limit :	20.0 %			Yes		
Pre HSP		20.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	1.66	kN	Min :	1.57	kN	Punch NO.;	10
SD :	1.90	%	Max :	1.76	kN	Punch NO.;	44
Mean Main Pressure :	10.77	kN	Min :	10.18	kN	Punch NO.;	28
SD :	2.30	%	Max :	11.47	kN	Punch NO.;	4
Filling Depth :	Increase ;	1363	Times	Decrease ;	1161	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	127200	Tablets/hour
Feeder : Status ;	Auto		Speed ;	13	RPM
Pre Upper Punch Position ;	2.50	mm			
Pre Lower Punch Position ;	5.65	mm	Pre Thickness ;	3.15	mm
Main Upper Punch Position ;	2.20	mm			
Main Lower Punch Position ;	4.03	mm	Main Thickness ;	1.83	mm
Filling Depth :	9.63	mm	Current Cam :	Cam C	
Main Air pressure :	0.809	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	16	Min			
Lower Punch Remain Time (S2):	13	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.17	kN		
	Max ;	0.26	kN	Max Punch ;	1
Lower Punch :	Average ;	0.11	kN		
	Max ;	0.13	kN	Max Punch ;	27
Ejection Force :	Average ;	0.05	kN		
	Max ;	0.06	kN	Max Punch ;	28

Tablet Data (N/A)

Total Counter :	1850744	Tablets			
A.W.C Counter :	1840483	Tablets			
HEP :	405 (0.0%)	Tablets	LEP :	688 (0.0%)	Tablets
GOOD :	1839390 (99.9%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	Mebeve135mg STMV2A00
User ID :	sj97904	Batch NO. :	MVM2500313
Print Interval :	50000 Tablets	Running Time :	14 Hour 34 Min 25 Sec
Total Counter :	1850744	Total Running Time :	575 Hour 13 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	55	%	Manual ;	10	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		2000000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		30	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		1.00	kN			
				Stop Condition ;		
HSP :	30.0 %	17.21	kN	No		
HEP :	22.0 %	16.15	kN	Yes 10	Rotations 10	Tablets
HCP :	2.0 %	13.50	kN	Yes 15	Times	
Ref :		13.24	kN			
LCP :	2.0 %	12.97	kN	Yes 15	Times	
LEP :	22.0 %	10.33	kN	Yes 10	Rotations 10	Tablets
LSP :	30.0 %	9.27	kN	No		
SD limit :	20.0 %			Yes		
Pre HSP		20.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	1.49	kN	Min :	1.43	kN	Punch NO.;	45
SD :	2.10	%	Max :	1.57	kN	Punch NO.;	28
Mean Main Pressure :	12.83	kN	Min :	12.16	kN	Punch NO.;	33
SD :	2.80	%	Max :	13.65	kN	Punch NO.;	53
Filling Depth :	Increase ;	915	Times	Decrease ;	811	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	127200	Tablets/hour
Feeder : Status ;	Auto		Speed ;	11	RPM
Pre Upper Punch Position ;	2.50	mm			
Pre Lower Punch Position ;	5.65	mm	Pre Thickness ;	3.15	mm
Main Upper Punch Position ;	2.20	mm			
Main Lower Punch Position ;	4.08	mm	Main Thickness ;	1.88	mm
Filling Depth :	8.78	mm	Current Cam :	Cam C	
Main Air pressure :	0.809	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	16	Min			
Lower Punch Remain Time (S2):	13	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.18	kN		
	Max ;	0.26	kN	Max Punch ;	1
Lower Punch :	Average ;	0.11	kN		
	Max ;	0.13	kN	Max Punch ;	27
Ejection Force :	Average ;	0.05	kN		
	Max ;	0.06	kN	Max Punch ;	28

Tablet Data (N/A)

Total Counter :	1850744	Tablets			
A.W.C Counter :	1840483	Tablets			
HEP :	405 (0.0%)	Tablets	LEP :	688 (0.0%)	Tablets
GOOD :	1839390 (99.9%)	Tablets			