

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	Pentoxifylline 400mg
User ID :	pb97604	Batch NO. :	PEN TAB XV 25 001
Print Interval :	50000 Tablets	Running Time :	02 Hour 57 Min 43 Sec
Total Counter :	351480	Total Running Time :	578 Hour 57 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	165	%	Manual ;	15	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		600000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		30	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		15	Min	Supply Time ;	10.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		1.00	kN			
				Stop Condition ;		
HSP :	30.0 %	24.21	kN	No		
HEP :	25.0 %	23.28	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	19.00	kN	Yes 15	Times	
Ref :		18.62	kN			
LCP :	2.0 %	18.25	kN	Yes 15	Times	
LEP :	25.0 %	13.97	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	13.04	kN	No		
SD limit :	20.0 %			Yes		
Pre HSP		20.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	2.86	kN	Min :	2.34	kN	Punch NO.;	11
SD :	8.30	%	Max :	3.32	kN	Punch NO.;	30
Mean Main Pressure :	19.05	kN	Min :	15.90	kN	Punch NO.;	11
SD :	7.00	%	Max :	21.87	kN	Punch NO.;	30
Filling Depth :	Increase ; 77	Times	Decrease ;	89	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	18	RPM	Capacity :	114480	Tablets/hour
Feeder : Status ;	Auto		Speed ;	30	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	4.80	mm	Pre Thickness ;	1.81	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	4.04	mm	Main Thickness ;	1.05	mm
Filling Depth :	8.10	mm	Current Cam :	Cam C 8.5-14mm	
Main Air pressure :	0.822	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	12	Min			
Lower Punch Remain Time (S2):	15	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.17	kN		
	Max ;	0.26	kN	Max Punch ;	50
Lower Punch :	Average ;	0.19	kN		
	Max ;	0.30	kN	Max Punch ;	15
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	351480	Tablets			
A.W.C Counter :	335572	Tablets			
HEP :	82 (0.0%)	Tablets	LEP :	32 (0.0%)	Tablets
GOOD :	335458 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	Pentoxifylline 400mg
User ID :	pb97604	Batch NO. :	PEN TAB XV 25 001
Print Interval :	50000 Tablets	Running Time :	02 Hour 57 Min 43 Sec
Total Counter :	351480	Total Running Time :	578 Hour 57 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	166	%	Manual ;	15	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		600000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		30	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		15	Min	Supply Time ;	10.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		1.00	kN			
				Stop Condition ;		
HSP :	30.0 %	24.73	kN	No		
HEP :	25.0 %	23.77	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	19.40	kN	Yes 15	Times	
Ref :		19.02	kN			
LCP :	2.0 %	18.64	kN	Yes 15	Times	
LEP :	25.0 %	14.26	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	13.31	kN	No		
SD limit :	20.0 %			Yes		
Pre HSP		20.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	2.60	kN	Min :	2.21	kN	Punch NO.;	12
SD :	6.90	%	Max :	3.06	kN	Punch NO.;	43
Mean Main Pressure :	19.20	kN	Min :	17.07	kN	Punch NO.;	12
SD :	5.10	%	Max :	21.59	kN	Punch NO.;	43
Filling Depth :	Increase ; 82	Times	Decrease ; 90	Times			

PRODUCTION REPORT

Operation Value

Disk Speed :	18	RPM	Capacity :	114480	Tablets/hour
Feeder : Status ;	Auto		Speed ;	30	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	4.80	mm	Pre Thickness ;	1.81	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	4.12	mm	Main Thickness ;	1.12	mm
Filling Depth :	8.06	mm	Current Cam :	Cam C 8.5-14mm	
Main Air pressure :	0.822	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	12	Min			
Lower Punch Remain Time (S2):	15	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.17	kN		
	Max ;	0.26	kN	Max Punch ;	50
Lower Punch :	Average ;	0.19	kN		
	Max ;	0.30	kN	Max Punch ;	15
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	351480	Tablets			
A.W.C Counter :	335572	Tablets			
HEP :	82 (0.0%)	Tablets	LEP :	32 (0.0%)	Tablets
GOOD :	335458 (100.0%)	Tablets			