

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	ACICLO400MG,STV11B0
User ID :	dm98328	Batch NO. :	VIM2500540
Print Interval :	50000 Tablets	Running Time :	08 Hour 22 Min 58 Sec
Total Counter :	1300612	Total Running Time :	589 Hour 32 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	90	%	Manual ;	15	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		1500000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		30	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		15	Min	Supply Time ;	10.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		1.00	kN			
				Stop Condition ;		
HSP :	30.0 %	17.57	kN	No		
HEP :	25.0 %	16.89	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	13.79	kN	Yes 15	Times	
Ref :		13.52	kN			
LCP :	2.0 %	13.25	kN	Yes 15	Times	
LEP :	25.0 %	10.14	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	9.46	kN	No		
SD limit :	20.0 %			Yes		
Pre HSP		20.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	2.17	kN	Min :	2.09	kN	Punch NO.;	18
SD :	1.40	%	Max :	2.25	kN	Punch NO.;	32
Mean Main Pressure :	13.31	kN	Min :	12.90	kN	Punch NO.;	18
SD :	1.10	%	Max :	13.64	kN	Punch NO.;	32
Filling Depth :	Increase ; 1	Times	Decrease ;	14	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	156000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	18	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	6.30	mm	Pre Thickness ;	3.31	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.13	mm	Main Thickness ;	2.14	mm
Filling Depth :	7.16	mm	Current Cam :	Cam C	
Main Air pressure :	0.803	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	23	Min			
Lower Punch Remain Time (S2):	3	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.20	kN		
	Max ;	0.27	kN	Max Punch ;	30
Lower Punch :	Average ;	0.11	kN		
	Max ;	0.17	kN	Max Punch ;	41
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	1300612	Tablets			
A.W.C Counter :	1293769	Tablets			
HEP :	27 (0.0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	1293742 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	ACICLO400MG,STV11B0
User ID :	dm98328	Batch NO. :	VIM2500540
Print Interval :	50000 Tablets	Running Time :	08 Hour 22 Min 58 Sec
Total Counter :	1300612	Total Running Time :	589 Hour 32 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	90	%	Manual ;	15	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		1500000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		30	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		15	Min	Supply Time ;	10.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		1.00	kN			
				Stop Condition ;		
HSP :	30.0 %	19.31	kN	No		
HEP :	25.0 %	18.57	kN	Yes	10	Rotations 15 Tablets
HCP :	2.0 %	15.15	kN	Yes	15	Times
Ref :		14.85	kN			
LCP :	2.0 %	14.56	kN	Yes	15	Times
LEP :	25.0 %	11.14	kN	Yes	10	Rotations 15 Tablets
LSP :	30.0 %	10.40	kN	No		
SD limit :	20.0 %			Yes		
Pre HSP		20.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	2.15	kN	Min :	2.03	kN	Punch NO.;	20
SD :	2.20	%	Max :	2.24	kN	Punch NO.;	10
Mean Main Pressure :	14.95	kN	Min :	14.51	kN	Punch NO.;	1
SD :	1.60	%	Max :	15.57	kN	Punch NO.;	42
Filling Depth :	Increase ;	2	Times	Decrease ;	6	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	156000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	18	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	6.30	mm	Pre Thickness ;	3.31	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.23	mm	Main Thickness ;	2.24	mm
Filling Depth :	7.31	mm	Current Cam :	Cam C	
Main Air pressure :	0.803	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	23	Min			
Lower Punch Remain Time (S2):	3	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.20	kN		
	Max ;	0.27	kN	Max Punch ;	30
Lower Punch :	Average ;	0.11	kN		
	Max ;	0.14	kN	Max Punch ;	41
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	1300612	Tablets			
A.W.C Counter :	1293769	Tablets			
HEP :	27 (0.0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	1293742 (100.0%)	Tablets			