

## PRODUCTION REPORT

### Product Information

|                  |               |                      |                       |
|------------------|---------------|----------------------|-----------------------|
| Machine Name :   | VANTIX P720D  | Product Name :       | ACICLO400MG,STV11B0   |
| User ID :        | pb97604       | Batch NO. :          | VIM2500740            |
| Print Interval : | 50000 Tablets | Running Time :       | 05 Hour 27 Min 52 Sec |
| Total Counter :  | 850224        | Total Running Time : | 605 Hour 50 Min       |
| Station :        | Station 1     |                      |                       |

### Setting Value

|                                    |             |          |         |                    |       |                      |
|------------------------------------|-------------|----------|---------|--------------------|-------|----------------------|
| Feeder :                           | Auto ;      | 90       | %       | Manual ;           | 15    | RPM                  |
| Filling Cam :                      |             | Cam C    |         | Cam Range :        | Min : | 6.50 mm              |
|                                    |             | 8.5-14mm |         |                    | Max : | 12.00 mm             |
| Target Quantity :                  |             | 1500000  | Tablets |                    |       |                      |
| Air Pressure Low Limit :           |             | 0.400    | MPa     |                    |       |                      |
| Oil Lubrication :                  |             |          |         |                    |       |                      |
| Upper Punch Interval Time(S1) ;    |             | 30       | Min     | Supply Time ;      | 0.5   | Sec                  |
| Lower Punch Interval Time(S2) ;    |             | 15       | Min     | Supply Time ;      | 10.0  | Sec                  |
| Powder Supply Time :               |             | 5.0      | Sec     |                    |       |                      |
| Initial Reject Time :              |             | 2        | Tablets |                    |       |                      |
| Upper Punch Tightness High Limit : |             | 1.00     | kN      |                    |       |                      |
| Lower Punch Tightness High Limit : |             | 1.00     | kN      |                    |       |                      |
| Ejecting Force High Limit :        |             | 1.00     | kN      |                    |       |                      |
|                                    |             |          |         | Stop Condition ;   |       |                      |
| HSP :                              | 30.0 %      | 16.50    | kN      | No                 |       |                      |
| HEP :                              | 25.0 %      | 15.87    | kN      | Yes                | 10    | Rotations 15 Tablets |
| HCP :                              | 2.0 %       | 12.95    | kN      | Yes                | 15    | Times                |
| Ref :                              |             | 12.70    | kN      |                    |       |                      |
| LCP :                              | 2.0 %       | 12.44    | kN      | Yes                | 15    | Times                |
| LEP :                              | 25.0 %      | 9.52     | kN      | Yes                | 10    | Rotations 15 Tablets |
| LSP :                              | 30.0 %      | 8.89     | kN      | No                 |       |                      |
| SD limit :                         | 20.0 %      |          |         | Yes                |       |                      |
| Pre HSP                            |             | 20.00    | kN      | Yes                |       |                      |
| Mean Calculation range :           | 2 Rotations |          |         | Calculation Pass : | 2     | Rotations            |
| Empty Punch No. :                  | None        |          |         |                    |       |                      |

### Pressure Data

|                      |            |    |       |            |    |            |    |
|----------------------|------------|----|-------|------------|----|------------|----|
| Mean Pre Pressure :  | 2.17       | kN | Min : | 2.09       | kN | Punch NO.; | 18 |
| SD :                 | 1.50       | %  | Max : | 2.26       | kN | Punch NO.; | 32 |
| Mean Main Pressure : | 12.75      | kN | Min : | 12.21      | kN | Punch NO.; | 18 |
| SD :                 | 1.40       | %  | Max : | 13.14      | kN | Punch NO.; | 50 |
| Filling Depth :      | Increase ; | 15 | Times | Decrease ; | 1  | Times      |    |

## PRODUCTION REPORT

### Operation Value

|                               |         |     |                  |          |              |
|-------------------------------|---------|-----|------------------|----------|--------------|
| Disk Speed :                  | 20      | RPM | Capacity :       | 156000   | Tablets/hour |
| Feeder : Status ;             | Auto    |     | Speed ;          | 18       | RPM          |
| Pre Upper Punch Position ;    | 2.99    | mm  |                  |          |              |
| Pre Lower Punch Position ;    | 6.30    | mm  | Pre Thickness ;  | 3.31     | mm           |
| Main Upper Punch Position ;   | 2.99    | mm  |                  |          |              |
| Main Lower Punch Position ;   | 5.13    | mm  | Main Thickness ; | 2.14     | mm           |
| Filling Depth :               | 7.40    | mm  | Current Cam :    | Cam C    |              |
| Main Air pressure :           | 0.791   | MPa |                  | 8.5-14mm |              |
| Oil Lubrication status :      |         |     |                  |          |              |
| Upper Punch Remain Time (S1): | 23      | Min |                  |          |              |
| Lower Punch Remain Time (S2): | 9       | Min |                  |          |              |
| Lower Head Remain Time (S3):  | 0       | Min |                  |          |              |
| Powder Status :               | Disable |     | Dust Collector : | Off      |              |
| Initial Reject :              | Off     |     | Buzzer :         | Off      |              |

### Tightness

|                  |           |      |    |             |    |
|------------------|-----------|------|----|-------------|----|
| Upper Punch :    | Average ; | 0.19 | kN |             |    |
|                  | Max ;     | 0.25 | kN | Max Punch ; | 59 |
| Lower Punch :    | Average ; | 0.11 | kN |             |    |
|                  | Max ;     | 0.15 | kN | Max Punch ; | 41 |
| Ejection Force : | Average ; | 0.00 | kN |             |    |
|                  | Max ;     | 0.00 | kN | Max Punch ; | 0  |

### Tablet Data (N/A)

|                 |                    |         |       |           |         |
|-----------------|--------------------|---------|-------|-----------|---------|
| Total Counter : | 850224             | Tablets |       |           |         |
| A.W.C Counter : | 848581             | Tablets |       |           |         |
| HEP :           | 0 (0%)             | Tablets | LEP : | 43 (0.0%) | Tablets |
| GOOD :          | 848538<br>(100.0%) | Tablets |       |           |         |

## PRODUCTION REPORT

### Product Information

|                  |               |                      |                       |
|------------------|---------------|----------------------|-----------------------|
| Machine Name :   | VANTIX P720D  | Product Name :       | ACICLO400MG,STV11B0   |
| User ID :        | pb97604       | Batch NO. :          | VIM2500740            |
| Print Interval : | 50000 Tablets | Running Time :       | 05 Hour 27 Min 52 Sec |
| Total Counter :  | 850224        | Total Running Time : | 605 Hour 50 Min       |
| Station :        | Station 2     |                      |                       |

### Setting Value

|                                    |        |           |         |                    |       |                      |
|------------------------------------|--------|-----------|---------|--------------------|-------|----------------------|
| Feeder :                           | Auto ; | 90        | %       | Manual ;           | 15    | RPM                  |
| Filling Cam :                      |        | Cam C     |         | Cam Range :        | Min : | 6.50 mm              |
|                                    |        | 8.5-14mm  |         |                    | Max : | 12.00 mm             |
| Target Quantity :                  |        | 1500000   | Tablets |                    |       |                      |
| Air Pressure Low Limit :           |        | 0.400     | MPa     |                    |       |                      |
| Oil Lubrication :                  |        |           |         |                    |       |                      |
| Upper Punch Interval Time(S1) ;    |        | 30        | Min     | Supply Time ;      | 0.5   | Sec                  |
| Lower Punch Interval Time(S2) ;    |        | 15        | Min     | Supply Time ;      | 10.0  | Sec                  |
| Powder Supply Time :               |        | 5.0       | Sec     |                    |       |                      |
| Initial Reject Time :              |        | 2         | Tablets |                    |       |                      |
| Upper Punch Tightness High Limit : |        | 1.00      | kN      |                    |       |                      |
| Lower Punch Tightness High Limit : |        | 1.00      | kN      |                    |       |                      |
| Ejecting Force High Limit :        |        | 1.00      | kN      |                    |       |                      |
|                                    |        |           |         | Stop Condition ;   |       |                      |
| HSP :                              | 30.0 % | 19.31     | kN      | No                 |       |                      |
| HEP :                              | 25.0 % | 18.57     | kN      | Yes                | 10    | Rotations 15 Tablets |
| HCP :                              | 2.0 %  | 15.15     | kN      | Yes                | 15    | Times                |
| Ref :                              |        | 14.85     | kN      |                    |       |                      |
| LCP :                              | 2.0 %  | 14.56     | kN      | Yes                | 15    | Times                |
| LEP :                              | 25.0 % | 11.14     | kN      | Yes                | 10    | Rotations 15 Tablets |
| LSP :                              | 30.0 % | 10.40     | kN      | No                 |       |                      |
| SD limit :                         | 20.0 % |           |         | Yes                |       |                      |
| Pre HSP                            |        | 20.00     | kN      | Yes                |       |                      |
| Mean Calculation range :           | 2      | Rotations |         | Calculation Pass : | 2     | Rotations            |
| Empty Punch No. :                  | N      |           |         |                    |       |                      |

### Pressure Data

|                      |            |    |       |            |    |            |    |
|----------------------|------------|----|-------|------------|----|------------|----|
| Mean Pre Pressure :  | 2.04       | kN | Min : | 1.96       | kN | Punch NO.; | 35 |
| SD :                 | 1.80       | %  | Max : | 2.14       | kN | Punch NO.; | 50 |
| Mean Main Pressure : | 14.79      | kN | Min : | 14.19      | kN | Punch NO.; | 35 |
| SD :                 | 1.50       | %  | Max : | 15.35      | kN | Punch NO.; | 50 |
| Filling Depth :      | Increase ; | 7  | Times | Decrease ; | 3  | Times      |    |

## PRODUCTION REPORT

### Operation Value

|                               |         |     |                  |          |              |
|-------------------------------|---------|-----|------------------|----------|--------------|
| Disk Speed :                  | 20      | RPM | Capacity :       | 156000   | Tablets/hour |
| Feeder : Status ;             | Auto    |     | Speed ;          | 18       | RPM          |
| Pre Upper Punch Position ;    | 2.99    | mm  |                  |          |              |
| Pre Lower Punch Position ;    | 6.30    | mm  | Pre Thickness ;  | 3.31     | mm           |
| Main Upper Punch Position ;   | 2.99    | mm  |                  |          |              |
| Main Lower Punch Position ;   | 5.23    | mm  | Main Thickness ; | 2.24     | mm           |
| Filling Depth :               | 7.31    | mm  | Current Cam :    | Cam C    |              |
| Main Air pressure :           | 0.791   | MPa |                  | 8.5-14mm |              |
| Oil Lubrication status :      |         |     |                  |          |              |
| Upper Punch Remain Time (S1): | 23      | Min |                  |          |              |
| Lower Punch Remain Time (S2): | 9       | Min |                  |          |              |
| Lower Head Remain Time (S3):  | 0       | Min |                  |          |              |
| Powder Status :               | Disable |     | Dust Collector : | Off      |              |
| Initial Reject :              | Off     |     | Buzzer :         | Off      |              |

### Tightness

|                  |           |      |    |             |    |
|------------------|-----------|------|----|-------------|----|
| Upper Punch :    | Average ; | 0.19 | kN |             |    |
|                  | Max ;     | 0.25 | kN | Max Punch ; | 30 |
| Lower Punch :    | Average ; | 0.11 | kN |             |    |
|                  | Max ;     | 0.15 | kN | Max Punch ; | 41 |
| Ejection Force : | Average ; | 0.00 | kN |             |    |
|                  | Max ;     | 0.00 | kN | Max Punch ; | 0  |

### Tablet Data (N/A)

|                 |                    |         |       |           |         |
|-----------------|--------------------|---------|-------|-----------|---------|
| Total Counter : | 850224             | Tablets |       |           |         |
| A.W.C Counter : | 848581             | Tablets |       |           |         |
| HEP :           | 0 (0%)             | Tablets | LEP : | 43 (0.0%) | Tablets |
| GOOD :          | 848538<br>(100.0%) | Tablets |       |           |         |