

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	ACICLO400MG,STV11B0
User ID :	pb97604	Batch NO. :	VIM2500740
Print Interval :	50000 Tablets	Running Time :	09 Hour 19 Min 12 Sec
Total Counter :	1450438	Total Running Time :	609 Hour 41 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	90	%	Manual ;	15	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		1500000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		30	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		15	Min	Supply Time ;	10.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		1.00	kN			
				Stop Condition ;		
HSP :	30.0 %	16.54	kN	No		
HEP :	25.0 %	15.91	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	12.98	kN	Yes 15	Times	
Ref :		12.73	kN			
LCP :	2.0 %	12.47	kN	Yes 15	Times	
LEP :	25.0 %	9.54	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	8.91	kN	No		
SD limit :	20.0 %			Yes		
Pre HSP		20.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	2.13	kN	Min :	2.07	kN	Punch NO.;	8
SD :	1.60	%	Max :	2.22	kN	Punch NO.;	41
Mean Main Pressure :	12.66	kN	Min :	12.26	kN	Punch NO.;	33
SD :	1.30	%	Max :	13.04	kN	Punch NO.;	41
Filling Depth :	Increase ; 15	Times	Decrease ;	1	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	156000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	18	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	6.30	mm	Pre Thickness ;	3.31	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.13	mm	Main Thickness ;	2.14	mm
Filling Depth :	7.40	mm	Current Cam :	Cam C	
Main Air pressure :	0.826	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	23	Min			
Lower Punch Remain Time (S2):	9	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.19	kN		
	Max ;	0.24	kN	Max Punch ;	4
Lower Punch :	Average ;	0.12	kN		
	Max ;	0.18	kN	Max Punch ;	26
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	1450438	Tablets			
A.W.C Counter :	1448791	Tablets			
HEP :	0 (0%)	Tablets	LEP :	43 (0.0%)	Tablets
GOOD :	1448748 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	ACICLO400MG,STV11B0
User ID :	pb97604	Batch NO. :	VIM2500740
Print Interval :	50000 Tablets	Running Time :	09 Hour 19 Min 12 Sec
Total Counter :	1450438	Total Running Time :	609 Hour 41 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	90	%	Manual ;	15	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		1500000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		30	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		15	Min	Supply Time ;	10.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		1.00	kN			
				Stop Condition ;		
HSP :	30.0 %	19.21	kN	No		
HEP :	25.0 %	18.47	kN	Yes	10	Rotations 15 Tablets
HCP :	2.0 %	15.07	kN	Yes	15	Times
Ref :		14.78	kN			
LCP :	2.0 %	14.48	kN	Yes	15	Times
LEP :	25.0 %	11.08	kN	Yes	10	Rotations 15 Tablets
LSP :	30.0 %	10.34	kN	No		
SD limit :	20.0 %			Yes		
Pre HSP		20.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	SD :	2.01	kN	Min :	1.95	kN	Punch NO.;	36
		1.50	%	Max :	2.10	kN	Punch NO.;	12
Mean Main Pressure :		14.75	kN	Min :	14.26	kN	Punch NO.;	36
	SD :	1.30	%	Max :	15.23	kN	Punch NO.;	16
Filling Depth :	Increase ;	7	Times	Decrease ;	3	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	156000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	18	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	6.30	mm	Pre Thickness ;	3.31	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.23	mm	Main Thickness ;	2.24	mm
Filling Depth :	7.31	mm	Current Cam :	Cam C 8.5-14mm	
Main Air pressure :	0.826	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	23	Min			
Lower Punch Remain Time (S2):	9	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.19	kN		
	Max ;	0.25	kN	Max Punch ;	27
Lower Punch :	Average ;	0.12	kN		
	Max ;	0.18	kN	Max Punch ;	26
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	1450438	Tablets			
A.W.C Counter :	1448791	Tablets			
HEP :	0 (0%)	Tablets	LEP :	43 (0.0%)	Tablets
GOOD :	1448748 (100.0%)	Tablets			