

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	SETRA 50 MG,STSH4A00
User ID :	pb97604	Batch NO. :	SHM2500350
Print Interval :	50000 Tablets	Running Time :	00 Hour 09 Min 04 Sec
Total Counter :	36894	Total Running Time :	610 Hour 5 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	33	%	Manual ;	15	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		6000000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		30	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		15	Min	Supply Time ;	10.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		1.00	kN			
				Stop Condition ;		
HSP :	30.0 %	14.90	kN	No		
HEP :	25.0 %	14.32	kN	Yes	10	Rotations 15 Tablets
HCP :	2.0 %	11.69	kN	Yes	15	Times
Ref :		11.46	kN			
LCP :	2.0 %	11.23	kN	Yes	15	Times
LEP :	25.0 %	8.59	kN	Yes	10	Rotations 15 Tablets
LSP :	30.0 %	8.02	kN	No		
SD limit :	20.0 %			Yes		
Pre HSP		20.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	SD :	1.06	kN	Min :	1.01	kN	Punch NO.;	16
		1.60	%	Max :	1.11	kN	Punch NO.;	58
Mean Main Pressure :		11.47	kN	Min :	10.44	kN	Punch NO.;	70
	SD :	3.40	%	Max :	12.68	kN	Punch NO.;	60
Filling Depth :	Increase ;	17	Times	Decrease ;	16	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	258720	Tablets/hour
Feeder : Status ;	Auto		Speed ;	9	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	5.80	mm	Pre Thickness ;	2.80	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	4.47	mm	Main Thickness ;	1.47	mm
Filling Depth :	5.16	mm	Current Cam :	Cam B	
Main Air pressure :	0.782	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	18	Min			
Lower Punch Remain Time (S2):	4	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.07	kN		
	Max ;	0.13	kN	Max Punch ;	1
Lower Punch :	Average ;	0.11	kN		
	Max ;	0.18	kN	Max Punch ;	56
Ejection Force :	Average ;	0.04	kN		
	Max ;	0.13	kN	Max Punch ;	61

Tablet Data (N/A)

Total Counter :	36894	Tablets			
A.W.C Counter :	33581	Tablets			
HEP :	0 (0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	33581 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	SETRA 50 MG,STSH4A00
User ID :	pb97604	Batch NO. :	SHM2500350
Print Interval :	50000 Tablets	Running Time :	00 Hour 09 Min 05 Sec
Total Counter :	36964	Total Running Time :	610 Hour 5 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	35	%	Manual ;	15	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		6000000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		30	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		15	Min	Supply Time ;	10.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		1.00	kN			
				Stop Condition ;		
HSP :	30.0 %	16.51	kN	No		
HEP :	25.0 %	15.87	kN	Yes	10	Rotations 15 Tablets
HCP :	2.0 %	12.95	kN	Yes	15	Times
Ref :		12.70	kN			
LCP :	2.0 %	12.44	kN	Yes	15	Times
LEP :	25.0 %	9.52	kN	Yes	10	Rotations 15 Tablets
LSP :	30.0 %	8.89	kN	No		
SD limit :	20.0 %			Yes		
Pre HSP		20.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	SD :	1.09	kN	Min :	1.04	kN	Punch NO.;	70
		2.20	%	Max :	1.16	kN	Punch NO.;	76
Mean Main Pressure :		12.56	kN	Min :	11.94	kN	Punch NO.;	70
	SD :	2.90	%	Max :	13.87	kN	Punch NO.;	76
Filling Depth :	Increase ;	12	Times	Decrease ;	16	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	258720	Tablets/hour
Feeder : Status ;	Auto		Speed ;	10	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	5.70	mm	Pre Thickness ;	2.70	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	4.60	mm	Main Thickness ;	1.60	mm
Filling Depth :	5.14	mm	Current Cam :	Cam B	
Main Air pressure :	0.781	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	18	Min			
Lower Punch Remain Time (S2):	4	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.07	kN		
	Max ;	0.11	kN	Max Punch ;	1
Lower Punch :	Average ;	0.11	kN		
	Max ;	0.18	kN	Max Punch ;	56
Ejection Force :	Average ;	0.04	kN		
	Max ;	0.13	kN	Max Punch ;	61

Tablet Data (N/A)

Total Counter :	36964	Tablets			
A.W.C Counter :	33581	Tablets			
HEP :	0 (0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	33581 (100.0%)	Tablets			