

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	SETRA 50 MG,STSH4A00
User ID :	sj97904	Batch NO. :	SHM2500350
Print Interval :	50000 Tablets	Running Time :	06 Hour 46 Min 22 Sec
Total Counter :	1751274	Total Running Time :	616 Hour 43 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	22	%	Manual ;	15	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		6000000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		30	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		15	Min	Supply Time ;	10.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		1.00	kN			
				Stop Condition ;		
HSP :	30.0 %	17.94	kN	No		
HEP :	25.0 %	17.25	kN	Yes	10	Rotations 15 Tablets
HCP :	2.0 %	14.08	kN	Yes	15	Times
Ref :		13.80	kN			
LCP :	2.0 %	13.53	kN	Yes	15	Times
LEP :	25.0 %	10.35	kN	Yes	10	Rotations 15 Tablets
LSP :	30.0 %	9.66	kN	No		
SD limit :	20.0 %			Yes		
Pre HSP		20.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	0.92	kN	Min :	0.87	kN	Punch NO.;	73
SD :	2.20	%	Max :	1.00	kN	Punch NO.;	76
Mean Main Pressure :	13.81	kN	Min :	12.86	kN	Punch NO.;	73
SD :	3.70	%	Max :	16.32	kN	Punch NO.;	76
Filling Depth :	Increase ;	142	Times	Decrease ;	238	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	258720	Tablets/hour
Feeder : Status ;	Auto		Speed ;	6	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	5.80	mm	Pre Thickness ;	2.80	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	4.44	mm	Main Thickness ;	1.44	mm
Filling Depth :	5.12	mm	Current Cam :	Cam B	
Main Air pressure :	0.797	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	11	Min			
Lower Punch Remain Time (S2):	2	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	On	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.16	kN		
	Max ;	0.20	kN	Max Punch ;	61
Lower Punch :	Average ;	0.11	kN		
	Max ;	0.15	kN	Max Punch ;	46
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	1751274	Tablets			
A.W.C Counter :	1747652	Tablets			
HEP :	16 (0.0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	1747636 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	SETRA 50 MG,STSH4A00
User ID :	sj97904	Batch NO. :	SHM2500350
Print Interval :	50000 Tablets	Running Time :	06 Hour 46 Min 22 Sec
Total Counter :	1751274	Total Running Time :	616 Hour 43 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	25	%	Manual ;	15	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		6000000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		30	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		15	Min	Supply Time ;	10.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		1.00	kN			
				Stop Condition ;		
HSP :	30.0 %	19.03	kN	No		
HEP :	25.0 %	18.30	kN	Yes	10	Rotations 15 Tablets
HCP :	2.0 %	14.93	kN	Yes	15	Times
Ref :		14.64	kN			
LCP :	2.0 %	14.35	kN	Yes	15	Times
LEP :	25.0 %	10.98	kN	Yes	10	Rotations 15 Tablets
LSP :	30.0 %	10.25	kN	No		
SD limit :	20.0 %			Yes		
Pre HSP		20.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	1.02	kN	Min :	0.97	kN	Punch NO.;	12
SD :	2.30	%	Max :	1.11	kN	Punch NO.;	76
Mean Main Pressure :	14.69	kN	Min :	13.38	kN	Punch NO.;	19
SD :	4.70	%	Max :	17.35	kN	Punch NO.;	76
Filling Depth :	Increase ;	76	Times	Decrease ;	128	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	258720	Tablets/hour
Feeder : Status ;	Auto		Speed ;	7	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	5.70	mm	Pre Thickness ;	2.70	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	4.59	mm	Main Thickness ;	1.59	mm
Filling Depth :	5.46	mm	Current Cam :	Cam B	
Main Air pressure :	0.797	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	11	Min			
Lower Punch Remain Time (S2):	2	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	On	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.16	kN		
	Max ;	0.20	kN	Max Punch ;	67
Lower Punch :	Average ;	0.11	kN		
	Max ;	0.15	kN	Max Punch ;	46
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	1751274	Tablets			
A.W.C Counter :	1747652	Tablets			
HEP :	16 (0.0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	1747636 (100.0%)	Tablets			