

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	SETRA 50 MG,STSH4A00
User ID :	sj97904	Batch NO. :	SHM2500350
Print Interval :	50000 Tablets	Running Time :	10 Hour 18 Min 25 Sec
Total Counter :	2667080	Total Running Time :	620 Hour 15 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	22	%	Manual ;	15	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		6000000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		30	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		15	Min	Supply Time ;	10.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		1.00	kN			
				Stop Condition ;		
HSP :	30.0 %	18.38	kN	No		
HEP :	25.0 %	17.67	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	14.42	kN	Yes 15	Times	
Ref :		14.14	kN			
LCP :	2.0 %	13.86	kN	Yes 15	Times	
LEP :	25.0 %	10.60	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	9.90	kN	No		
SD limit :	20.0 %			Yes		
Pre HSP		20.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	1.02	kN	Min :	0.98	kN	Punch NO.;	3
SD :	2.30	%	Max :	1.11	kN	Punch NO.;	76
Mean Main Pressure :	14.19	kN	Min :	13.23	kN	Punch NO.;	70
SD :	3.90	%	Max :	16.42	kN	Punch NO.;	76
Filling Depth :	Increase ;	151	Times	Decrease ;	182	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	258720	Tablets/hour
Feeder : Status ;	Auto		Speed ;	6	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	5.80	mm	Pre Thickness ;	2.81	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	4.47	mm	Main Thickness ;	1.48	mm
Filling Depth :	5.23	mm	Current Cam :	Cam B	
Main Air pressure :	0.743	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	30	Min			
Lower Punch Remain Time (S2):	7	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.17	kN		
	Max ;	0.22	kN	Max Punch ;	61
Lower Punch :	Average ;	0.10	kN		
	Max ;	0.14	kN	Max Punch ;	62
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	2667080	Tablets			
A.W.C Counter :	2662499	Tablets			
HEP :	92 (0.0%)	Tablets	LEP :	99 (0.0%)	Tablets
GOOD :	2662308 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	SETRA 50 MG,STSH4A00
User ID :	sj97904	Batch NO. :	SHM2500350
Print Interval :	50000 Tablets	Running Time :	10 Hour 18 Min 25 Sec
Total Counter :	2667080	Total Running Time :	620 Hour 15 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	25	%	Manual ;	15	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		6000000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		30	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		15	Min	Supply Time ;	10.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		1.00	kN			
				Stop Condition ;		
HSP :	30.0 %	19.00	kN	No		
HEP :	25.0 %	18.27	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	14.91	kN	Yes 15	Times	
Ref :		14.61	kN			
LCP :	2.0 %	14.32	kN	Yes 15	Times	
LEP :	25.0 %	10.96	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	10.23	kN	No		
SD limit :	20.0 %			Yes		
Pre HSP		20.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	1.10	kN	Min :	1.06	kN	Punch NO.;	29
SD :	2.10	%	Max :	1.19	kN	Punch NO.;	76
Mean Main Pressure :	14.55	kN	Min :	13.55	kN	Punch NO.;	14
SD :	4.50	%	Max :	17.08	kN	Punch NO.;	76
Filling Depth :	Increase ;	64	Times	Decrease ;	89	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	258720	Tablets/hour
Feeder : Status ;	Auto		Speed ;	7	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	5.70	mm	Pre Thickness ;	2.71	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	4.60	mm	Main Thickness ;	1.60	mm
Filling Depth :	5.53	mm	Current Cam :	Cam B	
Main Air pressure :	0.743	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	30	Min			
Lower Punch Remain Time (S2):	7	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.17	kN		
	Max ;	0.24	kN	Max Punch ;	61
Lower Punch :	Average ;	0.10	kN		
	Max ;	0.14	kN	Max Punch ;	62
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	2667080	Tablets			
A.W.C Counter :	2662499	Tablets			
HEP :	92 (0.0%)	Tablets	LEP :	99 (0.0%)	Tablets
GOOD :	2662308 (100.0%)	Tablets			