

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	SETRA 50 MG,STSH4A00
User ID :	yu98249	Batch NO. :	SHM2500350
Print Interval :	50000 Tablets	Running Time :	16 Hour 05 Min 53 Sec
Total Counter :	4168114	Total Running Time :	626 Hour 3 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	22	%	Manual ;	15	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		6000000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		30	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		15	Min	Supply Time ;	10.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		1.00	kN			
				Stop Condition ;		
HSP :	30.0 %	18.09	kN	No		
HEP :	25.0 %	17.39	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	14.19	kN	Yes 15	Times	
Ref :		13.91	kN			
LCP :	2.0 %	13.64	kN	Yes 15	Times	
LEP :	25.0 %	10.44	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	9.74	kN	No		
SD limit :	20.0 %			Yes		
Pre HSP		20.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	1.07	kN	Min :	1.04	kN	Punch NO.;	13
SD :	2.20	%	Max :	1.15	kN	Punch NO.;	75
Mean Main Pressure :	14.04	kN	Min :	12.96	kN	Punch NO.;	23
SD :	4.40	%	Max :	16.37	kN	Punch NO.;	35
Filling Depth :	Increase ;	314	Times	Decrease ;	335	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	258720	Tablets/hour
Feeder : Status ;	Auto		Speed ;	6	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	5.80	mm	Pre Thickness ;	2.81	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	4.49	mm	Main Thickness ;	1.50	mm
Filling Depth :	5.45	mm	Current Cam :	Cam B	
Main Air pressure :	0.792	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	15	Min			
Lower Punch Remain Time (S2):	11	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.18	kN		
	Max ;	0.26	kN	Max Punch ;	29
Lower Punch :	Average ;	0.09	kN		
	Max ;	0.12	kN	Max Punch ;	1
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.01	kN	Max Punch ;	35

Tablet Data (N/A)

Total Counter :	4168114	Tablets			
A.W.C Counter :	4163460	Tablets			
HEP :	158 (0.0%)	Tablets	LEP :	99 (0.0%)	Tablets
GOOD :	4163203 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	SETRA 50 MG,STSH4A00
User ID :	yu98249	Batch NO. :	SHM2500350
Print Interval :	50000 Tablets	Running Time :	16 Hour 05 Min 53 Sec
Total Counter :	4168114	Total Running Time :	626 Hour 3 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	25	%	Manual ;	15	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		6000000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		30	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		15	Min	Supply Time ;	10.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		1.00	kN			
				Stop Condition ;		
HSP :	30.0 %	19.06	kN	No		
HEP :	25.0 %	18.33	kN	Yes	10	Rotations 15 Tablets
HCP :	2.0 %	14.96	kN	Yes	15	Times
Ref :		14.67	kN			
LCP :	2.0 %	14.37	kN	Yes	15	Times
LEP :	25.0 %	11.00	kN	Yes	10	Rotations 15 Tablets
LSP :	30.0 %	10.27	kN	No		
SD limit :	20.0 %			Yes		
Pre HSP		20.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	1.16	kN	Min :	1.11	kN	Punch NO.;	13
SD :	2.10	%	Max :	1.25	kN	Punch NO.;	35
Mean Main Pressure :	14.58	kN	Min :	13.39	kN	Punch NO.;	11
SD :	4.70	%	Max :	17.13	kN	Punch NO.;	76
Filling Depth :	Increase ;	137	Times	Decrease ;	173	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	258720	Tablets/hour
Feeder : Status ;	Auto		Speed ;	7	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	5.70	mm	Pre Thickness ;	2.71	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	4.62	mm	Main Thickness ;	1.62	mm
Filling Depth :	5.52	mm	Current Cam :	Cam B	
Main Air pressure :	0.792	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	15	Min			
Lower Punch Remain Time (S2):	11	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.18	kN		
	Max ;	0.29	kN	Max Punch ;	29
Lower Punch :	Average ;	0.09	kN		
	Max ;	0.12	kN	Max Punch ;	1
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.01	kN	Max Punch ;	35

Tablet Data (N/A)

Total Counter :	4168114	Tablets			
A.W.C Counter :	4163537	Tablets			
HEP :	158 (0.0%)	Tablets	LEP :	99 (0.0%)	Tablets
GOOD :	4163280 (100.0%)	Tablets			