

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	SETRA 50 MG,STSH4A00
User ID :	yu98249	Batch NO. :	SHM2500350
Print Interval :	50000 Tablets	Running Time :	20 Hour 55 Min 21 Sec
Total Counter :	5418694	Total Running Time :	630 Hour 53 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	22	%	Manual ;	15	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		6000000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		30	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		15	Min	Supply Time ;	10.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		1.00	kN			
				Stop Condition ;		
HSP :	30.0 %	18.08	kN	No		
HEP :	25.0 %	17.38	kN	Yes	10	Rotations 15 Tablets
HCP :	2.0 %	14.18	kN	Yes	15	Times
Ref :		13.90	kN			
LCP :	2.0 %	13.63	kN	Yes	15	Times
LEP :	25.0 %	10.43	kN	Yes	10	Rotations 15 Tablets
LSP :	30.0 %	9.73	kN	No		
SD limit :	20.0 %			Yes		
Pre HSP		20.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	1.08	kN	Min :	1.02	kN	Punch NO.;	73
SD :	2.10	%	Max :	1.17	kN	Punch NO.;	35
Mean Main Pressure :	13.90	kN	Min :	12.71	kN	Punch NO.;	70
SD :	4.20	%	Max :	15.91	kN	Punch NO.;	35
Filling Depth :	Increase ;	375	Times	Decrease ;	401	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	258720	Tablets/hour
Feeder : Status ;	Auto		Speed ;	6	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	5.80	mm	Pre Thickness ;	2.81	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	4.51	mm	Main Thickness ;	1.52	mm
Filling Depth :	5.53	mm	Current Cam :	Cam B	
Main Air pressure :	0.794	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	25	Min			
Lower Punch Remain Time (S2):	10	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.20	kN		
	Max ;	0.26	kN	Max Punch ;	14
Lower Punch :	Average ;	0.09	kN		
	Max ;	0.11	kN	Max Punch ;	62
Ejection Force :	Average ;	0.07	kN		
	Max ;	0.11	kN	Max Punch ;	16

Tablet Data (N/A)

Total Counter :	5418694	Tablets			
A.W.C Counter :	5414094	Tablets			
HEP :	185 (0.0%)	Tablets	LEP :	99 (0.0%)	Tablets
GOOD :	5413810 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	SETRA 50 MG,STSH4A00
User ID :	yu98249	Batch NO. :	SHM2500350
Print Interval :	50000 Tablets	Running Time :	20 Hour 55 Min 21 Sec
Total Counter :	5418694	Total Running Time :	630 Hour 53 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	25	%	Manual ;	15	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		6000000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		30	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		15	Min	Supply Time ;	10.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		1.00	kN			
				Stop Condition ;		
HSP :	30.0 %	19.10	kN	No		
HEP :	25.0 %	18.36	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	14.99	kN	Yes 15	Times	
Ref :		14.69	kN			
LCP :	2.0 %	14.40	kN	Yes 15	Times	
LEP :	25.0 %	11.02	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	10.28	kN	No		
SD limit :	20.0 %			Yes		
Pre HSP		20.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	1.19	kN	Min :	1.15	kN	Punch NO.;	9
SD :	2.70	%	Max :	1.30	kN	Punch NO.;	2
Mean Main Pressure :	14.66	kN	Min :	13.55	kN	Punch NO.;	27
SD :	4.60	%	Max :	17.39	kN	Punch NO.;	76
Filling Depth :	Increase ;	174	Times	Decrease ;	214	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	258720	Tablets/hour
Feeder : Status ;	Auto		Speed ;	7	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	5.70	mm	Pre Thickness ;	2.71	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	4.64	mm	Main Thickness ;	1.64	mm
Filling Depth :	5.57	mm	Current Cam :	Cam B	
Main Air pressure :	0.794	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	25	Min			
Lower Punch Remain Time (S2):	10	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.20	kN		
	Max ;	0.26	kN	Max Punch ;	14
Lower Punch :	Average ;	0.09	kN		
	Max ;	0.11	kN	Max Punch ;	62
Ejection Force :	Average ;	0.07	kN		
	Max ;	0.13	kN	Max Punch ;	35

Tablet Data (N/A)

Total Counter :	5418694	Tablets			
A.W.C Counter :	5414094	Tablets			
HEP :	185 (0.0%)	Tablets	LEP :	99 (0.0%)	Tablets
GOOD :	5413810 (100.0%)	Tablets			