

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MET1000mg STYQ1A00
User ID :	vg96371	Batch NO. :	YQM2500910
Print Interval :	50000 Tablets	Running Time :	00 Hour 55 Min 56 Sec
Total Counter :	100044	Total Running Time :	633 Hour 46 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	120	%	Manual ;	24	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		2250000	Tablets			
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		45	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		30	Min	Supply Time ;	0.5	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		1.00	kN			
				Stop Condition ;		
HSP :	30.0 %	26.67	kN	No		
HEP :	25.0 %	25.65	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	20.93	kN	Yes 15	Times	
Ref :		20.52	kN			
LCP :	2.0 %	20.11	kN	Yes 15	Times	
LEP :	25.0 %	15.39	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	14.36	kN	No		
SD limit :	20.0 %			Yes		
Pre HSP		20.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	SD :	3.56	kN	Min :	3.31	kN	Punch NO.;	18
		3.00	%	Max :	3.79	kN	Punch NO.;	44
Mean Main Pressure :		20.85	kN	Min :	19.96	kN	Punch NO.;	21
	SD :	2.40	%	Max :	21.98	kN	Punch NO.;	44
Filling Depth :	Increase ;	18	Times	Decrease ;	25	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	17	RPM	Capacity :	108120	Tablets/hour
Feeder : Status ;	Auto		Speed ;	20	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	7.70	mm	Pre Thickness ;	4.71	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	6.64	mm	Main Thickness ;	3.64	mm
Filling Depth :	8.94	mm	Current Cam :	Cam C	
Main Air pressure :	0.801	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	24	Min			
Lower Punch Remain Time (S2):	9	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.05	kN		
	Max ;	0.14	kN	Max Punch ;	1
Lower Punch :	Average ;	0.08	kN		
	Max ;	0.09	kN	Max Punch ;	25
Ejection Force :	Average ;	0.04	kN		
	Max ;	0.06	kN	Max Punch ;	1

Tablet Data (N/A)

Total Counter :	100044	Tablets			
A.W.C Counter :	97452	Tablets			
HEP :	0 (0%)	Tablets	LEP :	100 (0.1%)	Tablets
GOOD :	97352 (99.9%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MET1000mg STYQ1A00
User ID :	vg96371	Batch NO. :	YQM2500910
Print Interval :	50000 Tablets	Running Time :	00 Hour 55 Min 56 Sec
Total Counter :	100044	Total Running Time :	633 Hour 46 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	120	%	Manual ;	15	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		2250000	Tablets			
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		45	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		30	Min	Supply Time ;	0.5	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		1.00	kN			
				Stop Condition ;		
HSP :	30.0 %	28.17	kN	No		
HEP :	25.0 %	27.09	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	22.10	kN	Yes 15	Times	
Ref :		21.67	kN			
LCP :	2.0 %	21.23	kN	Yes 15	Times	
LEP :	25.0 %	16.25	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	15.17	kN	No		
SD limit :	20.0 %			Yes		
Pre HSP		20.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	3.17	kN	Min :	3.00	kN	Punch NO.;	6
SD :	2.90	%	Max :	3.36	kN	Punch NO.;	26
Mean Main Pressure :	21.31	kN	Min :	20.50	kN	Punch NO.;	1
SD :	2.20	%	Max :	22.51	kN	Punch NO.;	26
Filling Depth :	Increase ; 15	Times	Decrease ; 19	Times			

PRODUCTION REPORT

Operation Value

Disk Speed :	17	RPM	Capacity :	108120	Tablets/hour
Feeder : Status ;	Auto		Speed ;	20	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	7.70	mm	Pre Thickness ;	4.71	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	6.64	mm	Main Thickness ;	3.65	mm
Filling Depth :	9.36	mm	Current Cam :	Cam C	
Main Air pressure :	0.801	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	24	Min			
Lower Punch Remain Time (S2):	9	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.05	kN		
	Max ;	0.13	kN	Max Punch ;	1
Lower Punch :	Average ;	0.08	kN		
	Max ;	0.09	kN	Max Punch ;	25
Ejection Force :	Average ;	0.04	kN		
	Max ;	0.06	kN	Max Punch ;	1

Tablet Data (N/A)

Total Counter :	100044	Tablets			
A.W.C Counter :	97452	Tablets			
HEP :	0 (0%)	Tablets	LEP :	100 (0.1%)	Tablets
GOOD :	97352 (99.9%)	Tablets			