

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MET1000mg STYQ1A00
User ID :	pb97604	Batch NO. :	YQM2501110
Print Interval :	50000 Tablets	Running Time :	08 Hour 17 Min 04 Sec
Total Counter :	1050434	Total Running Time :	682 Hour 27 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	120	%	Manual ;	40	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		2250000	Tablets			
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		60	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		30	Min	Supply Time ;	0.5	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		1.00	kN			
				Stop Condition ;		
HSP :	30.0 %	27.60	kN	No		
HEP :	25.0 %	26.54	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	21.66	kN	Yes 15	Times	
Ref :		21.23	kN			
LCP :	2.0 %	20.81	kN	Yes 15	Times	
LEP :	25.0 %	15.92	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	14.86	kN	No		
SD limit :	20.0 %			Yes		
Pre HSP		20.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	3.14	kN	Min :	2.99	kN	Punch NO.;	31
SD :	2.90	%	Max :	3.34	kN	Punch NO.;	22
Mean Main Pressure :	21.26	kN	Min :	20.08	kN	Punch NO.;	12
SD :	2.60	%	Max :	22.51	kN	Punch NO.;	22
Filling Depth :	Increase ; 41	Times	Decrease ; 58	Times			

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	127200	Tablets/hour
Feeder : Status ;	Auto		Speed ;	24	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	7.70	mm	Pre Thickness ;	4.71	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	6.64	mm	Main Thickness ;	3.65	mm
Filling Depth :	9.04	mm	Current Cam :	Cam C	
Main Air pressure :	0.789	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	7	Min			
Lower Punch Remain Time (S2):	7	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0
Lower Punch :	Average ;	0.09	kN		
	Max ;	0.10	kN	Max Punch ;	12
Ejection Force :	Average ;	0.04	kN		
	Max ;	0.13	kN	Max Punch ;	14

Tablet Data (N/A)

Total Counter :	1050434	Tablets			
A.W.C Counter :	1048588	Tablets			
HEP :	2 (0.0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	1048586 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MET1000mg STYQ1A00
User ID :	pb97604	Batch NO. :	YQM2501110
Print Interval :	50000 Tablets	Running Time :	08 Hour 17 Min 04 Sec
Total Counter :	1050434	Total Running Time :	682 Hour 27 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	120	%	Manual ;	40	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		2250000	Tablets			
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		60	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		30	Min	Supply Time ;	0.5	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		1.00	kN			
				Stop Condition ;		
HSP :	30.0 %	29.67	kN	No		
HEP :	25.0 %	28.53	kN	Yes	10	Rotations 15 Tablets
HCP :	2.0 %	23.28	kN	Yes	15	Times
Ref :		22.83	kN			
LCP :	2.0 %	22.37	kN	Yes	15	Times
LEP :	25.0 %	17.12	kN	Yes	10	Rotations 15 Tablets
LSP :	30.0 %	15.98	kN	No		
SD limit :	20.0 %			Yes		
Pre HSP		20.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	SD :	3.09	kN	Min :	2.87	kN	Punch NO.;	52
		3.10	%	Max :	3.36	kN	Punch NO.;	8
Mean Main Pressure :		22.76	kN	Min :	21.67	kN	Punch NO.;	5
	SD :	2.10	%	Max :	24.02	kN	Punch NO.;	8
Filling Depth :	Increase ;	27	Times	Decrease ;	34	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	127200	Tablets/hour
Feeder : Status ;	Auto		Speed ;	24	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	7.70	mm	Pre Thickness ;	4.71	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	6.64	mm	Main Thickness ;	3.65	mm
Filling Depth :	9.42	mm	Current Cam :	Cam C	
Main Air pressure :	0.789	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	7	Min			
Lower Punch Remain Time (S2):	7	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0
Lower Punch :	Average ;	0.09	kN		
	Max ;	0.10	kN	Max Punch ;	12
Ejection Force :	Average ;	0.04	kN		
	Max ;	0.13	kN	Max Punch ;	14

Tablet Data (N/A)

Total Counter :	1050434	Tablets			
A.W.C Counter :	1048588	Tablets			
HEP :	2 (0.0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	1048586 (100.0%)	Tablets			