

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MET1000mg STYQ1A00
User ID :	yu98249	Batch NO. :	YQM2501210
Print Interval :	50000 Tablets	Running Time :	13 Hour 48 Min 10 Sec
Total Counter :	1750688	Total Running Time :	705 Hour 41 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	115	%	Manual ;	40	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		2250000	Tablets			
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		60	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		30	Min	Supply Time ;	0.5	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		1.00	kN			
				Stop Condition ;		
HSP :	30.0 %	27.78	kN	No		
HEP :	25.0 %	26.71	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	21.80	kN	Yes 15	Times	
Ref :		21.37	kN			
LCP :	2.0 %	20.94	kN	Yes 15	Times	
LEP :	25.0 %	16.03	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	14.96	kN	No		
SD limit :	20.0 %			Yes		
Pre HSP		20.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	3.41	kN	Min :	3.13	kN	Punch NO.;	4
SD :	3.00	%	Max :	3.65	kN	Punch NO.;	37
Mean Main Pressure :	21.86	kN	Min :	20.29	kN	Punch NO.;	4
SD :	2.20	%	Max :	23.07	kN	Punch NO.;	49
Filling Depth :	Increase ; 249	Times	Decrease ;	261	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	127200	Tablets/hour
Feeder : Status ;	Auto		Speed ;	23	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	7.70	mm	Pre Thickness ;	4.71	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	6.64	mm	Main Thickness ;	3.65	mm
Filling Depth :	9.15	mm	Current Cam :	Cam C	
Main Air pressure :	0.743	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	6	Min			
Lower Punch Remain Time (S2):	6	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0
Lower Punch :	Average ;	0.09	kN		
	Max ;	0.10	kN	Max Punch ;	17
Ejection Force :	Average ;	0.05	kN		
	Max ;	0.13	kN	Max Punch ;	13

Tablet Data (N/A)

Total Counter :	1750688	Tablets			
A.W.C Counter :	1742827	Tablets			
HEP :	0 (0%)	Tablets	LEP :	113 (0.0%)	Tablets
GOOD :	1742714 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MET1000mg STYQ1A00
User ID :	yu98249	Batch NO. :	YQM2501210
Print Interval :	50000 Tablets	Running Time :	13 Hour 48 Min 10 Sec
Total Counter :	1750688	Total Running Time :	705 Hour 41 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	123	%	Manual ;	40	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		2250000	Tablets			
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		60	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		30	Min	Supply Time ;	0.5	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		1.00	kN			
				Stop Condition ;		
HSP :	30.0 %	27.95	kN	No		
HEP :	25.0 %	26.87	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	21.93	kN	Yes 15	Times	
Ref :		21.50	kN			
LCP :	2.0 %	21.07	kN	Yes 15	Times	
LEP :	25.0 %	16.12	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	15.05	kN	No		
SD limit :	20.0 %			Yes		
Pre HSP		20.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	3.40	kN	Min :	3.22	kN	Punch NO.;	31
SD :	3.00	%	Max :	3.66	kN	Punch NO.;	22
Mean Main Pressure :	21.80	kN	Min :	20.74	kN	Punch NO.;	31
SD :	2.50	%	Max :	23.26	kN	Punch NO.;	20
Filling Depth :	Increase ; 116	Times	Decrease ;	127	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	127200	Tablets/hour
Feeder : Status ;	Auto		Speed ;	25	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	7.70	mm	Pre Thickness ;	4.71	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	6.72	mm	Main Thickness ;	3.73	mm
Filling Depth :	9.56	mm	Current Cam :	Cam C	
Main Air pressure :	0.743	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	6	Min			
Lower Punch Remain Time (S2):	6	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.00	kN		
	Max ;	0.01	kN	Max Punch ;	36
Lower Punch :	Average ;	0.09	kN		
	Max ;	0.10	kN	Max Punch ;	17
Ejection Force :	Average ;	0.05	kN		
	Max ;	0.13	kN	Max Punch ;	13

Tablet Data (N/A)

Total Counter :	1750688	Tablets			
A.W.C Counter :	1742827	Tablets			
HEP :	0 (0%)	Tablets	LEP :	113 (0.0%)	Tablets
GOOD :	1742714 (100.0%)	Tablets			