

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	IBUPRO400MG STIU2B00
User ID :	pb97604	Batch NO. :	IUM2500140
Print Interval :	50000 Tablets	Running Time :	01 Hour 26 Min 02 Sec
Total Counter :	200068	Total Running Time :	711 Hour 20 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	198	%	Manual ;	66	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		2025000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		60	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		30	Min	Supply Time ;	0.5	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		1.00	kN			
				Stop Condition ;		
HSP :	30.0 %	24.15	kN	No		
HEP :	25.0 %	23.22	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	18.95	kN	Yes 15	Times	
Ref :		18.58	kN			
LCP :	2.0 %	18.21	kN	Yes 15	Times	
LEP :	25.0 %	13.93	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	13.00	kN	No		
SD limit :	20.0 %			Yes		
Pre HSP		20.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	0.58	kN	Min :	0.54	kN	Punch NO.;	25
SD :	3.00	%	Max :	0.63	kN	Punch NO.;	49
Mean Main Pressure :	19.03	kN	Min :	17.60	kN	Punch NO.;	50
SD :	4.20	%	Max :	20.84	kN	Punch NO.;	33
Filling Depth :	Increase ;	469	Times	Decrease ;	480	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	25	RPM	Capacity :	159000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	50	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	6.70	mm	Pre Thickness ;	3.71	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	4.50	mm	Main Thickness ;	1.51	mm
Filling Depth :	7.29	mm	Current Cam :	Cam C	
Main Air pressure :	0.800	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	46	Min			
Lower Punch Remain Time (S2):	16	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.00	kN		
	Max ;	0.01	kN	Max Punch ;	31
Lower Punch :	Average ;	0.13	kN		
	Max ;	0.21	kN	Max Punch ;	46
Ejection Force :	Average ;	0.03	kN		
	Max ;	0.05	kN	Max Punch ;	49

Tablet Data (N/A)

Total Counter :	200068	Tablets			
A.W.C Counter :	187258	Tablets			
HEP :	17 (0.0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	187241 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	IBUPRO400MG STIU2B00
User ID :	pb97604	Batch NO. :	IUM2500140
Print Interval :	50000 Tablets	Running Time :	01 Hour 26 Min 02 Sec
Total Counter :	200068	Total Running Time :	711 Hour 20 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	200	%	Manual ;	74	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		2025000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		60	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		30	Min	Supply Time ;	0.5	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		1.00	kN			
				Stop Condition ;		
HSP :	30.0 %	25.91	kN	No		
HEP :	25.0 %	24.91	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	20.33	kN	Yes 15	Times	
Ref :		19.93	kN			
LCP :	2.0 %	19.53	kN	Yes 15	Times	
LEP :	25.0 %	14.95	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	13.95	kN	No		
SD limit :	20.0 %			Yes		
Pre HSP		20.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	0.75	kN	Min :	0.69	kN	Punch NO.;	34
SD :	2.80	%	Max :	0.79	kN	Punch NO.;	13
Mean Main Pressure :	19.85	kN	Min :	18.62	kN	Punch NO.;	36
SD :	3.20	%	Max :	21.23	kN	Punch NO.;	53
Filling Depth :	Increase ;	230	Times	Decrease ;	247	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	25	RPM	Capacity :	159000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	50	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	6.70	mm	Pre Thickness ;	3.71	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	4.55	mm	Main Thickness ;	1.56	mm
Filling Depth :	7.00	mm	Current Cam :	Cam C	
Main Air pressure :	0.800	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	46	Min			
Lower Punch Remain Time (S2):	16	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.00	kN		
	Max ;	0.01	kN	Max Punch ;	31
Lower Punch :	Average ;	0.12	kN		
	Max ;	0.22	kN	Max Punch ;	46
Ejection Force :	Average ;	0.03	kN		
	Max ;	0.05	kN	Max Punch ;	49

Tablet Data (N/A)

Total Counter :	200068	Tablets			
A.W.C Counter :	187258	Tablets			
HEP :	17 (0.0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	187241 (100.0%)	Tablets			