

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	IBUPRO400MG STIU2B00
User ID :	pb97604	Batch NO. :	IUM2500140
Print Interval :	50000 Tablets	Running Time :	05 Hour 13 Min 15 Sec
Total Counter :	800272	Total Running Time :	715 Hour 7 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	195	%	Manual ;	66	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		2025000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		60	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		30	Min	Supply Time ;	0.5	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		2.00	kN			
Ejecting Force High Limit :		1.00	kN			
				Stop Condition ;		
HSP :	30.0 %	24.73	kN	No		
HEP :	25.0 %	23.77	kN	Yes 10	Rotations 15	Tablets
HCP :	3.0 %	19.59	kN	Yes 15	Times	
Ref :		19.02	kN			
LCP :	3.0 %	18.45	kN	Yes 15	Times	
LEP :	25.0 %	14.26	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	13.31	kN	No		
SD limit :	20.0 %			Yes		
Pre HSP		20.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	0.53	kN	Min :	0.48	kN	Punch NO.;	28
SD :	4.00	%	Max :	0.57	kN	Punch NO.;	43
Mean Main Pressure :	19.60	kN	Min :	18.00	kN	Punch NO.;	15
SD :	3.80	%	Max :	21.07	kN	Punch NO.;	41
Filling Depth :	Increase ;	890	Times	Decrease ;	875	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	25	RPM	Capacity :	159000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	49	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	6.70	mm	Pre Thickness ;	3.71	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	4.50	mm	Main Thickness ;	1.51	mm
Filling Depth :	6.82	mm	Current Cam :	Cam C 8.5-14mm	
Main Air pressure :	0.799	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	5	Min			
Lower Punch Remain Time (S2):	5	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0
Lower Punch :	Average ;	0.13	kN		
	Max ;	0.20	kN	Max Punch ;	34
Ejection Force :	Average ;	0.03	kN		
	Max ;	0.08	kN	Max Punch ;	17

Tablet Data (N/A)

Total Counter :	800272	Tablets			
A.W.C Counter :	785215	Tablets			
HEP :	246 (0.0%)	Tablets	LEP :	33 (0.0%)	Tablets
GOOD :	784936 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	IBUPRO400MG STIU2B00
User ID :	pb97604	Batch NO. :	IUM2500140
Print Interval :	50000 Tablets	Running Time :	05 Hour 13 Min 15 Sec
Total Counter :	800272	Total Running Time :	715 Hour 7 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	200	%	Manual ;	74	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		2025000	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		60	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		30	Min	Supply Time ;	0.5	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		2.00	kN			
Ejecting Force High Limit :		1.00	kN			
				Stop Condition ;		
HSP :	30.0 %	26.04	kN	No		
HEP :	25.0 %	25.04	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	20.43	kN	Yes 15	Times	
Ref :		20.03	kN			
LCP :	2.0 %	19.63	kN	Yes 15	Times	
LEP :	25.0 %	15.02	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	14.02	kN	No		
SD limit :	20.0 %			Yes		
Pre HSP		20.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	0.66	kN	Min :	0.61	kN	Punch NO.;	47
SD :	3.30	%	Max :	0.71	kN	Punch NO.;	33
Mean Main Pressure :	20.72	kN	Min :	19.14	kN	Punch NO.;	52
SD :	4.00	%	Max :	22.31	kN	Punch NO.;	11
Filling Depth :	Increase ;	541	Times	Decrease ;	517	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	25	RPM	Capacity :	159000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	50	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	6.70	mm	Pre Thickness ;	3.71	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	4.55	mm	Main Thickness ;	1.56	mm
Filling Depth :	7.50	mm	Current Cam :	Cam C	
Main Air pressure :	0.799	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	5	Min			
Lower Punch Remain Time (S2):	5	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0
Lower Punch :	Average ;	0.13	kN		
	Max ;	0.20	kN	Max Punch ;	34
Ejection Force :	Average ;	0.03	kN		
	Max ;	0.07	kN	Max Punch ;	17

Tablet Data (N/A)

Total Counter :	800272	Tablets			
A.W.C Counter :	785215	Tablets			
HEP :	246 (0.0%)	Tablets	LEP :	33 (0.0%)	Tablets
GOOD :	784936 (100.0%)	Tablets			