

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	Amioda 200mgSTAl3A00
User ID :	am98755	Batch NO. :	AIM2500220
Print Interval :	50000 Tablets	Running Time :	00 Hour 22 Min 56 Sec
Total Counter :	35914	Total Running Time :	724 Hour 34 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	102	%	Manual ;	20	RPM
Filling Cam :		Cam B		Cam Range :	Min :	2.50 mm
		4.5-10mm			Max :	8.00 mm
Target Quantity :		1500000	Tablets			
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		60	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		30	Min	Supply Time ;	0.5	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		1.00	kN			
				Stop Condition ;		
HSP :	30.0 %	21.81	kN	No		
HEP :	25.0 %	20.97	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	17.11	kN	Yes 15	Times	
Ref :		16.77	kN			
LCP :	2.0 %	16.44	kN	Yes 15	Times	
LEP :	25.0 %	12.58	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	11.74	kN	No		
SD limit :	20.0 %			Yes		
Pre HSP		20.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	1.47	kN	Min :	1.33	kN	Punch NO.;	37
SD :	5.30	%	Max :	1.67	kN	Punch NO.;	6
Mean Main Pressure :	16.11	kN	Min :	14.70	kN	Punch NO.;	37
SD :	4.10	%	Max :	17.74	kN	Punch NO.;	6
Filling Depth :	Increase ; 52	Times	Decrease ; 20	Times			

PRODUCTION REPORT

Operation Value

Disk Speed :	15	RPM	Capacity :	95400	Tablets/hour
Feeder : Status ;	Auto		Speed ;	15	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	5.00	mm	Pre Thickness ;	2.01	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	3.90	mm	Main Thickness ;	0.91	mm
Filling Depth :	6.05	mm	Current Cam :	Cam B	
Main Air pressure :	0.800	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	10	Min			
Lower Punch Remain Time (S2):	10	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	On	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.11	kN		
	Max ;	0.17	kN	Max Punch ;	52
Lower Punch :	Average ;	0.09	kN		
	Max ;	0.12	kN	Max Punch ;	42
Ejection Force :	Average ;	0.04	kN		
	Max ;	0.05	kN	Max Punch ;	18

Tablet Data (N/A)

Total Counter :	35914	Tablets			
A.W.C Counter :	28733	Tablets			
HEP :	111 (0.4%)	Tablets	LEP :	78 (0.3%)	Tablets
GOOD :	28544 (99.3%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name : VANTIX P720D User ID : am98755 Print Interval : 50000 Tablets Total Counter : 35914 Station : Station 2	Product Name : Amioda 200mgSTAl3A00 Batch NO. : AIM2500220 Running Time : 00 Hour 22 Min 56 Sec Total Running Time : 724 Hour 34 Min
---	---

Setting Value

Feeder :	Auto ;	90	%	Manual ;	25	RPM
Filling Cam :		Cam B		Cam Range :	Min :	2.50 mm
		4.5-10mm			Max :	8.00 mm
Target Quantity :		1500000	Tablets			
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		60	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		30	Min	Supply Time ;	0.5	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		1.00	kN			
				Stop Condition ;		
HSP :	30.0 %	23.45	kN	No		
HEP :	25.0 %	22.54	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	18.40	kN	Yes 15	Times	
Ref :		18.03	kN			
LCP :	2.0 %	17.67	kN	Yes 15	Times	
LEP :	25.0 %	13.53	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	12.62	kN	No		
SD limit :	20.0 %			Yes		
Pre HSP		20.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :		1.71	kN	Min :	1.54	kN	Punch NO.;	44
	SD :	4.80	%	Max :	1.95	kN	Punch NO.;	18
Mean Main Pressure :		18.19	kN	Min :	17.27	kN	Punch NO.;	53
	SD :	2.90	%	Max :	19.60	kN	Punch NO.;	18
Filling Depth :	Increase ;	34	Times	Decrease ;	25	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	15	RPM	Capacity :	95400	Tablets/hour
Feeder : Status ;	Auto		Speed ;	14	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	5.00	mm	Pre Thickness ;	2.01	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	3.96	mm	Main Thickness ;	0.97	mm
Filling Depth :	5.74	mm	Current Cam :	Cam B	
Main Air pressure :	0.800	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	10	Min			
Lower Punch Remain Time (S2):	10	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	On	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.11	kN		
	Max ;	0.17	kN	Max Punch ;	50
Lower Punch :	Average ;	0.09	kN		
	Max ;	0.12	kN	Max Punch ;	42
Ejection Force :	Average ;	0.04	kN		
	Max ;	0.05	kN	Max Punch ;	18

Tablet Data (N/A)

Total Counter :	35914	Tablets			
A.W.C Counter :	28733	Tablets			
HEP :	111 (0.4%)	Tablets	LEP :	78 (0.3%)	Tablets
GOOD :	28544 (99.3%)	Tablets			