

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	Amioda 200mgSTAl3A00
User ID :	mr99799	Batch NO. :	AIM2500220
Print Interval :	50000 Tablets	Running Time :	02 Hour 44 Min 05 Sec
Total Counter :	300130	Total Running Time :	726 Hour 56 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	110	%	Manual ;	20	RPM
Filling Cam :		Cam B		Cam Range :	Min :	2.50 mm
		4.5-10mm			Max :	8.00 mm
Target Quantity :		1500000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		60	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		30	Min	Supply Time ;	0.5	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		1.00	kN			
				Stop Condition ;		
HSP :	30.0 %	24.85	kN	No		
HEP :	25.0 %	23.89	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	19.49	kN	Yes 15	Times	
Ref :		19.11	kN			
LCP :	2.0 %	18.73	kN	Yes 15	Times	
LEP :	25.0 %	14.33	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	13.38	kN	No		
SD limit :	20.0 %			Yes		
Pre HSP		20.00	kN	Yes		
Mean Calculation range :	1 Rotations			Calculation Pass :	1	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	2.79	kN	Min :	2.55	kN	Punch NO.;	16
SD :	4.60	%	Max :	3.10	kN	Punch NO.;	39
Mean Main Pressure :	19.16	kN	Min :	17.74	kN	Punch NO.;	20
SD :	3.40	%	Max :	20.48	kN	Punch NO.;	44
Filling Depth :	Increase ;	315	Times	Decrease ;	291	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	18	RPM	Capacity :	0	Tablets/hour
Feeder : Status ;	Auto		Speed ;	20	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	4.70	mm	Pre Thickness ;	1.71	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	3.83	mm	Main Thickness ;	0.84	mm
Filling Depth :	5.80	mm	Current Cam :	Cam B	
Main Air pressure :	0.816	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	58	Min			
Lower Punch Remain Time (S2):	28	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.00	kN		
	Max ;	0.04	kN	Max Punch ;	1
Lower Punch :	Average ;	0.09	kN		
	Max ;	0.10	kN	Max Punch ;	5
Ejection Force :	Average ;	0.04	kN		
	Max ;	0.05	kN	Max Punch ;	5

Tablet Data (N/A)

Total Counter :	300130	Tablets			
A.W.C Counter :	287200	Tablets			
HEP :	346 (0.1%)	Tablets	LEP :	493 (0.2%)	Tablets
GOOD :	286361 (99.7%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	Amioda 200mgSTAI3A00
User ID :	mr99799	Batch NO. :	AIM2500220
Print Interval :	50000 Tablets	Running Time :	02 Hour 44 Min 05 Sec
Total Counter :	300130	Total Running Time :	726 Hour 56 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	100	%	Manual ;	25	RPM
Filling Cam :		Cam B		Cam Range :	Min :	2.50 mm
		4.5-10mm			Max :	8.00 mm
Target Quantity :		1500000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		60	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		30	Min	Supply Time ;	0.5	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		1.00	kN			
				Stop Condition ;		
HSP :	30.0 %	26.33	kN	No		
HEP :	25.0 %	25.32	kN	Yes	10	Rotations 15 Tablets
HCP :	2.0 %	20.66	kN	Yes	15	Times
Ref :		20.26	kN			
LCP :	2.0 %	19.85	kN	Yes	15	Times
LEP :	25.0 %	15.19	kN	Yes	10	Rotations 15 Tablets
LSP :	30.0 %	14.18	kN	No		
SD limit :	20.0 %			Yes		
Pre HSP		20.00	kN	Yes		
Mean Calculation range :	1	Rotations		Calculation Pass :	1	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	2.93	kN	Min :	2.49	kN	Punch NO.;	11
SD :	7.50	%	Max :	3.46	kN	Punch NO.;	18
Mean Main Pressure :	20.80	kN	Min :	19.10	kN	Punch NO.;	11
SD :	3.80	%	Max :	22.60	kN	Punch NO.;	18
Filling Depth :	Increase ;	323	Times	Decrease ;	321	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	18	RPM	Capacity :	0	Tablets/hour
Feeder : Status ;	Auto		Speed ;	18	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	4.70	mm	Pre Thickness ;	1.71	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	3.85	mm	Main Thickness ;	0.86	mm
Filling Depth :	5.99	mm	Current Cam :	Cam B 4.5-10mm	
Main Air pressure :	0.816	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	58	Min			
Lower Punch Remain Time (S2):	28	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.00	kN		
	Max ;	0.04	kN	Max Punch ;	53
Lower Punch :	Average ;	0.09	kN		
	Max ;	0.10	kN	Max Punch ;	5
Ejection Force :	Average ;	0.04	kN		
	Max ;	0.05	kN	Max Punch ;	5

Tablet Data (N/A)

Total Counter :	300130	Tablets			
A.W.C Counter :	287200	Tablets			
HEP :	346 (0.1%)	Tablets	LEP :	493 (0.2%)	Tablets
GOOD :	286361 (99.7%)	Tablets			