

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	Amioda 200mgSTAl3A00
User ID :	am98755	Batch NO. :	AIM2500220
Print Interval :	50000 Tablets	Running Time :	08 Hour 04 Min 55 Sec
Total Counter :	901862	Total Running Time :	732 Hour 16 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	96	%	Manual ;	20	RPM
Filling Cam :		Cam B		Cam Range :	Min :	2.50 mm
		4.5-10mm			Max :	8.00 mm
Target Quantity :		1500000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		25	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		30	Min	Supply Time ;	0.5	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		1.00	kN			
				Stop Condition ;		
HSP :	30.0 %	25.60	kN	No		
HEP :	25.0 %	24.62	kN	Yes 10	Rotations 15	Tablets
HCP :	2.5 %	20.19	kN	Yes 15	Times	
Ref :		19.70	kN			
LCP :	2.5 %	19.20	kN	Yes 15	Times	
LEP :	25.0 %	14.77	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	13.79	kN	No		
SD limit :	20.0 %			Yes		
Pre HSP		20.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	1	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	2.77	kN	Min :	2.54	kN	Punch NO.;	4
SD :	4.70	%	Max :	3.15	kN	Punch NO.;	44
Mean Main Pressure :	19.10	kN	Min :	17.99	kN	Punch NO.;	28
SD :	3.60	%	Max :	20.98	kN	Punch NO.;	44
Filling Depth :	Increase ; 347	Times	Decrease ;	361	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	17	RPM	Capacity :	108120	Tablets/hour
Feeder : Status ;	Auto		Speed ;	16	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	4.69	mm	Pre Thickness ;	1.70	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	3.83	mm	Main Thickness ;	0.84	mm
Filling Depth :	5.76	mm	Current Cam :	Cam B	
Main Air pressure :	0.797	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	20	Min			
Lower Punch Remain Time (S2):	15	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.03	kN		
	Max ;	0.07	kN	Max Punch ;	1
Lower Punch :	Average ;	0.10	kN		
	Max ;	0.13	kN	Max Punch ;	17
Ejection Force :	Average ;	0.04	kN		
	Max ;	0.07	kN	Max Punch ;	17

Tablet Data (N/A)

Total Counter :	901862	Tablets			
A.W.C Counter :	884283	Tablets			
HEP :	716 (0.1%)	Tablets	LEP :	558 (0.1%)	Tablets
GOOD :	883009 (99.9%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	Amioda 200mgSTAl3A00
User ID :	am98755	Batch NO. :	AIM2500220
Print Interval :	50000 Tablets	Running Time :	08 Hour 04 Min 55 Sec
Total Counter :	901862	Total Running Time :	732 Hour 16 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	90	%	Manual ;	32	RPM
Filling Cam :		Cam B		Cam Range :	Min :	2.50 mm
		4.5-10mm			Max :	8.00 mm
Target Quantity :		1500000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		25	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		30	Min	Supply Time ;	0.5	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		1.00	kN			
				Stop Condition ;		
HSP :	30.0 %	24.11	kN	No		
HEP :	25.0 %	23.18	kN	Yes 10	Rotations 15	Tablets
HCP :	2.5 %	19.01	kN	Yes 15	Times	
Ref :		18.54	kN			
LCP :	2.5 %	18.08	kN	Yes 15	Times	
LEP :	25.0 %	13.91	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	12.98	kN	No		
SD limit :	20.0 %			Yes		
Pre HSP		20.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	1	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	2.70	kN	Min :	2.43	kN	Punch NO.;	33
SD :	5.20	%	Max :	3.02	kN	Punch NO.;	44
Mean Main Pressure :	18.25	kN	Min :	17.10	kN	Punch NO.;	26
SD :	3.00	%	Max :	19.59	kN	Punch NO.;	49
Filling Depth :	Increase ; 298	Times	Decrease ;	297	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	17	RPM	Capacity :	108120	Tablets/hour
Feeder : Status ;	Auto		Speed ;	15	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	4.70	mm	Pre Thickness ;	1.71	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	3.94	mm	Main Thickness ;	0.95	mm
Filling Depth :	6.02	mm	Current Cam :	Cam B	
Main Air pressure :	0.797	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	20	Min			
Lower Punch Remain Time (S2):	15	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.03	kN		
	Max ;	0.08	kN	Max Punch ;	22
Lower Punch :	Average ;	0.10	kN		
	Max ;	0.13	kN	Max Punch ;	17
Ejection Force :	Average ;	0.04	kN		
	Max ;	0.07	kN	Max Punch ;	17

Tablet Data (N/A)

Total Counter :	901862	Tablets			
A.W.C Counter :	884283	Tablets			
HEP :	716 (0.1%)	Tablets	LEP :	558 (0.1%)	Tablets
GOOD :	883009 (99.9%)	Tablets			