

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	Amioda 200mgSTAl3A00
User ID :	am98755	Batch NO. :	AIM2500320
Print Interval :	50000 Tablets	Running Time :	04 Hour 05 Min 22 Sec
Total Counter :	456548	Total Running Time :	741 Hour 23 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	92	%	Manual ;	20	RPM
Filling Cam :		Cam B		Cam Range :	Min :	2.50 mm
		4.5-10mm			Max :	8.00 mm
Target Quantity :		1500000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		25	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		30	Min	Supply Time ;	0.5	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		1.00	kN			
				Stop Condition ;		
HSP :	30.0 %	20.41	kN	No		
HEP :	25.0 %	19.62	kN	Yes 10	Rotations 15	Tablets
HCP :	2.5 %	16.09	kN	Yes 15	Times	
Ref :		15.70	kN			
LCP :	2.5 %	15.31	kN	Yes 15	Times	
LEP :	25.0 %	11.77	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	10.99	kN	No		
SD limit :	20.0 %			Yes		
Pre HSP		20.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	1	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	2.86	kN	Min :	2.57	kN	Punch NO.;	11
SD :	5.10	%	Max :	3.22	kN	Punch NO.;	46
Mean Main Pressure :	15.77	kN	Min :	14.59	kN	Punch NO.;	15
SD :	3.90	%	Max :	17.34	kN	Punch NO.;	46
Filling Depth :	Increase ; 130	Times	Decrease ;	138	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	18	RPM	Capacity :	114480	Tablets/hour
Feeder : Status ;	Auto		Speed ;	17	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	4.69	mm	Pre Thickness ;	1.70	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	3.99	mm	Main Thickness ;	1.00	mm
Filling Depth :	5.20	mm	Current Cam :	Cam B	
Main Air pressure :	0.817	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	13	Min			
Lower Punch Remain Time (S2):	23	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	On	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.02	kN		
	Max ;	0.09	kN	Max Punch ;	52
Lower Punch :	Average ;	0.11	kN		
	Max ;	0.18	kN	Max Punch ;	1
Ejection Force :	Average ;	0.04	kN		
	Max ;	0.06	kN	Max Punch ;	17

Tablet Data (N/A)

Total Counter :	456548	Tablets			
A.W.C Counter :	445148	Tablets			
HEP :	36 (0.0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	445112 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	Amioda 200mgSTAl3A00
User ID :	am98755	Batch NO. :	AIM2500320
Print Interval :	50000 Tablets	Running Time :	04 Hour 05 Min 22 Sec
Total Counter :	456548	Total Running Time :	741 Hour 23 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	95	%	Manual ;	32	RPM
Filling Cam :		Cam B		Cam Range :	Min :	2.50 mm
		4.5-10mm			Max :	8.00 mm
Target Quantity :		1500000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		25	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		30	Min	Supply Time ;	0.5	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		1.00	kN			
				Stop Condition ;		
HSP :	30.0 %	18.93	kN	No		
HEP :	25.0 %	18.20	kN	Yes 10	Rotations 15	Tablets
HCP :	2.5 %	14.93	kN	Yes 15	Times	
Ref :		14.56	kN			
LCP :	2.5 %	14.20	kN	Yes 15	Times	
LEP :	25.0 %	10.92	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	10.19	kN	No		
SD limit :	20.0 %			Yes		
Pre HSP		20.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	1	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	2.56	kN	Min :	2.07	kN	Punch NO.;	15
SD :	9.70	%	Max :	3.22	kN	Punch NO.;	49
Mean Main Pressure :	13.83	kN	Min :	12.29	kN	Punch NO.;	15
SD :	5.50	%	Max :	15.80	kN	Punch NO.;	49
Filling Depth :	Increase ; 266	Times	Decrease ;	274	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	18	RPM	Capacity :	114480	Tablets/hour
Feeder : Status ;	Auto		Speed ;	17	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	4.70	mm	Pre Thickness ;	1.71	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	4.14	mm	Main Thickness ;	1.15	mm
Filling Depth :	5.45	mm	Current Cam :	Cam B	
Main Air pressure :	0.817	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	13	Min			
Lower Punch Remain Time (S2):	23	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	On	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.02	kN		
	Max ;	0.09	kN	Max Punch ;	52
Lower Punch :	Average ;	0.11	kN		
	Max ;	0.18	kN	Max Punch ;	1
Ejection Force :	Average ;	0.04	kN		
	Max ;	0.06	kN	Max Punch ;	17

Tablet Data (N/A)

Total Counter :	456548	Tablets			
A.W.C Counter :	445148	Tablets			
HEP :	36 (0.0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	445112 (100.0%)	Tablets			