

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	IBU 600MG STIU2C00
User ID :	rp98927	Batch NO. :	IUM2500560
Print Interval :	50000 Tablets	Running Time :	03 Hour 42 Min 59 Sec
Total Counter :	409542	Total Running Time :	754 Hour 21 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	260	%	Manual ;	20	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		1350000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		60	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		5	Min	Supply Time ;	0.5	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		1.00	kN			
				Stop Condition ;		
HSP :	30.0 %	32.91	kN	No		
HEP :	25.0 %	31.65	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	25.82	kN	Yes 15	Times	
Ref :		25.32	kN			
LCP :	2.0 %	24.81	kN	Yes 15	Times	
LEP :	25.0 %	18.99	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	17.72	kN	No		
SD limit :	20.0 %			Yes		
Pre HSP		20.00	kN	Yes		
Mean Calculation range :	1 Rotations			Calculation Pass :	1	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	3.99	kN	Min :	3.44	kN	Punch NO.;	43
SD :	7.20	%	Max :	4.73	kN	Punch NO.;	7
Mean Main Pressure :	24.44	kN	Min :	21.68	kN	Punch NO.;	43
SD :	5.90	%	Max :	27.57	kN	Punch NO.;	7
Filling Depth :	Increase ; 242	Times	Decrease ;	197	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	18	RPM	Capacity :	114480	Tablets/hour
Feeder : Status ;	Auto		Speed ;	47	RPM
Pre Upper Punch Position ;	2.00	mm			
Pre Lower Punch Position ;	6.50	mm	Pre Thickness ;	4.50	mm
Main Upper Punch Position ;	2.00	mm			
Main Lower Punch Position ;	5.48	mm	Main Thickness ;	3.48	mm
Filling Depth :	10.98	mm	Current Cam :	Cam C	
Main Air pressure :	0.803	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	37	Min			
Lower Punch Remain Time (S2):	4	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.01	kN		
	Max ;	0.10	kN	Max Punch ;	1
Lower Punch :	Average ;	0.21	kN		
	Max ;	0.39	kN	Max Punch ;	1
Ejection Force :	Average ;	0.06	kN		
	Max ;	0.14	kN	Max Punch ;	53

Tablet Data (N/A)

Total Counter :	409542	Tablets			
A.W.C Counter :	398616	Tablets			
HEP :	188 (0.0%)	Tablets	LEP :	275 (0.1%)	Tablets
GOOD :	398153 (99.9%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	IBU 600MG STIU2C00
User ID :	rp98927	Batch NO. :	IUM2500560
Print Interval :	50000 Tablets	Running Time :	03 Hour 42 Min 59 Sec
Total Counter :	409542	Total Running Time :	754 Hour 21 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	260	%	Manual ;	32	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		1350000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		60	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		5	Min	Supply Time ;	0.5	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		1.00	kN			
				Stop Condition ;		
HSP :	30.0 %	32.90	kN	No		
HEP :	25.0 %	31.63	kN	Yes	10	Rotations 15 Tablets
HCP :	2.0 %	25.81	kN	Yes	15	Times
Ref :		25.31	kN			
LCP :	2.0 %	24.80	kN	Yes	15	Times
LEP :	25.0 %	18.98	kN	Yes	10	Rotations 15 Tablets
LSP :	30.0 %	17.72	kN	No		
SD limit :	20.0 %			Yes		
Pre HSP		20.00	kN	Yes		
Mean Calculation range :	1	Rotations		Calculation Pass :	1	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	4.03	kN	Min :	3.65	kN	Punch NO.;	43
SD :	5.60	%	Max :	4.56	kN	Punch NO.;	7
Mean Main Pressure :	24.88	kN	Min :	22.64	kN	Punch NO.;	19
SD :	4.50	%	Max :	27.13	kN	Punch NO.;	7
Filling Depth :	Increase ;	129	Times	Decrease ;	91	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	18	RPM	Capacity :	114480	Tablets/hour
Feeder : Status ;	Auto		Speed ;	47	RPM
Pre Upper Punch Position ;	2.00	mm			
Pre Lower Punch Position ;	6.50	mm	Pre Thickness ;	4.50	mm
Main Upper Punch Position ;	2.00	mm			
Main Lower Punch Position ;	5.50	mm	Main Thickness ;	3.50	mm
Filling Depth :	10.93	mm	Current Cam :	Cam C	
Main Air pressure :	0.803	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	37	Min			
Lower Punch Remain Time (S2):	4	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.01	kN		
	Max ;	0.07	kN	Max Punch ;	1
Lower Punch :	Average ;	0.21	kN		
	Max ;	0.39	kN	Max Punch ;	1
Ejection Force :	Average ;	0.06	kN		
	Max ;	0.14	kN	Max Punch ;	53

Tablet Data (N/A)

Total Counter :	409542	Tablets			
A.W.C Counter :	398616	Tablets			
HEP :	188 (0.0%)	Tablets	LEP :	275 (0.1%)	Tablets
GOOD :	398153 (99.9%)	Tablets			