

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	IBU 600MG STIU2C00
User ID :	rp98927	Batch NO. :	IUM2500560
Print Interval :	50000 Tablets	Running Time :	09 Hour 38 Min 33 Sec
Total Counter :	1059762	Total Running Time :	760 Hour 17 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	272	%	Manual ;	20	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		1350000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		60	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		5	Min	Supply Time ;	0.5	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		1.00	kN			
				Stop Condition ;		
HSP :	30.0 %	33.91	kN	No		
HEP :	25.0 %	32.60	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	26.60	kN	Yes 15	Times	
Ref :		26.08	kN			
LCP :	2.0 %	25.56	kN	Yes 15	Times	
LEP :	25.0 %	19.56	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	18.26	kN	No		
SD limit :	20.0 %			Yes		
Pre HSP		20.00	kN	Yes		
Mean Calculation range :	1	Rotations		Calculation Pass :	1	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	4.38	kN	Min :	3.95	kN	Punch NO.;	21
SD :	5.30	%	Max :	4.89	kN	Punch NO.;	41
Mean Main Pressure :	26.54	kN	Min :	24.50	kN	Punch NO.;	8
SD :	5.10	%	Max :	29.46	kN	Punch NO.;	33
Filling Depth :	Increase ;	711	Times	Decrease ;	630	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	17	RPM	Capacity :	0	Tablets/hour
Feeder : Status ;	Auto		Speed ;	46	RPM
Pre Upper Punch Position ;	2.00	mm			
Pre Lower Punch Position ;	6.50	mm	Pre Thickness ;	4.50	mm
Main Upper Punch Position ;	2.00	mm			
Main Lower Punch Position ;	5.48	mm	Main Thickness ;	3.48	mm
Filling Depth :	9.96	mm	Current Cam :	Cam C 8.5-14mm	
Main Air pressure :	0.790	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	50	Min			
Lower Punch Remain Time (S2):	2	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	On		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.00	kN		
	Max ;	0.04	kN	Max Punch ;	53
Lower Punch :	Average ;	0.13	kN		
	Max ;	0.31	kN	Max Punch ;	47
Ejection Force :	Average ;	0.06	kN		
	Max ;	0.10	kN	Max Punch ;	47

Tablet Data (N/A)

Total Counter :	1059762	Tablets			
A.W.C Counter :	1047008	Tablets			
HEP :	728 (0.1%)	Tablets	LEP :	365 (0.0%)	Tablets
GOOD :	1045915 (99.9%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	IBU 600MG STIU2C00
User ID :	rp98927	Batch NO. :	IUM2500560
Print Interval :	50000 Tablets	Running Time :	09 Hour 38 Min 33 Sec
Total Counter :	1059762	Total Running Time :	760 Hour 17 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	274	%	Manual ;	32	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
Target Quantity :		8.5-14mm			Max :	12.00 mm
Air Pressure Low Limit :		1350000	Tablets			
Oil Lubrication :		0.400	MPa			
Upper Punch Interval Time(S1) ;		60	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		5	Min	Supply Time ;	0.5	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		1.00	kN			
				Stop Condition ;		
HSP :	30.0 %	34.33	kN	No		
HEP :	25.0 %	33.01	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	26.94	kN	Yes 15	Times	
Ref :		26.41	kN			
LCP :	2.0 %	25.88	kN	Yes 15	Times	
LEP :	25.0 %	19.81	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	18.49	kN	No		
SD limit :	20.0 %			Yes		
Pre HSP		20.00	kN	Yes		
Mean Calculation range :	1	Rotations		Calculation Pass :	1	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	4.05	kN	Min :	3.70	kN	Punch NO.;	16
SD :	5.40	%	Max :	4.70	kN	Punch NO.;	39
Mean Main Pressure :	26.37	kN	Min :	24.07	kN	Punch NO.;	42
SD :	4.10	%	Max :	29.06	kN	Punch NO.;	39
Filling Depth :	Increase ;	473	Times	Decrease ;	397	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	17	RPM	Capacity :	0	Tablets/hour
Feeder : Status ;	Auto		Speed ;	47	RPM
Pre Upper Punch Position ;	2.00	mm			
Pre Lower Punch Position ;	6.50	mm	Pre Thickness ;	4.50	mm
Main Upper Punch Position ;	2.00	mm			
Main Lower Punch Position ;	5.50	mm	Main Thickness ;	3.50	mm
Filling Depth :	10.44	mm	Current Cam :	Cam C 8.5-14mm	
Main Air pressure :	0.790	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	50	Min			
Lower Punch Remain Time (S2):	2	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	On		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	53
Lower Punch :	Average ;	0.13	kN		
	Max ;	0.31	kN	Max Punch ;	47
Ejection Force :	Average ;	0.06	kN		
	Max ;	0.10	kN	Max Punch ;	47

Tablet Data (N/A)

Total Counter :	1059762	Tablets			
A.W.C Counter :	1047008	Tablets			
HEP :	728 (0.1%)	Tablets	LEP :	365 (0.0%)	Tablets
GOOD :	1045915 (99.9%)	Tablets			