

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	SETRA50MG STSH4A00
User ID :	yd98913	Batch NO. :	SHM2500450
Print Interval :	50000 Tablets	Running Time :	00 Hour 12 Min 16 Sec
Total Counter :	50052	Total Running Time :	763 Hour 12 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	22	%	Manual ;	12	RPM
Filling Cam :		Cam B		Cam Range :	Min :	2.50 mm
		4.5-10mm			Max :	8.00 mm
Target Quantity :		6000000	Tablets			
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		30	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		5	Min	Supply Time ;	0.5	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		1.00	kN			
				Stop Condition ;		
HSP :	30.0 %	16.31	kN	No		
HEP :	25.0 %	15.69	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	12.80	kN	Yes 15	Times	
Ref :		12.55	kN			
LCP :	2.0 %	12.30	kN	Yes 15	Times	
LEP :	25.0 %	9.41	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	8.78	kN	No		
SD limit :	20.0 %			Yes		
Pre HSP		20.00	kN	Yes		
Mean Calculation range :	1	Rotations		Calculation Pass :	1	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	1.08	kN	Min :	1.02	kN	Punch NO.;	14
SD :	2.50	%	Max :	1.16	kN	Punch NO.;	75
Mean Main Pressure :	12.60	kN	Min :	11.16	kN	Punch NO.;	15
SD :	4.40	%	Max :	13.63	kN	Punch NO.;	73
Filling Depth :	Increase ; 2	Times	Decrease ;	17	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	258720	Tablets/hour
Feeder : Status ;	Auto		Speed ;	6	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	5.60	mm	Pre Thickness ;	2.61	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	4.40	mm	Main Thickness ;	1.41	mm
Filling Depth :	5.22	mm	Current Cam :	Cam B	
Main Air pressure :	0.806	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	21	Min			
Lower Punch Remain Time (S2):	4	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.30	kN		
	Max ;	0.42	kN	Max Punch ;	47
Lower Punch :	Average ;	0.07	kN		
	Max ;	0.12	kN	Max Punch ;	39
Ejection Force :	Average ;	0.05	kN		
	Max ;	0.12	kN	Max Punch ;	29

Tablet Data (N/A)

Total Counter :	50052	Tablets			
A.W.C Counter :	43874	Tablets			
HEP :	0 (0%)	Tablets	LEP :	33 (0.1%)	Tablets
GOOD :	43841 (99.9%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	SETRA50MG STSH4A00
User ID :	yd98913	Batch NO. :	SHM2500450
Print Interval :	50000 Tablets	Running Time :	00 Hour 12 Min 16 Sec
Total Counter :	50052	Total Running Time :	763 Hour 12 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	22	%	Manual ;	12	RPM
Filling Cam :		Cam B		Cam Range :	Min :	2.50 mm
		4.5-10mm			Max :	8.00 mm
Target Quantity :		6000000	Tablets			
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		30	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		5	Min	Supply Time ;	0.5	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		1.00	kN			
				Stop Condition ;		
HSP :	30.0 %	16.07	kN	No		
HEP :	25.0 %	15.45	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	12.61	kN	Yes 15	Times	
Ref :		12.36	kN			
LCP :	2.0 %	12.12	kN	Yes 15	Times	
LEP :	25.0 %	9.27	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	8.65	kN	No		
SD limit :	20.0 %			Yes		
Pre HSP		20.00	kN	Yes		
Mean Calculation range :	1	Rotations		Calculation Pass :	1	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	1.25	kN	Min :	1.20	kN	Punch NO.;	16
SD :	1.80	%	Max :	1.31	kN	Punch NO.;	60
Mean Main Pressure :	12.25	kN	Min :	11.08	kN	Punch NO.;	50
SD :	3.00	%	Max :	13.02	kN	Punch NO.;	67
Filling Depth :	Increase ;	5	Times	Decrease ;	4	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	258720	Tablets/hour
Feeder : Status ;	Auto		Speed ;	6	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	5.60	mm	Pre Thickness ;	2.61	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	4.50	mm	Main Thickness ;	1.51	mm
Filling Depth :	5.35	mm	Current Cam :	Cam B	
Main Air pressure :	0.806	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	21	Min			
Lower Punch Remain Time (S2):	4	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.30	kN		
	Max ;	0.41	kN	Max Punch ;	47
Lower Punch :	Average ;	0.07	kN		
	Max ;	0.12	kN	Max Punch ;	39
Ejection Force :	Average ;	0.05	kN		
	Max ;	0.12	kN	Max Punch ;	29

Tablet Data (N/A)

Total Counter :	50052	Tablets			
A.W.C Counter :	43874	Tablets			
HEP :	0 (0%)	Tablets	LEP :	33 (0.1%)	Tablets
GOOD :	43841 (99.9%)	Tablets			