

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	SETRA50MG STSH4A00
User ID :	yd98913	Batch NO. :	SHM2500450
Print Interval :	50000 Tablets	Running Time :	00 Hour 23 Min 53 Sec
Total Counter :	100122	Total Running Time :	763 Hour 23 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	22	%	Manual ;	12	RPM
Filling Cam :		Cam B		Cam Range :	Min :	2.50 mm
		4.5-10mm			Max :	8.00 mm
Target Quantity :		6000000	Tablets			
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		30	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		10	Min	Supply Time ;	0.5	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		1.00	kN			
				Stop Condition ;		
HSP :	30.0 %	16.31	kN	No		
HEP :	25.0 %	15.69	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	12.80	kN	Yes 15	Times	
Ref :		12.55	kN			
LCP :	2.0 %	12.30	kN	Yes 15	Times	
LEP :	25.0 %	9.41	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	8.78	kN	No		
SD limit :	20.0 %			Yes		
Pre HSP		20.00	kN	Yes		
Mean Calculation range :	1 Rotations			Calculation Pass :	1	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	1.07	kN	Min :	1.00	kN	Punch NO.;	25
SD :	2.50	%	Max :	1.14	kN	Punch NO.;	35
Mean Main Pressure :	12.50	kN	Min :	11.46	kN	Punch NO.;	26
SD :	4.10	%	Max :	13.97	kN	Punch NO.;	35
Filling Depth :	Increase ; 2	Times	Decrease ;	17	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	258720	Tablets/hour
Feeder : Status ;	Auto		Speed ;	6	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	5.60	mm	Pre Thickness ;	2.61	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	4.40	mm	Main Thickness ;	1.41	mm
Filling Depth :	5.22	mm	Current Cam :	Cam B	
Main Air pressure :	0.750	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	10	Min			
Lower Punch Remain Time (S2):	3	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.20	kN		
	Max ;	0.26	kN	Max Punch ;	16
Lower Punch :	Average ;	0.07	kN		
	Max ;	0.13	kN	Max Punch ;	66
Ejection Force :	Average ;	0.05	kN		
	Max ;	0.12	kN	Max Punch ;	33

Tablet Data (N/A)

Total Counter :	100122	Tablets			
A.W.C Counter :	94001	Tablets			
HEP :	0 (0%)	Tablets	LEP :	33 (0.0%)	Tablets
GOOD :	93968 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	SETRA50MG STSH4A00
User ID :	yd98913	Batch NO. :	SHM2500450
Print Interval :	50000 Tablets	Running Time :	00 Hour 23 Min 53 Sec
Total Counter :	100122	Total Running Time :	763 Hour 23 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	22	%	Manual ;	12	RPM
Filling Cam :		Cam B		Cam Range :	Min :	2.50 mm
		4.5-10mm			Max :	8.00 mm
Target Quantity :		6000000	Tablets			
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		30	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		10	Min	Supply Time ;	0.5	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		1.00	kN			
				Stop Condition ;		
HSP :	30.0 %	16.07	kN	No		
HEP :	25.0 %	15.45	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	12.61	kN	Yes 15	Times	
Ref :		12.36	kN			
LCP :	2.0 %	12.12	kN	Yes 15	Times	
LEP :	25.0 %	9.27	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	8.65	kN	No		
SD limit :	20.0 %			Yes		
Pre HSP		20.00	kN	Yes		
Mean Calculation range :	1	Rotations		Calculation Pass :	1	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	1.25	kN	Min :	1.19	kN	Punch NO.;	9
SD :	1.80	%	Max :	1.30	kN	Punch NO.;	18
Mean Main Pressure :	12.29	kN	Min :	11.56	kN	Punch NO.;	46
SD :	3.00	%	Max :	13.28	kN	Punch NO.;	61
Filling Depth :	Increase ;	13	Times	Decrease ;	8	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	258720	Tablets/hour
Feeder : Status ;	Auto		Speed ;	6	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	5.60	mm	Pre Thickness ;	2.61	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	4.50	mm	Main Thickness ;	1.51	mm
Filling Depth :	5.47	mm	Current Cam :	Cam B	
Main Air pressure :	0.750	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	10	Min			
Lower Punch Remain Time (S2):	3	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.20	kN		
	Max ;	0.26	kN	Max Punch ;	16
Lower Punch :	Average ;	0.07	kN		
	Max ;	0.11	kN	Max Punch ;	66
Ejection Force :	Average ;	0.05	kN		
	Max ;	0.13	kN	Max Punch ;	33

Tablet Data (N/A)

Total Counter :	100122	Tablets			
A.W.C Counter :	94001	Tablets			
HEP :	0 (0%)	Tablets	LEP :	33 (0.0%)	Tablets
GOOD :	93968 (100.0%)	Tablets			