

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	SETRA50MG STSH4A00
User ID :	pn98247	Batch NO. :	SHM2500450
Print Interval :	50000 Tablets	Running Time :	04 Hour 50 Min 48 Sec
Total Counter :	1250776	Total Running Time :	767 Hour 51 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	18	%	Manual ;	12	RPM
Filling Cam :		Cam B		Cam Range :	Min :	2.50 mm
		4.5-10mm			Max :	8.00 mm
Target Quantity :		6000000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		30	Min	Supply Time ;	2.0	Sec
Lower Punch Interval Time(S2) ;		5	Min	Supply Time ;	4.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		1.00	kN			
				Stop Condition ;		
HSP :	30.0 %	18.60	kN	No		
HEP :	25.0 %	17.89	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	14.60	kN	Yes 15	Times	
Ref :		14.31	kN			
LCP :	2.0 %	14.02	kN	Yes 15	Times	
LEP :	25.0 %	10.73	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	10.02	kN	No		
SD limit :	20.0 %			Yes		
Pre HSP		20.00	kN	Yes		
Mean Calculation range :	1 Rotations			Calculation Pass :	1	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	1.10	kN	Min :	1.03	kN	Punch NO.;	14
SD :	2.50	%	Max :	1.19	kN	Punch NO.;	75
Mean Main Pressure :	14.18	kN	Min :	13.04	kN	Punch NO.;	5
SD :	4.00	%	Max :	15.84	kN	Punch NO.;	75
Filling Depth :	Increase ; 269	Times	Decrease ;	298	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	258720	Tablets/hour
Feeder : Status ;	Auto		Speed ;	5	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	5.60	mm	Pre Thickness ;	2.61	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	4.50	mm	Main Thickness ;	1.51	mm
Filling Depth :	6.06	mm	Current Cam :	Cam B	
Main Air pressure :	0.684	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	17	Min			
Lower Punch Remain Time (S2):	1	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.08	kN		
	Max ;	0.14	kN	Max Punch ;	4
Lower Punch :	Average ;	0.08	kN		
	Max ;	0.09	kN	Max Punch ;	17
Ejection Force :	Average ;	0.08	kN		
	Max ;	0.13	kN	Max Punch ;	33

Tablet Data (N/A)

Total Counter :	1250776	Tablets			
A.W.C Counter :	1242669	Tablets			
HEP :	5 (0.0%)	Tablets	LEP :	35 (0.0%)	Tablets
GOOD :	1242629 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	SETRA50MG STSH4A00
User ID :	pn98247	Batch NO. :	SHM2500450
Print Interval :	50000 Tablets	Running Time :	04 Hour 50 Min 48 Sec
Total Counter :	1250776	Total Running Time :	767 Hour 51 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	18	%	Manual ;	12	RPM
Filling Cam :		Cam B		Cam Range :	Min :	2.50 mm
Target Quantity :		4.5-10mm			Max :	8.00 mm
Air Pressure Low Limit :		6000000	Tablets			
Oil Lubrication :		0.400	MPa			
Upper Punch Interval Time(S1) ;		30	Min	Supply Time ;	2.0	Sec
Lower Punch Interval Time(S2) ;		5	Min	Supply Time ;	4.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		1.00	kN			
				Stop Condition ;		
HSP :	30.0 %	17.04	kN	No		
HEP :	25.0 %	16.38	kN	Yes	10	Rotations
HCP :	2.0 %	13.37	kN	Yes	15	Times
Ref :		13.11	kN			
LCP :	2.0 %	12.84	kN	Yes	15	Times
LEP :	25.0 %	9.83	kN	Yes	10	Rotations
LSP :	30.0 %	9.17	kN	No		
SD limit :	20.0 %			Yes		
Pre HSP		20.00	kN	Yes		
Mean Calculation range :	1	Rotations		Calculation Pass :	1	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	1.22	kN	Min :	1.17	kN	Punch NO.;	21
SD :	1.80	%	Max :	1.27	kN	Punch NO.;	39
Mean Main Pressure :	13.04	kN	Min :	11.91	kN	Punch NO.;	71
SD :	3.10	%	Max :	14.00	kN	Punch NO.;	56
Filling Depth :	Increase ;	124	Times	Decrease ;	113	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	258720	Tablets/hour
Feeder : Status ;	Auto		Speed ;	5	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	5.60	mm	Pre Thickness ;	2.61	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	4.54	mm	Main Thickness ;	1.55	mm
Filling Depth :	5.93	mm	Current Cam :	Cam B	
Main Air pressure :	0.684	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	17	Min			
Lower Punch Remain Time (S2):	1	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.08	kN		
	Max ;	0.13	kN	Max Punch ;	16
Lower Punch :	Average ;	0.08	kN		
	Max ;	0.09	kN	Max Punch ;	17
Ejection Force :	Average ;	0.08	kN		
	Max ;	0.13	kN	Max Punch ;	33

Tablet Data (N/A)

Total Counter :	1250776	Tablets			
A.W.C Counter :	1242669	Tablets			
HEP :	5 (0.0%)	Tablets	LEP :	35 (0.0%)	Tablets
GOOD :	1242629 (100.0%)	Tablets			